1012[™] IEEE Standard for Software Verification and Validation

IEEE Computer Society

Sponsored by the Software Engineering Standards Committee



3 Park Avenue, New York, NY10016-5997, USA

8 June 2005 Print: SH95308 PDF: SS95308

IEEE Standard for Software Verification and Validation

Sponsor

Software Engineering Standards Committee of the IEEE Computer Society

Approved 12 April 2005

American National Standards Institute

Approved 8 December 2004

IEEE-SA Standards Board

Abstract: Software verification and validation (V&V) processes determine whether the development products of a given activity conform to the requirements of that activity and whether the software satisfies its intended use and user needs. Software V&V life cycle process requirements are specified for different software integrity levels. The scope of V&V processes encompasses software-based systems, computer software, hardware, and interfaces. This standard applies to software being developed, maintained, or reused [legacy, commercial off-the-shelf (COTS), non-developmental items]. The term software also includes firmware, microcode, and documentation. Software V&V processes include analysis, evaluation, review, inspection, assessment, and testing of software products.

Keywords: IV&V, software integrity level, software life cycle, V&V, validation, verification

Print: ISBN 0-7381-4641-2 SH95308 PDF: ISBN 0-7381-4642-0 SS95308

The Institute of Electrical and Electronics Engineers, Inc.

³ Park Avenue, New York, NY 10016-5997, USA

Copyright © 2005 by the Institute of Electrical and Electronics Engineers, Inc. All rights reserved. Published 8 June 2005. Printed in the United States of America.

IEEE is a registered trademark in the U.S. Patent & Trademark Office, owned by the Institute of Electrical and Electronics Engineers, Incorporated.

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without the prior written permission of the publisher.

IEEE Standards documents are developed within the IEEE Societies and the Standards Coordinating Committees of the IEEE Standards Association (IEEE-SA) Standards Board. The IEEE develops its standards through a consensus development process, approved by the American National Standards Institute, which brings together volunteers representing varied viewpoints and interests to achieve the final product. Volunteers are not necessarily members of the Institute and serve without compensation. While the IEEE administers the process and establishes rules to promote fairness in the consensus development process, the IEEE does not independently evaluate, test, or verify the accuracy of any of the information contained in its standards.

Use of an IEEE Standard is wholly voluntary. The IEEE disclaims liability for any personal injury, property or other damage, of any nature whatsoever, whether special, indirect, consequential, or compensatory, directly or indirectly resulting from the publication, use of, or reliance upon this, or any other IEEE Standard document.

The IEEE does not warrant or represent the accuracy or content of the material contained herein, and expressly disclaims any express or implied warranty, including any implied warranty of merchantability or fitness for a specific purpose, or that the use of the material contained herein is free from patent infringement. IEEE Standards documents are supplied "AS IS."

The existence of an IEEE Standard does not imply that there are no other ways to produce, test, measure, purchase, market, or provide other goods and services related to the scope of the IEEE Standard. Furthermore, the viewpoint expressed at the time a standard is approved and issued is subject to change brought about through developments in the state of the art and comments received from users of the standard. Every IEEE Standard is subjected to review at least every five years for revision or reaffirmation. When a document is more than five years old and has not been reaffirmed, it is reasonable to conclude that its contents, although still of some value, do not wholly reflect the present state of the art. Users are cautioned to check to determine that they have the latest edition of any IEEE Standard.

In publishing and making this document available, the IEEE is not suggesting or rendering professional or other services for, or on behalf of, any person or entity. Nor is the IEEE undertaking to perform any duty owed by any other person or entity to another. Any person utilizing this, and any other IEEE Standards document, should rely upon the advice of a competent professional in determining the exercise of reasonable care in any given circumstances.

Interpretations: Occasionally questions may arise regarding the meaning of portions of standards as they relate to specific applications. When the need for interpretations is brought to the attention of IEEE, the Institute will initiate action to prepare appropriate responses. Since IEEE Standards represent a consensus of concerned interests, it is important to ensure that any interpretation has also received the concurrence of a balance of interests. For this reason, IEEE and the members of its societies and Standards Coordinating Committees are not able to provide an instant response to interpretation requests except in those cases where the matter has previously received formal consideration. At lectures, symposia, seminars, or educational courses, an individual presenting information on IEEE standards shall make it clear that his or her views should be considered the personal views of that individual rather than the formal position, explanation, or interpretation of the IEEE.

Comments for revision of IEEE Standards are welcome from any interested party, regardless of membership affiliation with IEEE. Suggestions for changes in documents should be in the form of a proposed change of text, together with appropriate supporting comments. Comments on standards and requests for interpretations should be addressed to:

Secretary, IEEE-SA Standards Board

Piscataway, NJ 08854

USA

NOTE-Attention is called to the possibility that implementation of this standard may require use of subject matter covered by patent rights. By publication of this standard, no position is taken with respect to the existence or validity of any patent rights in connection therewith. The IEEE shall not be responsible for identifying patents for which a license may be required by an IEEE standard or for conducting inquiries into the legal validity or scope of those patents that are brought to its attention.

Authorization to photocopy portions of any individual standard for internal or personal use is granted by the Institute of Electrical and Electronics Engineers, Inc., provided that the appropriate fee is paid to Copyright Clearance Center. To arrange for payment of licensing fee, please contact Copyright Clearance Center, Customer Service, 222 Rosewood Drive, Danvers, MA 01923 USA; +1 978 750 8400. Permission to photocopy portions of any individual standard for educational classroom use can also be obtained through the Copyright Clearance Center.

⁴⁴⁵ Hoes Lane

Introduction

This introduction is not part of IEEE Std 1012-2004, IEEE Standard for Software Verification and Validation.

Software verification and validation (V&V) is a technical discipline of systems engineering. The purpose of software V&V is to help the development organization build quality into the software during the software life cycle. V&V processes provide an objective assessment of software products and processes throughout the software life cycle. This assessment demonstrates whether the software requirements and system requirements (i.e., those allocated to software) are correct, complete, accurate, consistent, and testable. The software V&V processes determine whether the development products of a given activity conform to the requirements of that activity and whether the software satisfies its intended use and user needs. The determination includes assessment, analysis, evaluation, review, inspection, and testing of software products and processes. Software V&V is performed in parallel with software development, not at the conclusion of the development effort.

Software V&V is an extension of program management and systems engineering that employs a rigorous methodology to identify objective data and conclusions to provide feedback about software quality, performance, and schedule to the development organization. This feedback consists of anomaly resolutions, performance improvements, and quality improvements not only for expected operating conditions, but also across the full spectrum of the system and its interfaces. Early feedback results allow the development organization to modify the software products in a timely fashion and thereby reduce overall project and schedule impacts. Without a proactive approach, anomalies and associated software system changes are typically delayed to later in the program schedule, resulting in greater program costs and schedule delays.

IEEE Std 1012-2004 is a process standard that defines the V&V processes in terms of specific activities and related tasks. The standard also defines the contents of the *software v&v plan* (SVVP), including an example format.

This version of the standard contains minor changes to IEEE Std 1012-1998. Following is a summary:

- a) Revised Clause 1 to conform to IEEE style and
 - 1) Moved the description of the verification process and validation process from 1.3 to 1.1.
 - 2) Expanded 1.2 to discuss the importance of performing the software V&V from a systems perspective—software and its interaction with the system of which it is a part.
- b) Moved Figure 3 into the definition of V&V effort (see 3.1.37) with no figure reference.
- c) Clarified Clause 4 concept of software integrity and selection of software integrity levels.
- d) Revised Clause 6 to contain all of the normative documentation requirements (see 6.1) that were in Clause 7.
- e) Revised Clause 7 to consolidate IEEE 1012A[™]-1998 [B6] into the revision of this standard.
- f) Revised Table 1 as follows:
 - 1) Added "security analysis" to the required V&V tasks.
 - 2) Reformatted test tasks to uniquely identify requirements for each test type—no normative changes were made to the test tasks.
 - 3) Added a subtask to the "scoping of V&V" in the Acquisition support V&V activity to determine the extent of V&V on reused software.
 - 4) Corrected previous editorial errors.
- g) Added mapping of IEEE 1012 tasks to CMMI Engineering Process Groups in Annex A.
- h) Added a definition of integrated independent V&V (IV&V) to Annex C.
- i) Clarified treatment of reuse software in Annex D.
- j) Added sample measures to Annex E.
- k) Removed Annex I and moved the definitions into 3.1.

The following key concepts are emphasized in this standard:

- *Software integrity levels.* Defines four software integrity levels to describe the importance of the software, varying from high integrity to low integrity, to the user.
- Minimum V&V tasks for each software integrity level. Defines the minimum V&V tasks required for each of the four software integrity levels. Includes a table of optional V&V tasks for tailoring the V&V effort to address project needs and application specific characteristics.
- Intensity and rigor applied to V&V tasks. Introduces the notion that the intensity and rigor applied to the V&V tasks vary according to the software integrity level. Higher software integrity levels require the application of greater intensity and rigor to the V&V task. Intensity includes greater scope of analysis across all normal and abnormal system operating conditions. Rigor includes more formal techniques and recording procedures.
- Detailed criteria for V&V tasks. Defines specific criteria for each V&V task, including minimum criteria for correctness, consistency, completeness, accuracy, readability, and testability. The V&V task descriptions include a list of the required task inputs and outputs.
- Systems viewpoints. Includes minimum V&V tasks to address system issues. These tasks include hazard analysis, security analysis, risk analysis, migration assessment, and retirement assessment. Specific system issues are contained in individual V&V task criteria.
- Conformance to international and IEEE standards. Defines the V&V processes to conform to life cycle process standards such as ISO/IEC Std 12207:1995 [B13], IEEE Std 1074[™]-1997 [B10], and IEEE/EIA Std 12207.0[™]-1996 [B12], as well as the entire family of IEEE software engineering standards. This standard addresses the full software life cycle processes, including acquisition, supply, development, operation, and maintenance. This standard is compatible with all life cycle models; however, not all life cycle models use all of the life cycle processes described in this standard.

Notice to users

Errata

Errata, if any, for this and all other standards can be accessed at the following URL: <u>http://</u><u>standards.ieee.org/reading/ieee/updates/errata/index.html.</u> Users are encouraged to check this URL for errata periodically.

Interpretations

Current interpretations can be accessed at the following URL: <u>http://standards.ieee.org/reading/ieee/interp/index.html.</u>

Patents

Attention is called to the possibility that implementation of this standard may require use of subject matter covered by patent rights. By publication of this standard, no position is taken with respect to the existence or validity of any patent rights in connection therewith. The IEEE shall not be responsible for identifying patents or patent applications for which a license may be required to implement an IEEE standard or for conducting inquiries into the legal validity or scope of those patents that are brought to its attention.

Participants

At the time this standard was completed, the Software Verification and Validation Working Group had the following membership:

Roger U. Fujii, Chair Dolores R. Wallace, Vice Chair David H. Daniel, Secretary

John W. Bradbury Paul R. Croll H. Taz Daughtrey Harpal S. Dhama Michael Edwards Uma D. Ferrell Eva Freund Ron K. Greenthaler Lisa A. Jensen Rex Kidd Norm Leblanc Kevin B. Morgan Steven M. Raque Subrato Sensharma Nancy E. Sunderland Richard J. Stevenson Gina B. To Michael E. Waterman

The following members of the individual balloting committee voted on this standard. Balloters may have voted for approval, disapproval, or abstention.

William Eventoff

Satish K. Aggarwal Michael Baldwin **Bakul Banerjee** Mario Barbacci Edward Bartlett Juris Borzovs Wesley Bowers John W. Bradbury Daniel Brosnan Nissen Burstein Joseph Butchko Garry Chapman Keith Chow Antonio M. Cicu Todd Cooper Paul R. Croll Surin Dureia David Daniel H. Taz Daughtrey Harpal S. Dhama Dr. Guru Dutt Dhingra Scott Duncan Dr. Sourav Dutta Clint Early, Jr. Christof Ebert Michael Edwards Amir El-Sheikh Gary Engmann Caroline Evans

John Fendrich Yaacov Fenster Uma D. Ferrell Ronald Fluegge Rabiz Foda Eva Freund Samuel Fryer Roger Fujii Juan Garbajosa Sopeña Jean-Denis Gorin Lewis Gray Ron K. Greenthaler Britton Grim Michael Grimley Randall Groves Jon Hagar Peter Hung Mark Heinrich John Horch David Horvath Peeya Iwagoshi Joseph Jancauskas William Junk Piotr Karocki Dwayne Knirk Subrahmanyam Kommu Robert Konnik

Thomas M. Kurihara Susan Land Carol Long Yuhai Ma G Michel James Moore Dennis Nickle Craig Noah Roger Parker Charles Roslund James Ruggieri Helmut Sandmayr Robert J. Schaaf Hans Schaefer David Schultz James Sivak Mike Smith Luca Spotorno Richard J. Stevenson Graeme Stewart Booker Thomas Gina B. To T.H. Tse John Waclo Richard Walker Michael E. Waterman Oren Yuen Janusz Zalewski Li Zhang

When the IEEE-SA Standards Board approved this standard on 8 December 2004, it had the following membership:

Don Wright, Chair Steve M. Mills, Vice Chair Judith Gorman, Secretary

Chuck Adams Stephen Berger Mark D. Bowman Joseph A. Bruder Bob Davis Roberto de Marca Boisson Julian Forster* Arnold M. Greenspan Mark S. Halpin lith Gorman, Secretar Raymond Hapeman Richard J. Holleman Richard H. Hulett Lowell G. Johnson Joseph L. Koepfinger* Hermann Koch Thomas J. McGean

Daleep C. Mohla Paul Nikolich T. W. Olsen Ronald C. Petersen Gary S. Robinson Frank Stone Malcolm V. Thaden Doug Topping Joe D. Watson

*Member Emeritus

Also included are the following nonvoting IEEE-SA Standards Board liaisons:

Satish K. Aggarwal, *NRC Representative* Richard DeBlasio, *DOE Representative* Alan Cookson, *NIST Representative*

> Michael D. Fisher IEEE Standards Project Editor

Contents

1.	Overview	
	1.1 Scope	
	1.2 Purpose	2
	1.3 Field of application	2
	1.4 V&V objectives	
	1.5 Organization of the standard	
	1.6 Audience	
	1.7 Conformance	5
	1.8 Disclaimer	5
	1.9 Limitations	
2.	References	5
3.	Definitions, abbreviations, and acronyms	
	3.1 Definitions	
	3.2 Abbreviations and acronyms	
4.	Software integrity levels	
5.	Software V&V processes	
	5.1 Process: Management	
	5.2 Process: Acquisition	
	5.3 Process: Supply	
	5.4 Process: Development	
	5.5 Process: Operation	
	5.6 Process: Maintenance	
6.	Software V&V reporting, administrative, and documentation requirements	
	6.1 V&V reporting requirements	
	6.2 V&V administrative requirements	
	6.3 V&V documentation requirements	
7.	Software V&V plan outline	
	7.1 SVVP section 1: Purpose	
	7.2 SVVP section 2: Referenced documents	
	7.3 SVVP section 3: Definitions	
	7.4 SVVP section 4: V&V overview	
	7.5 SVVP section 5: V&V processes	
	7.6 SVVP section 6: V&V reporting requirements	
	7.7 SVVP section 7: V&V administrative requirements	
	7.8 SVVP section 8: V&V test documentation requirements	

Annex A (informative) Mapping of IEEE Std 1012 V&V activities and tasks	71
Annex B (informative) A risk-based software integrity level scheme	88
Annex C (informative) Definition of independent V&V (IV&V)	90
Annex D (informative) V&V of reuse software	93
Annex E (informative) V&V measures	. 100
Annex F (informative) Example of V&V organizational relationship to other project responsibilities	. 103
Annex G (informative) Optional V&V tasks	. 104
Annex H (informative) Bibliography	. 110

IEEE Standard for Software Verification and Validation

1. Overview

This verification and validation (V&V) standard is a process standard that addresses all software life cycle processes including acquisition, supply, development, operation, and maintenance. This standard is compatible with all life cycle models; however, not all life cycle models use all of the life cycle processes listed in this standard.

Software V&V processes determine whether the development products of a given activity conform to the requirements of that activity and whether the software satisfies its intended use and user needs. This determination may include analysis, evaluation, review, inspection, assessment, and testing of software products and processes.

The user of this standard may invoke those software life cycle processes and the associated V&V processes that apply to the project. A description of software life cycle processes may be found in ISO/IEC 12207:1995 [B13],¹ IEEE Std 1074TM-1997 [B10], and IEEE/EIA Std 12207.0TM-1996 [B12]. Annex A maps ISO/IEC 12207:1995 [B13] (Table A.1.1) and IEEE Std 1074-1997 [B10] (Table A.2.1) to the V&V activities and tasks defined in this standard.

1.1 Scope

This standard applies to software being acquired, developed, maintained, or reused [legacy, modified, commercial off-the-shelf (COTS), non-developmental items (NDI)]. The term software also includes firmware, microcode, and documentation.

Software V&V processes consist of the verification process and validation process. The verification process provides objective evidence whether the software and its associated products and processes

- a) Conform to requirements (e.g., for correctness, completeness, consistency, accuracy) for all life cycle activities during each life cycle process (acquisition, supply, development, operation, and maintenance)
- b) Satisfy standards, practices, and conventions during life cycle processes
- c) Successfully complete each life cycle activity and satisfy all the criteria for initiating succeeding life cycle activities (e.g., building the software correctly)

¹The numbers in brackets correspond to those of the bibliography in Annex H.

The validation process provides evidence whether the software and its associated products and processes

- 1) Satisfy system requirements allocated to software at the end of each life cycle activity
- 2) Solve the right problem (e.g., correctly model physical laws, implement business rules, use the proper system assumptions)
- 3) Satisfy intended use and user needs

The verification process and the validation process are interrelated and complementary processes that use each other's process results to establish better completion criteria and analysis, evaluation, review, inspection, assessment, and test V&V tasks for each software life cycle activity. The V&V task criteria described in Table 1 uniquely define the conformance requirements for V&V processes.

The development of a reasonable body of evidence requires a trade-off between the amount of time spent and a finite set of system conditions and assumptions against which to perform the V&V tasks. Each project should define criteria for a reasonable body of evidence (i.e., selecting a software integrity level establishes one of the basic parameters), time schedule, and scope of the V&V analysis and test tasks (i.e., range of system conditions and assumptions).

This standard does not assign the responsibility for performing the V&V tasks to any specific organization. The analysis, evaluation, and test activities may be performed by multiple organizations; however, the methods and purpose will differ for each organization's functional objectives.

ISO/IEC 12207:1995 [B13] or IEEE/EIA 12207.0-1996 [B12] require that the developer perform various testing and evaluation tasks as an integral part of the development process. Even though the tests and evaluations are not part of the V&V processes, the techniques described in this standard may be useful in performing them. Therefore, whenever this standard mentions the developer's performance of a verification or validation activity, it is to be understood that the reference applies to the integral test and evaluation tasks of the development process.

1.2 Purpose

The purpose of this standard is to

- Establish a common framework for V&V processes, activities, and tasks in support of all software life cycle processes, including acquisition, supply, development, operation, and maintenance processes
- Define the V&V tasks, required inputs, and required outputs
- Identify the minimum V&V tasks corresponding to a four-level software integrity scheme
- Define the content of a *software V&V plan* (SVVP)

1.3 Field of application

This standard applies to all applications of software. When conducting the software V&V process, it is important to examine the software in its interactions with the system of which it is a part. This standard identifies the important system considerations that software V&V processes and tasks address in determining software correctness and other software V&V attributes (e.g., completeness, accuracy, consistency, testability).

The dynamics of software and the multitude of different logic paths available within software in response to varying system stimuli and conditions demand that the software V&V effort examine the correctness of the code for each possible variation in system conditions. The ability to model complex real world conditions will be limited, and thus the software V&V effort must examine whether the limits of the modeling are realistic and reasonable for the desired solution. The unlimited combination of system conditions presents

the software V&V effort with the unique challenge of using a finite set of analytical, test, simulation, and demonstration techniques to establish a reasonable body of evidence that the software is correct.

A software system provides a capability to satisfy a stated need or objective by combining one or more of the following: processes, hardware, software, facilities, and people. This relationship between the software and the system requires that software V&V processes consider software interactions with all system components. Since software links together all key components of a digital system, the software V&V process examines the interactions with each of the key system components to determine the extent to which each component influences the software and is conversely influenced by the software. The V&V process addresses the following interactions with software:

- *Environment:* Determines that the solution represented in the software correctly accounts for all conditions, natural phenomena, physical laws of nature, business rules, and physical properties and the full ranges of the system operating environment.
- Operators/users: Determines that the software communicates the proper status/condition of the software system to the operator/user and correctly processes all operator/user inputs to produce the required results. For incorrect operator/user inputs, ensure that the software protects the system from entering into a dangerous or uncontrolled state. Validate that operator/user policies and procedures (e.g., security, interface protocols, data representations, system assumptions) are consistently applied and used across each component interface.
- *Hardware:* Determines that the software correctly interacts with each hardware interface and provides a controlled system response (i.e., graceful degradation) for hardware faults.
- Other software: Determines that the software interfaces correctly with other software components in the system in accordance with requirements and that errors are not propagated between software components of the system.

Since software directly affects system behavior and performance, the scope of V&V processes is the software system, including the operational environment, operators and users, hardware, and interfacing software. The user of this standard should consider V&V as part of the software life cycle processes defined by industry standards, such as ISO/IEC 12207:1995 [B13], IEEE Std 1074-1997 [B10], or IEEE/EIA Std 12207.0-1996 [B12].

To address the systems perspective, software V&V should provide an integrated analysis where the V&V tasks are interrelated, providing input and insight to other V&V tasks. Results from completed life cycle processes provide valuable and necessary inputs to V&V tasks in later life cycle processes. Results and findings from one V&V task may cause previously completed V&V tasks to be analyzed again with the new data. This relationship among V&V tasks (including feedback to the development process) employing rigorous systems engineering techniques is a key approach to an integrated systems and software V&V. The software V&V results provide the development process with early detection of anomalies and potential process trends that may be used for development process improvement. The software V&V process and tasks described in this standard are consistent with systems engineering and process improvement models, such as the Capability Maturity Model Integrated (CMMI).

1.4 V&V objectives

V&V processes provide an objective assessment of software products and processes throughout the software life cycle. This assessment demonstrates whether the software requirements and system requirements (i.e., those allocated to software) are correct, complete, accurate, consistent, and testable. The software V&V processes determine whether the development products of a given activity conform to the requirements of that activity and whether the software satisfies its intended use and user needs. The determination includes assessment, analysis, evaluation, review, inspection, and testing of software products and processes. Software V&V should be performed in parallel with software development, not at the conclusion of the development effort.

The results of V&V create the following benefits to the program:

- Facilitate early detection and correction of software anomalies
- Enhance management insight into process and product risk
- Support the life cycle processes to ensure conformance to program performance, schedule, and budget
- Provide an early assessment of software and system performance
- Provide objective evidence of software and system conformance to support a formal certification process
- Improve the software development and maintenance processes
- Support the process improvement for an integrated systems analysis model

1.5 Organization of the standard

This standard is organized into clauses (Clauses 1 through 7), tables (Table 1, Table 2, and Table 3), figures (Figure 1 and Figure 2), and annexes (Annexes A through H). Clauses 2 through 7 and Table 1 and Table 2 provide the mandatory V&V requirements for this standard. Table 1 and Table 2 are the focal point of this standard, containing detailed V&V process, activity, and task requirements. Clause 2 is reserved for normative references; however, this standard does not prescribe any normative references. Clause 3 provides a definition of terms, abbreviations, and conventions. Clause 4 describes the use of software integrity levels to determine the scope and rigor of V&V processes. Clause 5 describes primary software life cycle processes and lists the V&V activities associated with the life cycle process. Clause 6 describes V&V reporting, administrative, and documentation requirements. Clause 7 describes the content of a software V&V plan. Clause 1, Figure 1, Figure 2, and Table 3 contain informative material that provides examples of V&V processes and provide guidance for using this standard. All annexes are informative.

Table 1 provides V&V task descriptions, inputs, and outputs for each life cycle process. Table 2 lists minimum V&V tasks required for different software integrity levels. Table 3 provides a list of optional V&V tasks and their suggested applications in the software system life cycle. These optional V&V tasks may be added to the minimum V&V tasks, as necessary, to tailor the V&V effort to project needs.

Figure 1 provides an example of an overview of the V&V inputs, outputs, and minimum V&V tasks for software integrity level 4. Figure 2 provides guidelines for scheduling V&V test planning, execution, and verification activities. An example of a phased life cycle model was used in Figure 1 and Figure 2 to illustrate a mapping of the ISO/IEC 12207:1995 [B13] life cycle processes to the V&V activities and tasks described in this standard.

Annex A describes the mapping of ISO/IEC 12207:1995 [B13] and IEEE Std 1074-1997 [B10] to this standard's V&V activities and tasks. Annex B provides an example of a risk-based, four-level integrity scheme. Annex C provides a definition of *independent verification and validation* (IV&V). Annex D provides guidelines for conducting V&V of reuse software. Annex E describes V&V measures. Annex F illustrates an example of the V&V organizational relationship to other project responsibilities. Annex G describes optional V&V tasks. Annex H provides a bibliography of informative standards referenced in this standard.

1.6 Audience

The audience for this standard includes software suppliers, acquirers, developers, maintainers, V&V practitioners, operators, users, and managers in both the supplier and acquirer organizations.

1.7 Conformance

The word *shall* identifies mandatory requirements strictly to be followed in order to conform to this standard. The words *should* and *may* indicate optional tasks that are not required to claim conformance to this standard.

Not all V&V efforts are initiated at the start of the life cycle process of acquisition and continued through the maintenance process. If a project uses only selected life cycle processes, then conformance to this standard is achieved if the minimum V&V tasks are implemented for the associated life cycle processes selected for the project. Any claim of conformance to this standard shall identify the applicable life cycle processes. As in all cases, the minimum V&V tasks are defined by the software integrity level assigned to the software. For life cycle processes that are not used by the project, the V&V requirements and tasks for those life cycle processes are optional V&V tasks invoked as needed at the discretion of the project. Specific software development methods and technologies (such as automated code generation from detailed design) may eliminate development steps or combine several development steps into one. Therefore, a corresponding adaptation of the minimum V&V tasks is permitted.

When this standard is invoked for existing software and the required V&V inputs are not available, then V&V tasks may use other available project input sources or may reconstruct the needed inputs to achieve conformance to this standard.

1.8 Disclaimer

This standard establishes minimum criteria for V&V processes, activities, and tasks. However, implementing these criteria does not automatically ensure conformance to system or mission objectives, or prevent adverse consequences (e.g., loss of life, mission failure, loss of system safety or security, financial or social loss). Conformance to this standard does not absolve any party from any social, moral, financial, or legal obligations.

1.9 Limitations

None.

2. References

This standard does not require the use of any normative references. Standards useful for the implementation and interpretation of this standard are listed in Annex H.

3. Definitions, abbreviations, and acronyms

3.1 Definitions

For the purposes of this standard, the following terms and definitions apply. *The Authoritative Dictionary of IEEE Standards Terms*, Seventh Edition [B2] and IEEE Std 610.12[™]-1990 [B3] should be referenced for terms not defined in this clause.

3.1.1 acceptance testing: (A) Formal testing conducted to determine whether or not a system satisfies its acceptance criteria and to enable the customer to determine whether or not to accept the system. **(B)** Formal testing conducted to enable a user, customer, or other authorized entity to determine whether to accept a system or component.

NOTE—See IEEE Std 610.12-1990 [B3].²

3.1.2 anomaly: Anything observed in the documentation or operation of software that deviates from expectations based on previously verified software products or reference documents.

NOTE—See IEEE Std 610.12-1990 [B3].

3.1.3 asset: An item (e.g., design, specifications, source code, documentation, test suites, manual procedures) that has been designed for use in multiple contexts.

NOTE—See IEEE Std 1517[™]-1999 [B11].

3.1.4 component: One of the parts that make up a system. A component may be hardware or software and may be subdivided into other components.

NOTE 1—The terms "module," "component," and "unit" are often used interchangeably or defined to be subelements of one another in different ways depending upon the context. The relationship of these terms is not yet standardized.

NOTE 2-See IEEE Std 610.12-1990 [B3].

3.1.5 component testing: Testing of individual hardware or software components or groups of related components.

NOTE—See IEEE Std 610.12-1990 [B3].

3.1.6 criticality: The degree of impact that a requirement, module, error, fault, failure, or other item has on the development or operation of a system.

NOTE—See IEEE Std 610.12-1990 [B3].

3.1.7 domain: A problem space.

NOTE—See IEEE Std 1517-1999 [B11].

3.1.8 domain analysis: (A) The analysis of systems within a domain to discover commonalities and differences among them. **(B)** The process by which information used in developing software systems is identified, captured, and organized so that it can be reused to create new systems, within a domain. **(C)** The result of the process in (A) and (B).

NOTE—See IEEE Std 1517-1999 [B11].

3.1.9 domain engineering: A reuse-based approach to defining the scope (i.e., domain definition), specifying the structure (i.e., domain architecture), and building the assets (e.g., requirements, designs, software code, documentation) for a class of systems, subsystems, or applications. Domain engineering may include the following activities: domain definition, domain analysis, developing the domain architecture, and domain implementation.

NOTE—See IEEE Std 1517-1999 [B11].

3.1.10 firmware: The combination of a hardware device and computer instructions and data that reside as read-only software on that device.

NOTE 1—This term is sometimes used to refer only to the hardware device or only to the computer instructions or data, but these meanings are deprecated.

NOTE 2-The confusion surrounding this term has led some to suggest that it be avoided altogether.

NOTE 3—See IEEE Std 610.12-1990 [B3].

²Notes in text, tables, and figures are given for information only and do not contain requirements needed to implement the standard.

3.1.11 hazard: (A) An intrinsic property or condition that has the potential to cause harm or damage. **(B)** A source of potential harm or a situation with a potential for harm in terms of human injury, damage to health, property, or the environment, or some combination of these.

NOTE—For (A), see IEEE/EIA Std 12207.0[™]-1996 [B12].

3.1.12 hazard identification: The process of recognizing that a hazard exists and defining its characteristics.

3.1.13 independent verification and validation (IV&V): V&V performed by an organization that is technically, managerially, and financially independent of the development organization.

NOTE—See IEEE Std 610.12-1990 [B3].

3.1.14 integration testing: Testing in which software components, hardware components, or both are combined and tested to evaluate the interaction between them.

NOTE—See IEEE Std 610.12-1990 [B3].

3.1.15 integrity level: A value representing project-unique characteristics (e.g., software complexity, criticality, risk, safety level, security level, desired performance, reliability) that define the importance of the software to the user.

3.1.16 interface design document (IDD): Documentation that describes the architecture and design interfaces between system and components. These descriptions include control algorithms, protocols, data contents and formats, and performance.

NOTE—See IEEE Std 610.12-1990 [B3].

3.1.17 interface requirements specification (IRS): Documentation that specifies requirements for interfaces between systems and components. These requirements include constraints on formats and timing.

NOTE—See *The Authoritative Dictionary* [B2].

3.1.18 life cycle processes: A set of interrelated activities that result in the development or assessment of software products. Each activity consists of tasks. The life cycle processes may overlap one another. For V&V purposes, no process is concluded until its development products are verified and validated according to the defined tasks in the SVVP.

NOTE—See The Authoritative Dictionary [B2].

3.1.19 microcode: A collection of microinstructions, comprising part of or all of microprograms.

NOTE—See IEEE Std 610.12-1990 [B3].

3.1.20 microprogram: A sequence of instructions, called microinstructions, specifying the basic operations needed to carry out a machine language instruction.

NOTE—See IEEE Std 610.12-1990 [B3].

3.1.21 minimum tasks: Those V&V tasks required for the software integrity level assigned to the software to be verified and validated.

NOTE—See The Authoritative Dictionary [B2].

3.1.22 optional tasks: Those V&V tasks that may be added to the minimum V&V tasks to address specific application requirements.

NOTE—See The Authoritative Dictionary [B2].

3.1.23 required inputs: The set of items necessary to perform the minimum V&V tasks mandated within any life cycle activity.

NOTE—See The Authoritative Dictionary [B2].

3.1.24 required outputs: The set of items produced as a result of performing the minimum V&V tasks mandated within any life cycle activity.

NOTE—See *The Authoritative Dictionary* [B2].

3.1.25 reusable software product: A software product developed for one use but having other uses, or one developed specifically to be usable on multiple projects or in multiple roles on one project. Examples include, but are not limited to, COTS software products, acquirer-furnished software products, software products in reuse libraries, and preexisting developer software products. Each use may include all or part of the software product and may involve its modification. This term can be applied to any software product (for example, requirements, architectures), not just to software itself.

NOTE—See The Authoritative Dictionary [B2].

3.1.26 risk: (A) The combination of the probability of occurrence and the consequences of a given future undesirable event. Risk can be associated with products and/or projects. (B) The combination of the probability of an abnormal event or failure and the consequence(s) of that event or failure to a system's components, operators, users, or environment.

NOTE—See The Authoritative Dictionary [B2].

3.1.27 security: (A) The protection of computer hardware or software from accidental or malicious access, use, modification, destruction, or disclosure. Security also pertains to personnel, data, communications, and the physical protection of computer installations. (B) The protection of information and data so that unauthorized persons or systems cannot read or modify them and authorized persons or systems are not denied access to them.

NOTE—For (A), see The Authoritative Dictionary [B2]. For subdefinition (B), see ISO/IEC 12207:1995 [B13].

3.1.28 software design description (SDD): A representation of software created to facilitate analysis, planning, implementation, and decision-making. The software design description is used as a medium for communicating software design information and may be thought of as a blueprint or model of the system.

NOTE—See The Authoritative Dictionary [B2].

3.1.29 software requirements specification (SRS): Documentation of the essential requirements (functions, performance, design constraints, and attributes) of the software and its external interfaces.

NOTE—See IEEE Std 610.12-1990 [B3].

3.1.30 system testing: Testing conducted on a complete, integrated system to evaluate the system's compliance with its specified requirements.

NOTE—See IEEE Std 610.12-1990 [B3].

3.1.31 test case: (A) A set of test inputs, execution conditions, and expected results developed for a particular objective, such as to exercise a particular program path or to verify compliance with a specific requirement. (B) Documentation specifying inputs, predicted results, and a set of execution conditions for a test item.

NOTE—See IEEE Std 610.12-1990 [B3].

3.1.32 test design: Documentation specifying the details of the test approach for a software feature or combination of software features and identifying the associated tests.

NOTE—See IEEE Std 610.12-1990 [B3].

3.1.33 test plan: (A) A document describing the scope, approach, resources, and schedule of intended test activities. It identifies test items, the features to be tested, the testing tasks, who will do each task, and any risks requiring contingency planning. (B) A document that describes the technical and management approach to be followed for testing a system or component. Typical contents identify the items to be tested, tasks to be performed, responsibilities, schedules, and required resources for the testing activity.

NOTE—See IEEE Std 610.12-1990 [B3].

3.1.34 test procedure: (A) Detailed instructions for the setup, execution, and evaluation of results for a given test case. **(B)** A document containing a set of associated instructions as in (A). **(C)** Documentation that specifies a sequence of actions for the execution of a test.

NOTE—See IEEE 982.1[™]-1998 [B5].

3.1.35 validation: (A) The process of evaluating a system or component during or at the end of the development process to determine whether it satisfies specified requirements. (B) The process of providing evidence that the software and its associated products satisfy system requirements allocated to software at the end of each life cycle activity, solve the right problem (e.g., correctly model physical laws, implement business rules, use the proper system assumptions), and satisfy intended use and user needs.

NOTE—For (A), see IEEE Std 610.12-1990 [B3].

3.1.36 verification: (A) The process of evaluating a system or component to determine whether the products of a given development phase satisfy the conditions imposed at the start of that phase. (B) The process of providing objective evidence that the software and its associated products conform to requirements (e.g., for correctness, completeness, consistency, accuracy) for all life cycle activities during each life cycle process (acquisition, supply, development, operation, and maintenance); satisfy standards, practices, and conventions during life cycle processes; and successfully complete each life cycle activity and satisfy all the criteria for initiating succeeding life cycle activities (e.g., building the software correctly).

NOTE—For subdefinition (A), see IEEE Std 610.12-1990 [B3].

3.1.37 verification and validation (V&V) effort: The work associated with performing the V&V processes, activities, and tasks. The following framework illustrates how V&V processes are subdivided into activities, which in turn have associated tasks:



NOTE 1—Other supporting processes consist of documentation, configuration management, quality assurance, joint review, audit, and problem resolution.

NOTE 2-Management of V&V activity is concurrent with all V&V activities.

NOTE 3-The task description, inputs, and outputs of all V&V tasks are included in Table 1.

3.2 Abbreviations and acronyms

The following acronyms and abbreviations appear in this standard:

- ANSI American National Standards Institute
- COTS commercial off-the-shelf
- IEC International Electrotechnical Commission
- IEEE Institute of Electrical and Electronic Engineers
- IDD interface design document
- IRS interface requirements specification
- ISO International Organization for Standardization
- IV&V independent verification and validation
- NDI non-developmental item
- RFP request for proposal (tender)
- SDD software design description

- SRS software requirements specification
- SVVP software V&V plan
- SVVR software V&V report
- V&V verification and validation

4. Software integrity levels

Software integrity levels are a range of values that represent software complexity, criticality, risk, safety level, security level, desired performance, reliability, or other project-unique characteristics that define the importance of the software to the user and acquirer. The characteristics used to determine software integrity level vary depending on the intended application and use of the system. The software is a part of the system, and its integrity level is to be determined as a part of that system. The assigned software integrity levels may change as the software evolves. Design, coding, procedural, and technology features implemented in the system or software can raise or lower the assigned software integrity levels. The software integrity levels established for a project should result from agreements among the acquirer, supplier, developer, and independent assurance authorities (e.g., a regulatory body or responsible agency).

This standard uses software integrity levels to determine the V&V tasks to be performed. High-integrity software requires a larger set of V&V processes and a more rigorous application of V&V tasks. Integrity levels are assigned to software requirements, functions, groups of functions, or software components or subsystems. Some software elements and components may not require the assignment of an integrity level (i.e., not applicable) because their failure would impart no consequences on the intended system operations. The V&V processes should be tailored to specific system requirements and applications through the selection of a software integrity level with its corresponding minimum V&V tasks and addition of optional V&V tasks. The addition of optional V&V tasks allows the V&V effort to address application specific characteristics of the software. The V&V effort may recommend technical and procedural mitigation approaches to reduce the integrity level.

As an example, this standard uses the following four-level software integrity scheme. This example scheme is based upon the concepts of consequences and mitigation potential.

Description	Level
Software element must execute correctly or grave consequences (loss of life, loss of system, economic or social loss) will occur. No mitigation is possible.	4
Software element must execute correctly or the intended use (mission) of the system/ software will not be realized, causing serious consequences (permanent injury, major system degradation, economic or social impact). Partial to complete mitigation is possible.	3
Software element must execute correctly or an intended function will not be realized, causing minor consequences. Complete mitigation possible.	2
Software element must execute correctly or intended function will not be realized, causing negligible consequences. Mitigation not required.	1

Another example, a scheme based on risk, is described in Annex B. This standard does not require the use of any particular software integrity level scheme described or referenced in this standard.

Integrity levels shall be assigned to software elements or components as part of the criticality analysis task. The V&V effort shall specify a software integrity level scheme if one is not already defined. The integrity level assigned to reused software products shall be in accordance with the integrity level scheme adopted for the project (see Annex D), and the reused software product shall be evaluated for use in the context of its application. Tools that insert or translate code (e.g., optimizing compilers, auto-code generators) shall be assigned the same integrity level as the integrity level assigned to the software element that the tool affects. The software system shall be assigned the same integrity level as the highest level assigned to any individual element. The software integrity level assignment shall be continually reviewed and updated by conducting the V&V criticality analysis task throughout the software development process.

Table 2 identifies minimum V&V tasks that shall be performed for each software integrity level. To identify the minimum V&V tasks that apply to a different selected software integrity level scheme, the user of the standard shall map this standard's software integrity level scheme and associated minimum V&V tasks to their selected software integrity level scheme. The mapping of the software integrity level scheme and the associated minimum V&V tasks shall be documented in the SVVP. The basis for assigning software integrity levels to software components shall be documented in a V&V task report and V&V final report.

5. Software V&V processes

V&V processes support the six primary processes of ISO/IEC 12207:1995 [B13]: the management process (see 5.1), acquisition process (see 5.2), supply process (see 5.3), development process (see 5.4), operation process (see 5.5), and maintenance process (see 5.6). The minimum V&V activities and tasks supporting these processes are referenced in the following clauses and are defined in Table 1. The subclause titles in this clause are the same as the column headings in Table 1 to correlate the requirements of the following subclauses with Table 1 tasks. Not all software projects include each of the life cycle processes listed. To conform to this standard, the V&V processes shall address all those life cycle processes used by the software project.

The V&V effort shall conform to the task descriptions, inputs, and outputs as described in Table 1. The V&V effort shall perform the minimum V&V tasks specified in Table 2 for the assigned software integrity level. If the user of this standard has selected a different software integrity level scheme, then this standard's software integrity level scheme and associated minimum V&V tasks of Table 2 shall be mapped to their selected software integrity level scheme.

Optional V&V tasks may also be performed to augment the V&V effort to satisfy project needs. Optional V&V tasks are listed in Table 3 and described in Annex G. The list in Table 3 is illustrative and not exhaustive.

The degree of rigor and intensity in performing and documenting the task shall be commensurate with the software integrity level. As the software integrity level decreases, so does the required scope, intensity, and degree of rigor associated with the V&V task. For example, a hazard analysis performed for software integrity level 4 software might be formally documented and consider failures at the module level; a hazard analysis for software integrity level 3 software may consider only significant software failures and be documented informally as part of the design review process.

Some V&V activities and tasks include analysis, evaluations, and tests that may be performed by multiple organizations (e.g., software development, project management, quality assurance, V&V). For example, risk analysis and hazard analysis may be performed by project management, the development organization, and the V&V effort. The V&V effort performs these tasks to develop the supporting basis of evidence showing whether the software product satisfies its requirements. These V&V analyses are complementary to other analyses and do not eliminate or replace the analyses performed by other organizations. The degree to which these analysis efforts will be coordinated with other organizations shall be documented in the organizational responsibility section of the SVVP.

Testing requires advance planning that spans several development activities. Test documentation and its generation at specific processes in the life cycle are shown in Figure 1 and Figure 2.

The user of this standard shall document the V&V processes in the SVVP and shall define the information and facilities necessary to manage and perform these processes, activities, and tasks, and to coordinate the V&V processes with other related aspects of the project. The results of V&V activities and tasks shall be documented in task reports, activity summary reports, anomaly reports, V&V test documents, and the V&V final report.

5.1 Process: Management

The management process comprises the following generic activities and tasks:

- Preparing the plans for execution of the process
- Initiating the implementation of the plan
- Monitoring the execution of the plan
- Analyzing problems discovered during the execution of the plan
- Reporting progress of the processes
- Ensuring products satisfy requirements
- Assessing evaluation results
- Determining whether a task is complete
- Checking the results for completeness
- Checking processes for efficiency and effectiveness
- Reviewing project quality
- Reviewing project risks
- Reviewing project measures

5.1.1 Activity: Management of the V&V effort

The V&V management activity monitors and evaluates all V&V outputs. Management of the V&V effort is performed for all software life cycle processes and activities. This activity involves the following:

- A continual review of the V&V effort
- Revision of the SVVP as necessary based upon updated project schedules and development status
- Coordination of the V&V results with the developer and other supporting processes, such as quality assurance and configuration management
- Performance of reviews and audits
- Identification of process improvement opportunities in the conduct of V&V

V&V management assesses each proposed change to the system and software, identifies the software requirements that are affected by the change, and plans V&V tasks to address the change. For each proposed change, management assesses whether any new hazards or risks are introduced in the software or system development process, and identifies the impact of the change on the assigned software integrity levels. V&V task planning is revised by adding new V&V tasks or changing the scope or intensity of existing V&V tasks if software integrity levels, hazards, or risks are changed. A baseline change results from changes allocated to software releases in an incremental software development process (e.g., planned baseline versions).

Through the use of V&V measures and other qualitative and quantitative measures, this V&V activity develops program trend data and possible risk issues, which are then provided to the developer and acquirer to effect timely notification and resolution. At key program milestones (e.g., requirements review, design review, test readiness), V&V management consolidates the V&V results to establish supporting evidence of

whether to proceed to the next set of software development activities. Whenever necessary, the V&V management determines whether a V&V task should be reperformed as a result of changes in the software program.

The V&V effort shall perform, as specified in Table 2 for the selected software integrity level, the following Management V&V tasks described in Table 1:

- 1) Task: SVVP generation
- 2) Task: Proposed/baseline change assessment
- 3) Task: Management review of the V&V effort
- 4) Task: Management and technical review support
- 5) Task: Interface with organizational and supporting processes
- 6) Task: Identify process improvement opportunities in the conduct of V&V

5.2 Process: Acquisition

The acquisition process begins with the definition of the need (e.g., statement of need) to acquire a system, software product, or software service. The process continues with the possible preparation and issuance of a request for proposal (RFP) (e.g., bid request, tender), selection of a supplier, and management of the acquisition process through to the acceptance of the system, software product, or software service.

The acquisition process is used to scope the V&V effort, plan interfaces with the supplier and acquirer, review the draft systems requirements to be included in the RFP, and provide the V&V task results to support acquirer acceptance of the system. Acquirer acceptance of the system culminates after acceptance testing and installation. The V&V acquisition acceptance support activities occur throughout the software life cycle, in conjunction with other interrelated development and V&V tasks, inputs, and outputs.

5.2.1 Activity: Acquisition support V&V

The Acquisition support V&V activity addresses project initiation, RFP, contract preparation, supplier monitoring, and acceptance and completion.

The V&V effort shall perform, as specified in Table 2 for the selected software integrity level, the following Acquisition support V&V tasks described in Table 1:

- 1) Task: Scoping the V&V effort
- 2) Task: Planning the interface between the V&V effort and supplier
- 3) Task: System requirements review
- 4) Task: Acceptance support

5.3 Process: Supply

The supply process is initiated by either a decision to prepare a proposal to answer an acquirer's request for proposal or by negotiating, finalizing, and entering into a contract with the acquirer to provide the system, software product, or software service. The process continues with the determination of procedures and resources needed to manage the project, including development of project plans and execution of the plans through delivery of the system, software product, or software product, or software product, or software product.

The Supply V&V effort uses the supply process products to confirm that the request for proposal requirements and contract requirements are consistent and satisfy user needs before the contract is finalized. The V&V planning activity uses the contract requirements, including the program schedules, to revise and update the interface planning between the supplier and acquirer.

5.3.1 Activity: Planning V&V

The Planning V&V activity addresses the initiation, preparation of response, contract, planning, execution and control, review and evaluation, and delivery and completion activities.

The V&V effort shall perform, as specified in Table 2 for the selected software integrity level, the following Planning V&V tasks described in Table 1:

- 1) Task: Planning the interface between the V&V effort and supplier
- 2) Task: Contract verification

5.4 Process: Development

The development process contains the activities and tasks of the developer. The process contains the activities for requirements analysis, design, coding, integration, testing, and installation and support to acceptance of software products.

The V&V activities verify and validate these software products. The V&V activities are organized into Concept V&V, Requirements V&V, Design V&V, Implementation V&V, Test V&V, and Installation and checkout V&V.

5.4.1 Activity: Concept V&V

The concept activity represents the delineation of a specific implementation solution to solve the user's problem. During the concept activity, the system architecture is selected and system requirements are allocated to hardware, software, and user interface components. The Concept V&V activity addresses system architectural design and system requirements analysis. The objective of Concept V&V is to verify the allocation of system requirements, validate the selected solution, and ensure that no false assumptions have been incorporated in the solution.

The V&V effort shall perform, as specified in Table 2 for the selected software integrity level, the following Concept V&V tasks described in Table 1:

- 1) Task: Concept documentation evaluation
- 2) Task: Criticality analysis
- 3) Task: Hardware/software/user requirements allocation analysis
- 4) Task: Traceability analysis
- 5) Task: Hazard analysis
- 6) Task: Security analysis
- 7) Task: Risk analysis

5.4.2 Activity: Requirements V&V

The Requirements V&V activity addresses software requirements analysis of the functional and performance requirements, interfaces external to the software, and requirements for qualification, safety and security, human factors engineering, data definitions, user documentation for the software, installation and acceptance, user operation and execution, and user maintenance. V&V test planning begins during the Requirements V&V activity and spans several V&V activities.

The objective of Requirements V&V is to ensure the correctness, completeness, accuracy, testability, and consistency of the system software requirements.

The V&V effort shall perform, as specified in Table 2 for the selected software integrity level, the following Requirements V&V tasks described in Table 1:

- 1) Task: Traceability analysis
- 2) Task: Software requirements evaluation
- 3) Task: Interface analysis
- 4) Task: Criticality analysis
- 5) Task: System V&V test plan generation
- 6) Task: Acceptance V&V test plan generation
- 7) Task: Configuration management assessment
- 8) Task: Hazard analysis
- 9) Task: Security analysis
- 10) Task: Risk analysis

5.4.3 Activity: Design V&V

In software design, software requirements are transformed into an architecture and a detailed design for each software component. The design includes databases and system interfaces (e.g., hardware, operator/user, software components, and subsystems). The Design V&V activity addresses software architectural design and software detailed design. V&V test planning continues during the Design V&V activity.

The objective of Design V&V is to demonstrate that the design is a correct, accurate, and complete transformation of the software requirements and that no unintended features are introduced.

The V&V effort shall perform, as specified in Table 2 for the selected software integrity level, the following Design V&V tasks described in Table 1:

- 1) Task: Traceability analysis
- 2) Task: Software design evaluation
- 3) Task: Interface analysis
- 4) Task: Criticality analysis
- 5) Task: Component V&V test plan generation
- 6) Task: Integration V&V test plan generation
- 7) Task: Component V&V test design generation
- 8) Task: Integration V&V test design generation
- 9) Task: System V&V test design generation
- 10) Task: Acceptance V&V test design generation
- 11) Task: Hazard analysis
- 12) Task: Security analysis
- 13) Task: Risk analysis

5.4.4 Activity: Implementation V&V

In software implementation, the system design is transformed into code, database structures, and related machine executable representations. The Implementation V&V activity addresses software coding and testing, including the incorporation of reused software products. The objective of Implementation V&V is to verify and validate that these transformations are correct, accurate, and complete.

The V&V effort shall perform, as specified in Table 2 for the selected software integrity level, the following Implementation V&V tasks described in Table 1:

- 1) Task: Traceability analysis
- 2) Task: Source code and source code documentation evaluation
- 3) Task: Interface analysis
- 4) Task: Criticality analysis
- 5) Task: Component V&V test case generation
- 6) Task: Integration V&V test case generation
- 7) Task: System V&V test case generation
- 8) Task: Acceptance V&V test case generation
- 9) Task: Component V&V test procedure generation
- 10) Task: Integration V&V test procedure generation
- 11) Task: System V&V test procedure generation
- 12) Task: Component V&V test execution
- 13) Task: Hazard analysis
- 14) Task: Security analysis
- 15) Task: Risk analysis

5.4.5 Activity: Test V&V

Testing includes software testing, software integration testing, software qualification testing, system integration testing, and system qualification testing. The Test V&V activity and its relationship to the software life cycle are shown in Figure 2. The objective of Test V&V is to ensure that the software requirements and system requirements allocated to software are validated by execution of integration, system, and acceptance tests.

The V&V effort shall perform, as specified in Table 2 for the selected software integrity level, the following Test V&V tasks described in Table 1:

- 1) Task: Traceability analysis
- 2) Task: Acceptance V&V test procedure generation
- 3) Task: Integration V&V test execution
- 4) Task: System V&V test execution
- 5) Task: Acceptance V&V test execution
- 6) Task: Hazard analysis
- 7) Task: Security analysis
- 8) Task: Risk analysis

5.4.6 Activity: Installation and checkout V&V

In installation and checkout, the software product is installed and tested in the target environment. The Installation and checkout V&V activity supports the software system installation activities. The objective of Installation and checkout V&V is to verify and validate the correctness of the software installation in the target environment.

The V&V effort shall perform, as specified in Table 2 for the selected software integrity level, the following Installation and checkout V&V tasks described in Table 1:

- 1 Task: Installation configuration audit
- 2) Task: Installation checkout
- 3) Task: Hazard analysis

- 4) Task: Security analysis
- 5) Task: Risk analysis
- 6) Task: V&V final report generation

5.5 Process: Operation

The operation process involves the use of the software system by the end user in an operational environment.

5.5.1 Activity: Operation V&V

The Operation V&V activity evaluates the impact of changes in the operating environment; assesses the effect on the system of any proposed changes; evaluates operating procedures for adherence with the intended use; and analyzes risks affecting the user and the system. The objective of Operation V&V is to evaluate new constraints in the system, assess proposed system changes and their impact on the software, and evaluate operating procedures for correctness and usability.

The V&V effort shall perform, as specified in Table 2 for the selected software integrity level, the following Operation V&V tasks described in Table 1:

- 1) Task: Evaluation of new constraints
- 2) Task: Operating procedures evaluation
- 3) Task: Hazard analysis
- 4) Task: Security analysis
- 5) Task: Risk analysis

5.6 Process: Maintenance

The maintenance process is activated when the software system or associated documentation must be changed in response to a need for system maintenance. The Maintenance V&V activity addresses software system

- Modifications (i.e., corrective, adaptive, or perfective changes)
- Migration (i.e., the movement of software to a new operational environment)
- Retirement (i.e., the withdrawal of active support by the operation and maintenance organization, partial or total replacement by a new system, or installation of an upgraded system)

5.6.1 Activity: Maintenance V&V

System modifications may be derived from requirements specified to correct software errors (e.g., corrective); to adapt to a changed operating environment (e.g., adaptive); or to respond to additional user requests or enhancements (e.g., perfective). Modifications of the software system shall be treated as development processes and shall be verified and validated as described in the following:

- 5.1 Process: Management
- 5.4. Process: Development

Software integrity level assignments shall be assessed as described in Clause 4. The software integrity level assignments shall be revised as appropriate to reflect requirements derived from the maintenance process.

For migrating software, the V&V effort shall verify that the migrated software meets the requirements of Clauses 4 and 5.

If the software V&V was performed in accordance with this standard, the maintenance process shall continue to conform to this standard. If the software was not verified and validated using this standard and appropriate documentation is not available or adequate, the Maintenance V&V effort shall determine whether the missing or incomplete documentation should be generated. In making this determination of whether to generate missing documentation, the minimum V&V requirements of the assigned software integrity level shall be taken into consideration.

The objective of Maintenance V&V is to assess proposed software system changes and their impact on the software, evaluate anomalies that are discovered during operation, assess migration requirements, assess retirement requirements, and reperform V&V tasks. The proposed changes are assessed by the *proposed/baseline change assessment* task of the Management of V&V activity.

The V&V effort shall perform, as specified in Table 2 for the selected software integrity level, the following Maintenance V&V tasks described in Table 1:

- 1) Task: SVVP revision
- 2) Task: Anomaly evaluation
- 3) Task: Criticality analysis
- 4) Task: Migration assessment
- 5) Task: Retirement assessment
- 6) Task: Hazard analysis
- 7) Task: Security analysis
- 8) Task: Risk analysis
- 9) Task: Task iteration

6. Software V&V reporting, administrative, and documentation requirements

6.1 V&V reporting requirements

V&V reporting occurs throughout the software life cycle. The V&V effort shall produce the required outputs listed in Table 1 for each V&V task performed. The format and grouping of the V&V reports may be user defined. The V&V reports shall constitute the *software V&V report* (SVVR).

The V&V reports shall consist of the following:

- a) *V&V task reports*. The V&V effort shall document V&V task results and status. Task reports include the following:
 - 1) Anomaly evaluation
 - 2) Concept documentation evaluation
 - 3) Configuration management assessment
 - 4) Contract verification
 - 5) Criticality analysis
 - 6) Evaluation of new constraints
 - 7) Hardware/ software/user requirements allocation analysis
 - 8) Hazard analysis
 - 9) Installation checkout
 - 10) Installation configuration audit
 - 11) Interface analysis
 - 12) Migration assessment

- 13) Operating procedures evaluation
- 14) Proposed change assessment
- 15) Recommendations
- 16) Retirement assessment
- 17) Review results
- 18) Risk analysis
- 19) Security analysis
- 20) Software design evaluation
- 21) Software requirements evaluation
- 22) Source code and source code documentation evaluation
- 23) System requirements review
- 24) Test results
- 25) Traceability analysis
- b) *V&V activity summary reports*. An activity summary report shall summarize the results of V&V tasks performed for the following V&V life cycle activities:
 - 1) Acquisition support
 - 2) Planning
 - 3) Concept
 - 4) Requirements
 - 5) Design
 - 6) Implementation
 - 7) Test
 - 8) Installation and checkout
 - 9) Operation
 - 10) Maintenance

For the operation and maintenance life cycle activities, V&V activity summary reports may be either updates to previous V&V activity summary reports or separate documents.

- c) *V&V anomaly reports*. The V&V effort shall document in an anomaly report each anomaly it detects.
- d) *V&V final report.* The V&V final report shall be issued at the end of the installation and checkout activity or at the conclusion of the V&V effort.
- e) Optional V&V reports. The V&V reports may also include optional reports (i.e., special studies reports and other reports). The V&V effort shall document in a special studies report any special V&V studies conducted during the software life cycle. The V&V effort shall document in a report the results of tasks conducted but not defined in the SVVP. These other task reports may include, for example, quality assurance results, end-user testing results, safety assessment report, or configuration and data management status results. The title of the report may vary according to the subject matter.

Task report(s), V&V activity summary report(s), and anomaly report(s) should be provided as feedback to the software development process regarding the technical quality of each software product and process.

6.2 V&V administrative requirements

The V&V administrative requirements shall consist of the following:

- 1) Anomaly resolution and reporting policy
- 2) Task iteration policy
- 3) Deviation policy
- 4) Control procedures
- 5) Standards, practices, and conventions

These administrative requirements shall be documented in the SVVP.

6.3 V&V documentation requirements

The scope of V&V documentation consists of V&V test documentation and SVVP documentation. The requirements for documentation are described in the following subclauses.

6.3.1 V&V test documentation

V&V test documentation requirements shall include the test plans, designs, cases, procedures, and results for component, integration, system, and acceptance testing developed by the V&V effort. The V&V test documentation shall conform to project-defined test document purpose, format, and content (e.g., see IEEE Std 829^{TM} -1998 [B4]). If the V&V effort uses test documentation or test types different from those in this standard (i.e., component, integration, system, acceptance), the software V&V effort shall show a mapping of the proposed test documentation and execution to the test items defined in this standard. Test planning tasks defined in Table 1 shall be documented in the test plan, test design(s), test case(s), and test procedure(s).

6.3.2 SVVP documentation

The V&V effort shall generate an SVVP that addresses the topics described in Clause 7 of this standard. If there is no information pertinent to a topic, the SVVP shall contain the phrase "This topic is not applicable to this plan" and shall state an appropriate reason for the exclusion. Additional topics may be added to the plan. If some SVVP material appears in other documents, the SVVP may repeat the material or make reference to the material. The SVVP shall be maintained throughout the life of the software.

7. Software V&V plan outline

The SVVP shall contain the content described in this clause. The user of this standard may adopt any format and section numbering system for the SVVP. The SVVP section numbers listed in this clause are provided to assist readability. An example SVVP outline is shown in the following boxed text.

SVVP outline (example)		
1. Purpose		
2. Referenced documents		
3. Definitions		
4. V&V overview		
4.1 Organization		
4.2 Master schedule		
4.3 Software integrity level scheme		
4.4 Resources summary		
4.5 Responsibilities		
4.6 Tools, techniques, and methods		
5. V&V processes		
5.1 Process: Management		
5.1.1 Activity: Management of V&V		
5.2 Process: Acquisition		
5.2.1 Activity: Acquisition support V&V		
5.3 Process: Supply		
5.3.1 Activity: Planning V&V		
5.4 Process: Development		
5.4.1 Activity: Concept V&V		
5.4.2 Activity: Requirements V&V		
5.4.3 Activity: Design V&V		
5.4.4 Activity: Implementation V&V		
5.4.5 Activity: Test V&V		
5.4.6 Activity: Installation and checkout V&V		
5.5 Process: Operation		
5.5.1 Activity: Operation V&V		
5.6 Process: Maintenance		
5.6.1 Activity: Maintenance V&V		
6. V&V reporting requirements		
6.1 Task reports		
6.2 Activity summary reports		

SVVP outline (example) (continued)
6.3 Anomaly reports
6.4 V&V final report
6.5 Special studies reports (optional)
6.6 Other reports (optional)
7. V&V Administrative requirements
7.1 Anomaly resolution and reporting
7.2 Task iteration policy
7.3 Deviation policy
7.4 Control procedures
7.5 Standards, practices, and conventions
8. V&V test documentation requirements

7.1 SVVP section 1: Purpose

The SVVP shall describe the purpose, goals, and scope of the software V&V effort, including waivers from this standard. The SVVP also shall identify the specific software processes and products covered by the software V&V effort. Date of issue and status, identification of issuing organization, and identification of approval authority shall be provided.

7.2 SVVP section 2: Referenced documents

The SVVP shall identify the compliance documents, documents referenced by the SVVP, and any supporting documents supplementing or implementing the SVVP.

7.3 SVVP section 3: Definitions

The SVVP shall define or reference all terms used in the SVVP, including the criteria for classifying an anomaly as a critical anomaly. All abbreviations and notations used in the SVVP also shall be described.

7.4 SVVP section 4: V&V overview

The SVVP shall describe the organization, schedule, software integrity level scheme, resources, responsibilities, tools, techniques, and methods necessary to perform the software V&V.

7.4.1 SVVP section 4.1: Organization

The SVVP shall describe the organization of the V&V effort, including the degree of independence required (see Annex C). The SVVP shall describe the relationship of the V&V processes to other processes, such as development, project management, quality assurance, and configuration management. The SVVP shall describe the lines of communication within the V&V effort, the authority for resolving issues raised by V&V tasks, and the authority for approving V&V products. Annex F illustrates a sample organizational interrelationship chart.

7.4.2 SVVP section 4.2: Master schedule

The SVVP shall describe the project life cycle and milestones and shall summarize the schedule of V&V tasks and task results as feedback to the development, organizational, and supporting processes (e.g., quality assurance and configuration management). V&V tasks should be scheduled to be reperformed according to the task iteration policy.

If the life cycle used in the SVVP differs from the life cycle model in this standard, this section shall describe how all requirements of the standard are satisfied (e.g., by cross-referencing to this standard).

7.4.3 SVVP section 4.3: Software integrity level scheme

The SVVP shall describe the agreed upon software integrity level scheme established for the system and the mapping of the selected scheme to the model used in this standard. The SVVP shall document (by inclusion or by reference to the criticality analysis) the assignment of software integrity levels to individual components (e.g., requirements, detailed functions, software modules, subsystems, or other software partitions), where there are differing software integrity levels assigned within the program.

7.4.4 SVVP section 4.4: Resources summary

The SVVP shall summarize the V&V resources, including staffing, facilities, tools, finances, and special procedural requirements (e.g., security, access rights, and documentation control).

7.4.5 SVVP section 4.5: Responsibilities

The SVVP shall identify an overview of the organizational element(s) and responsibilities for V&V tasks.

7.4.6 SVVP section 4.6: Tools, techniques, and methods

The SVVP shall describe documents, hardware and software V&V tools, techniques, methods, and operating and test environment to be used in the V&V process. Acquisition, training, support, and qualification information for each tool, technology, and method shall be included.

The SVVP should document the measures to be used by V&V (see Annex E) and should describe how these measures support the V&V objectives.

7.5 SVVP section 5: V&V processes

The SVVP shall identify V&V activities and tasks to be performed for each of the V&V processes described in Clause 5 of this standard, and shall document those V&V activities and tasks. The SVVP shall contain an overview of the V&V activities and tasks for all software life cycle processes.

The SVVP shall address the following topics for each V&V activity.

7.5.1 SVVP sections 5.1 through 5.6: Software life cycle³

The SVVP shall include sections 5.1 through 5.6 for V&V activities and tasks as shown in the SVVP outline (boxed text).

The SVVP shall address the following eight topics for each V&V activity:

³Software life cycle V&V sections are 5.1 Process: Management, 5.2 Process: Acquisition, 5.3 Process: Supply, 5.4 Process: Development, 5.5 Process: Operation, and 5.6 Process: Maintenance.

1) V&V tasks

The SVVP shall identify the V&V tasks to be performed. Table 1 describes the minimum V&V tasks, task criteria, and required inputs and outputs. Table 2 specifies the minimum V&V tasks that shall be performed for each software integrity level.

The minimum tasks for software integrity level 4 are consolidated in graphic form in Figure 1.

2) Methods and procedures

The SVVP shall describe the methods and procedures for each task, including on-line access, and conditions for observation/evaluation of development processes. The SVVP shall define the criteria for evaluating the task results.

3) Inputs

The SVVP shall identify the required inputs for each V&V task. The SVVP shall specify the source and format of each input. The inputs required for the minimum V&V tasks are identified in Table 1. Other inputs may be used. For any V&V activity and task, all of the required inputs and outputs from preceding activities and tasks may be used, but for conciseness, only the primary inputs are listed in Table 1.

4) Outputs

The SVVP shall identify the required outputs from each V&V task. The SVVP shall specify the purpose, format, and recipients of each output. The required outputs from each of the V&V tasks are identified in Table 1. Other outputs may be produced.

The outputs of the management of V&V and of the V&V tasks shall become inputs to subsequent processes and activities, as appropriate (see Clause 6).

5) Schedule

The SVVP shall describe the schedule for the V&V tasks. The SVVP shall establish specific milestones for initiating and completing each task, for the receipt and criteria of each input, and for the delivery of each output.

6) Resources

The SVVP shall identify the resources for the performance of the V&V tasks. The SVVP shall specify resources by category (e.g., staffing, equipment, facilities, travel, and training). The costs of V&V activities and resources shall be provided or referenced.

7) Risks and assumptions

The SVVP shall identify the risks (e.g., schedule, resources, or technical approach) and assumptions associated with the V&V tasks. The SVVP shall provide recommendations to eliminate, reduce, or mitigate risks.

8) Roles and responsibilities

The SVVP shall identify the organizational elements or individuals responsible for performing the V&V tasks.

7.6 SVVP section 6: V&V reporting requirements

The SVVP shall specify the purpose, content, format, recipients, and timing of all V&V reports. The V&V reporting requirements are specified in Clause 6.

7.7 SVVP section 7: V&V administrative requirements

The SVVP shall describe the anomaly resolution and reporting, task iteration policy, deviation policy, control procedures, and standards, practices, and conventions.

7.7.1 SVVP section 7.1: Anomaly resolution and reporting

The SVVP shall describe the method of reporting and resolving anomalies, including the criteria for reporting an anomaly; the anomaly report distribution list; the authority and time lines for resolving anomalies; and the anomaly criticality levels. Classification for software anomalies may be found in IEEE Std 1044^{TM} -1993 [B8].

7.7.2 SVVP section 7.2: Task iteration policy

The SVVP shall describe the criteria used to determine the extent to which a V&V task should be repeated when its input is changed or task procedure is changed. These criteria may include assessments of change, software integrity level, and effects on budget, schedule, and quality.

7.7.3 SVVP section 7.3: Deviation policy

The SVVP shall describe the procedures and criteria used to deviate from the plan. The information required for deviations shall include task identification, rationale, and effect on software quality. The SVVP shall identify the authorities responsible for approving deviations.

7.7.4 SVVP section 7.4: Control procedures

The SVVP shall identify control procedures applied to the V&V effort. These procedures shall describe how software products and V&V results should be configured, protected, and stored.

These procedures may describe quality assurance, configuration management, data management, or other activities if they are not addressed by other efforts. The SVVP shall describe how the V&V effort shall conform to existing security provisions and how the validity of V&V results shall be protected from unauthorized alterations.

7.7.5 SVVP section 7.5: Standards, practices, and conventions

The SVVP shall identify the standards, practices, and conventions that govern the performance of V&V tasks including internal organizational standards, practices, and policies.

7.8 SVVP section 8: V&V test documentation requirements

The SVVP shall describe the purpose, format, and content for the following V&V test documents:

- 1) Test plan
- 2) Test design
- 3) Test cases
- 4) Test procedures
- 5) Test results

The V&V effort may define the format for these documents. IEEE Std 829-1998 [B4] contains sample formats for these test documents.
5.1.1 Activity: Management of the V&V Effort (Process: Management)				
	V&V tasks	Required inputs ^a	Required outputs	
(1) SV a) b) c) d) See Cl.	VP generation Generate an SVVP for all life cycle processes. The SVVP may require updating throughout the life cycle. Outputs of other activities are inputs to the SVVP. Establish a baseline SVVP prior to the Requirements V&V activities. Identify project milestones in the SVVP. Schedule V&V tasks to support project management reviews and technical reviews. ause 7 for an example SVVP outline and content of the SVVP.	SVVP (previous update) Contract Concept documentation (e.g., statement of need, advance planning report, project initiation memo, feasibility studies, system requirements, governing regulations, procedures, policies, customer acceptance criteria and requirements, acquisition documentation, business rules, draft system architecture) Supplier development plans and schedules	SVVP and updates	
(2) Pro a) b) c)	 by posed/baseline change assessment Evaluate proposed software changes (i.e., modifications, enhancements, and additions as a result of anomaly corrections or requirement changes) for effects on the systems and previously completed V&V tasks. Plan iteration of affected tasks or initiate new tasks to address software proposed changes or baseline changes associated with an iterative development process. Verify and validate that the change is consistent with system requirements and does not adversely affect requirements directly or indirectly. An adverse effect is a change that could create new system hazards and risks. 	SVVP Proposed changes Hazard analysis report Risks identified by V&V tasks Supplier development plans and schedules Developer products (produced to date)	Task report(s)— Proposed/ baseline change assessment Updated SVVP Anomaly report(s)	

Table 1—V&V tasks, inputs, and outputs

5.1.1 Activity: Management of the V&V Effort (Process: Management) (continued)				
	V&V tasks	Required inputs ^a	Required outputs	
(3) Ma a) b) c) d) e) f) g) h) i) j)	 anagement review of the V&V effort Review and summarize the V&V effort to define changes to V&V tasks or to redirect the V&V effort. Evaluate each anomaly for its impact on the software system and assess whether it is a critical anomaly (e.g., IEEE Std 1044-1993 [B8]). The scope and application of V&V activities and tasks shall be revised to address the causes of these anomalies and risks. Recommend whether to proceed to the next set of V&V and development life cycle activities, and provide task reports, anomaly reports, and V&V Activity Summary Reports to the organizations identified in the SVVP. Verify that all V&V tasks conform to task requirements defined in the SVVP. Verify that V&V task results have a basis of evidence supporting the results. Assess all V&V results and provide recommendations for program acceptance and certification as input to the V&V final report. Use results of review to identify process improvement opportunities in the conduct of V&V. Review the quality of the products and services to ensure they meet customer requirements Review the program risks and initiate actions to mitigate above threshold risks. Review program measures to ensure the quality of products 	SVVP and updates Supplier development plans and schedules Anomaly reports V&V task results [e.g., technical accomplishments, V&V reports, resource utilization, V&V measures (see Annex E), plans, and identified risks]	outputs Task report(s)— Recommen- dations Updated SVVP V&V activity summary reports Recommen- dations to the V&V final report	
The m (e.g., I	and processes. anagement review of V&V may use any review methodology EEE Std 1028-1997 [B7]).			
(4) Ma a)	anagement and technical review support Support project management reviews and technical reviews (e.g., preliminary design review, and critical design review) by assessing the review materials, attending the reviews, and providing task reports and anomaly reports.	V&V task results Materials for review (e.g., SRS, IRS, SDD, IDD, test documents)	Task report(s)— Review results Anomaly report(s)	
b) The m	Verify timely delivery according to the approved schedule of all software products and documents.			
metho				
(5) Int a)	Coordinate the V&V effort with organizational (e.g., management, improvement) and supporting processes (e.g., quality assurance, joint review, and problem resolution).	Data identified in the SVVP from organizational and	Updated SVVP	
c)	Document the data exchange requirements in the SVVP.	supporting processes		

5.1.1 Activity: Management of the V&V Effort (Process: Management) (continued)						
	V&V tasks Required inputs ^a Required outputs					
(6) Ide V&V	ntify process improvement opportunities in the conduct of	SVVP	Updated SVVP			
a)	Gather and analyze the lessons learned.	Results of analyses	Input to the end			
b)	Gather and analyze the risks identified.	Prior end of activity	of activity report			
c)	Gather and analyze the V&V measures.	reports	Input to the final			
d)	Identify and analyze deficiencies in the V&V process.		report			
e)	Determine and implement corrective actions (e.g., repeat V&V tasks or conduct a new V&V task to address the corrective action or use a different method/technique for executing a V&V task).	Task reports	New/updated V&V policies/ procedures/ reports			
f)	Monitor the efficacy of the corrective actions.					
g)	Document findings in final report.		Updated V&V infrastructure			

5.2.1 Activity: Acquisition support V&V (Process: Acquisition)			
	V&V tasks	Required inputs	Required outputs
(1) Scoping the V&V effort		Preliminary system	SVVP
a)	criticality, risk, safety level, security level, desired performance, reliability, or other project-unique	Statement of need	
	the user.	Draft RFP or tender	
b)	Adopt the system integrity scheme assigned to the project. If no system integrity level scheme exists, then one is selected.	System integrity level scheme	
c)	Assign a software integrity level to the system and the software.		
d)	Establish the degree of independence (see Annex C), if any, required for the V&V.		
e)	Determine the minimum V&V tasks for the software integ- rity level using Table 2 and the selected software integrity level scheme.		
f)	Determine the extent of V&V on reuse software selected for the program (see Annex D).		
g)	Determine the extent of V&V for tools that insert or translate code (e.g., optimizing compilers, auto-code generators).		
h)	Augment the minimum V&V tasks with optional V&V tasks, as necessary.		
i)	Provide an estimate of the V&V budget, including test facili- ties and tools as required.		

5.2.1 Activity: Acquisition support V&V (Process: Acquisition) (continued)			
	V&V tasks	Required inputs	Required outputs
(2) Plan a) b) c) d) e)	 nning the interface between the V&V effort and supplier (Preparing the preliminary data and processes for the interface with a supplier to be selected in the supply process) Plan the V&V schedule for each V&V task. Identify the preliminary list of development processes and products to be evaluated by the V&V processes. Describe V&V access rights to proprietary and classified information. Coordinated the plan with the acquirer. Incorporate the project software integrity level scheme into the planning process. 	SVVP Draft RFP or tender Contract	Task Report(s)— Recommen- dations for RFP or tender Updated SVVP
(3) Syst a) b)	 tem requirements review Review the system requirements (e.g., system requirements specification, feasibility study report, business rules description) in the RFP or tender to Verify the consistency of requirements to user needs. Validate whether the requirements can be satisfied by the defined technologies, methods, and algorithms defined for the project (feasibility). Verify whether objective information that can be demonstrated by testing is provided in the requirements (testability). Review other requirements such as deliverable definitions, listing of appropriate compliance standards and regulations, user needs, etc., for completeness, correctness, and accuracy. 	Preliminary system description Statement of need User needs Draft RFP or tender	Task report(s)— System requirements review Anomaly report(s)
(4) Acc a) b) c) d) e)	Ceptance support (The following V&V activities support acceptance in the acquisition process. The activities are described in the development process where required inputs for the V&V activities are generated to aid the understanding of the activity flow.) Acceptance V&V test plan generation (5.4.2, Task 6) Acceptance V&V test design generation (5.4.3, Task 10) Acceptance V&V test case generation (5.4.4., Task 8) Acceptance V&V test procedure generation (5.4.5, Task 2) Acceptance V&V test execution (5.4.5, Task 5)	Concept documentation SDD IDD SRS IRS Source code Executable code User documentation Test plans, designs, cases, procedures, results Acceptance test plan	Task report(s)— Acceptance V&V test plan, design(s), cases, procedures, test results Anomaly report(s)

	5.3.1 Activity: Planning V&V (Process: Supply)					
	V&V tasks Required inputs					
(1) Pla	nning	the interface between the V&V effort and supplier	SVVP	Updated SVVP		
	(Co cess	ordinating and documenting the interface data and pro- es with the selected supplier)	Contract			
a)	Rev coor	iew the supplier development plans and schedules to rdinate the V&V effort with development activities.	Supplier development plans and schedules			
b)	Esta the	blish procedures to exchange V&V data and results with development effort.	r			
c)	Coo	ordinate the plan with the supplier.				
(2) Co	ntract	tverification	SVVP	Task		
a)	Ver 1) 2) 3) 4)	ify the following: System requirements (from RFP or tender, and con- tract) satisfy and are consistent with user needs Procedures are documented for managing requirement changes and for identifying the management hierarchy to address problems Procedures for interface and cooperation among the parties are documented, including ownership, warranty, copyright, and confidentiality Acceptance criteria and procedures are documented in accordance with requirements	RFP or tender Contract User needs Supplier development plans and schedules	Report(s)— Contract verification Updated SVVP Anomaly report(s)		

	5.4.1 Activity: Concept V&V (Process: Development)				
		V&V tasks	Required inputs	Required outputs	
(1) Concept documentation evaluation			Concept	Task report(s)—	
a)	a) Validate that the concept documentation satisfies user needs and is consistent with acquisition needs.		documentation	Concept documentation	
b)	Val limi	Validate constraints of interfacing systems and constraints or limitations of proposed approach.	plans and schedules	Anomaly	
c)	Ana sati:	lyze system requirements and validate that the following sfy user needs:	User needs	report(s)	
	1)	System functions	Acquisition needs		
	2)	End-to-end system performance			
	3)	Feasibility and testability of the functional requirements			
	4)	System architecture design			
	5)	Operation and maintenance requirements and environments			
	6)	Migration requirements from an existing system where applicable.			

5.4.1 Activity: Concept V&V (Process: Development) (continued)			
	V&V tasks	Required inputs	Required outputs
(2) Cri a) b)	iticality analysis Determine whether software integrity levels are established for requirements, detailed functions, software modules, subsystem, or other software partitions. Verify that the assigned software integrity levels are correct.	Concept documentation (system requirements) Developer integrity level assignments	Task Report(s)— Criticality analysis
	If software integrity levels are not assigned, then assign soft- ware integrity levels to the system requirements.	lever assignments	report(s)
c)	Document the software integrity level assigned to individual software components (e.g., requirements, detailed functions, software modules, subsystems, or other software partitions). For V&V planning purposes, the software system shall be assigned the same integrity level as the highest level assigned to any individual element.		
d)	Verify whether any software component can influence indi- vidual software components assigned a higher software integrity level, and if such conditions exist, then assign that software component the same higher software integrity level.		
(3) Ha	rdware/software/user requirements allocation analysis	User needs	Task report(s)—
Verify require against	the correctness, accuracy, and completeness of the concept ment allocation to hardware, software, and user interfaces user needs.	Concept documentation	software/user requirements allocation
a)	Correctness Verify that performance requirements (e.g., timing, response time, and throughput) allocated to hardware, software, and user interfaces satisfy user needs.		Anomaly report(s)
b)	Accuracy Verify that the internal and external interfaces specify the data formats, interface protocols, frequency of data exchange at each interface, and other key performance requirements to demonstrate satisfaction of user requirements.		
c)	 Completeness 1) Verify that application specific requirements such as functional diversity, fault detection, fault isolation, and diagnostic and error recovery satisfy user needs. 		
	2) Verify that the user's maintenance requirements for the system are completely specified.		
	3) Verify that the migration from existing system and replacement of the system satisfy user needs.		
(4) Tra	nceability analysis	Concept	Task report(s)—
a)	Identify all system requirements that will be implemented completely or partially by software.	documentation	Traceability analysis
b)	Verify that these system requirements are traceable to acqui- sition needs.		Anomaly report(s)
c)	Start the software requirements traceability analysis with system requirements.		

5.4.1 Activity: Concept V&V (Process: Development) (continued)			
	V&V tasks	Required inputs	Required outputs
(5) Ha a)	 zard analysis Analyze the potential hazards to and from the conceptual system. The analysis shall 1) Identify the potential system hazards 2) Assess the severity of each hazard 3) Assess the probability of each hazard 4) Identify mitigation strategies for each hazard 	Concept documentation	Task report(s)— Hazard analysis Anomaly report(s)
(6) Sec a)	curity analysis Review the system owner's definition of an acceptable level of security risk.	Concept documentation	Task report(s— Security analysis
b)	Analyze the system concept from a security perspective, and ensure that potential security risks with respect to confidenti- ality (disclosure of sensitive information/data), integrity (modification of information/data), availability (withholding of information or services), and accountability (attributing actions to an individual/ process) have been identified. Include an assessment of the sensitivity of the information/ data to be processed.	Preliminary threat and risk assessment (TRA)	Anomaly report(s)
c)	Analyze security risks introduced by the system itself as well as those associated with the environment with which the sys- tem interfaces.		
(7) Ris	k analysis	Concept	Task
a)	Identify the technical and management risks.	documentation	Report(s)—Risk analysis
6)	the risks.	Supplier development plans and schedules Hazard analysis report	Anomaly report(s)
		V&V task results	

5.4.2 Activity: Requirements V&V (Process: Development)				
		V&V tasks	Required inputs	Required outputs
 (1) Traceability analysis Trace the software requirements (SRS and IRS) to system requirements (concept documentation) and system requirements to the software requirements. Analyze identified relationships for correctness, consistency, completeness, and accuracy. The task criteria are a) Correctness Validate that the relationships between each software requirement and its system requirement are correct. b) Consistency Verify that the relationships between the software and system requirements are specified to a consistent level of detail. c) Completeness Verify that every software requirement is traceable to a system requirement with sufficient detail to show conformance to the system requirement. 		Concept documentation (system requirements) SRS IRS	Task Report(s)— Traceability analysis Anomaly report(s)	
d)	Acc Vali teris requ	are traceable to software requirements. uracy idate that the system performance and operating charac- stics are accurately specified by the traced software uirements.		
(2) Sof Evalua qualifie docum mainte comple are a)	ftware the the cation entation entation eteness Cort 1) 2) 3) 4) 5)	e requirements evaluation requirements (e.g., functional, capability, interface, , safety, security, human factors, data definitions, user on, installation and acceptance, user operation, and user) of the SRS and IRS for correctness, consistency, s, accuracy, readability, and testability. The task criteria rectness Verify and validate that the software requirements satisfy the system requirements allocated to software within the assumptions, constraints, and operating environment for the system. Verify that the software requirements comply with standards, references, regulations, policies, physical laws, and business rules. Validate the sequences of states and state changes using logic and data flows coupled with domain expertise, prototyping results, engineering principles, or other basis. Validate that the flow of data and control satisfy functionality and performance requirements. Validate data usage and format.	Concept documentation SRS IRS	Task report(s)— Software requirements evaluation Anomaly report(s)

5.4.2 Activity: Requirements V&V (Process: Development) (continued)				
		V&V tasks	Required inputs	Required outputs
(2) Sof	tware	e requirements evaluation (continued)		
b)	Cor	sistency		
	1)	Verify that all terms and concepts are documented consistently.		
	2)	Verify that the function interactions and assumptions are consistent and satisfy system requirements and acquisition needs.		
	3)	Verify that there is internal consistency between the software requirements and external consistency with the system requirements.		
c)	Cor	npleteness		
	1)	Verify that the following elements are in the SRS or IRS, within the assumptions and constraints of the system:		
		 Functionality (e.g., algorithms, state/mode definitions, input/output validation, exception handling, reporting and logging) 		
		ii) Process definition and scheduling		
		iii) Hardware, software, and user interface descriptions		
		iv) Performance criteria (e.g., timing, sizing, speed, capacity, accuracy, precision, safety, and security)		
		v) Critical configuration data		
		vi) System, device, and software control (e.g., initialization, transaction and state monitoring, self-testing)		
	2)	Verify that the SRS and IRS satisfy specified configura- tion management procedures.		
d)	Acc	Puracy		
	1)	Validate that the logic, computational, and interface precision (e.g., truncation and rounding) satisfy the requirements in the system environment.		
	2)	Validate that the modeled physical phenomena conform to system accuracy requirements and physical laws.		
e)	Rea	dability		
	1)	Verify that the documentation is legible, understand- able, and unambiguous to the intended audience.		
	2)	Verify that the documentation defines all acronyms, mnemonics, abbreviations, terms, and symbols.		
f)	Tes	tability		
	Ver ing	ify that there are objective acceptance criteria for validat- the requirements of the SRS and IRS.		

5.4.2 Activity: Requirements V&V (Process: Development) (continued)			
	V&V tasks	Required inputs	Required outputs
 (3) Intervention (3) Intervention (3) Verify hardway complete a) b) c) d) e) 	erface analysis and validate that the requirements for software interfaces with are, user, operator, and other systems are correct, consistent, ete, accurate, and testable. The task criteria are Correctness Validate the external and internal system and software inter- face requirements. Consistency Verify that the interface descriptions are consistent between the SRS and IRS. Completeness Verify that each interface is described and includes data for- mat and performance criteria (e.g., timing, bandwidth, accu- racy, safety, and security). Accuracy Verify that each interface provides information with the required accuracy. Testability Verify that there are objective acceptance criteria for validat- ing the interface requirements.	Concept documentation IRS	Task report(s)— Interface analysis Anomaly report(s)
(4) Cri a) b)	iticality analysis Review and update the existing criticality analysis results from the prior criticality task report using the SRS and IRS. Implementation methods and interfacing technologies may cause previously assigned software integrity levels to be raised or lowered for a given software element (i.e., require- ment, module, function, subsystem, other software partition). Verify that no inconsistent or undesired software integrity consequences are introduced by reviewing the revised soft- ware integrity levels.	Criticality task report SRS IRS	Task report(s)— Criticality analysis Anomaly report(s)

5.4.2 Activity: Requirements V&V (Process: Development) (continued)					
			V&V tasks	Required inputs	Required outputs
(5) Syst a)	 (5) System V&V test plan generation a) Software integrity levels 3 and 4 1) Plan System V&V testing to validate software require- 		Concept documentation (system requirements)	Task report(s)— System V&V test plan	
	2)	men Plan	ts.	SRS	Anomaly report(s)
	3)	case Plan	s, procedures, and results.	IRS	
	<i></i>	and	results.	User documentation	
	4)	i)	System V&V test plan shall address the following: Conformance to all system requirements (e.g., functional, performance, security, operation, and maintenance) as complete software end items in the system environment	System test plan	
		11)	materials, procedural changes)		
		iii)	Performance at boundaries (e.g., data, interfaces) and under stress conditions		
	5)	Veri lowi	ify that the System V&V test plan satisfies the fol- ing criteria:		
		i)	Conformance to project-defined test document purpose, format, and content (e.g., see IEEE Std 829-1998 [B4])		
		ii)	Test coverage of system requirements		
	6)	Vali lowi	date that the System V&V test plan satisfies the fol- ing criteria:		
		i)	Appropriateness of test methods and standards used		
		ii)	Conformance to expected results		
		iii)	Feasibility of system qualification testing		
		iv)	Feasibility and testability of operation and mainte- nance requirements		
b)	Soft	ware	integrity levels 1 and 2		
	1)	Veri	ify that the developer's system test plan satisfies the		
		tollo	owing criteria:		
		1)	purpose, format, and content (e.g., see IEEE Std 829-1998 [B4]).		
		ii)	Test coverage of system requirements		
	2)	Vali the f	date that the developer's system test plan satisfies following criteria:		
		i)	Appropriateness of test methods and standards used		
		ii)	Conformance to expected results		
		iii)	Feasibility of system qualification testing		
		iv)	Capability to be operated and maintained		

5.4.2 Activity: Requirements V&V (Process: Development) (continued)				
		V&V tasks	Required inputs	Required outputs
(6) Acc a)	eptan Soft 1) 2) 3) 4)	 hee V&V test plan generation tware integrity levels 3 and 4 Plan Acceptance V&V testing to validate that the software correctly implements system and software requirements in an operational environment. Plan tracing of acceptance test requirements to test design, cases, procedures, and execution results. Plan documentation of test tasks and results. The Acceptance V&V test plan shall address the following: Conformance to acceptance requirements in the operational environment 	Concept documentation SRS IRS User documentation Acceptance test plan	Task report(s)— Acceptance V&V test plan Anomaly report(s)
	5) 6)	 ii) Adequacy of user documentation Verify that the Acceptance V&V test plan satisfies the following criteria: i) Conformance to project-defined test document purpose, format, and content (e.g., see IEEE Std 829-1998 [B4]) ii) Test coverage of acceptance requirements Validate that the Acceptance V&V test plan satisfies the following criteria: 		
		 i) Conformance to expected results ii) Feasibility of operation and maintenance (e.g., capability to be operated and maintained in accordance with user needs) 		
b)	Sof 1)	Ware integrity level 2 Verify that the acquirer's Acceptance Test Plan con- forms to project-defined test document purpose, format, and content (e.g., see IEEE Std 829-1998 [B4]).		
	2)	 Validate that the acquirer's acceptance test plan satisfies the following criteria i) Test coverage of acceptance requirements ii) Conformance to expected results iii) Feasibility of operation and maintenance (e.g., capability to be operated and maintained in accordance with user needs) 		
c)	Sof The	tware integrity level 1 re are no acceptance test requirements.		

5.4.2 Activity: Requirements V&V (Process: Development) (continued)				
V&V tasks	Required inputs	Required outputs		
 (7) Configuration management assessment Verify that the configuration management process is complete and adequate. The task criteria are a) Completeness Verify that there is a process for describing the software product functionality, tracking program versions, and managing changes. b) Adequacy Verify that the configuration management process is adequate for the development complexity, software and system size, software integrity level, project plans, and user needs. 	Software configuration management process documentation	Task report(s)— Configuration management assessment Anomaly report(s)		
 (8) Hazard analysis a) Determine software contributions to system hazards. The hazard analysis shall 1) Identify the software requirements that contribute to each system hazard. 2) Validate that the software addresses, controls, or mitigates each hazard. 	SRS IRS Hazard analysis report	Task report(s)— Hazard analysis Anomaly report(s)		
 (9) Security analysis a) Determine that the security requirements identified in the SRS and IRS address the security risks introduced by the system concept. b) Verify that the system security requirements will mitigate the identified security risks to an acceptable level. 	SRS IRS Preliminary TRA	Task report(s)— Security analysis Anomaly report(s)		
 (10) Risk analysis a) Review and update risk analysis using prior task reports. b) Provide recommendations to eliminate, reduce or mitigate the risks. 	Concept documentation SRS IRS Supplier development plans and schedules Hazard analysis report Security analysis V&V task results	Task report(s)— Risk analysis Anomaly report(s)		

5.4.3 Activity: Design V&V (Process: Development)				
		V&V tasks	Required inputs	Required outputs
(1) Tra	ceabi	lity analysis	SRS	Task report(s)—
Trace d IRS), at	lesign nd req	elements (SDD and IDD) to requirements (SRS and uirements to design elements. Analyze relationships for	SDD	analysis
a)	Corr	ectness	IRS	report(s)
	Vali the s	date the relationship between each design element and offware requirement(s).	IDD	
b)	Con	sistency		
	Veri the s of de	fy that the relationships between the design elements and software requirements are specified to a consistent level etail.		
c)	Com	pleteness		
	1)	Verify that all design elements are traceable from the software requirements.		
	2)	Verify that all software requirements are traceable to the design elements.		
(2) Soft	tware	design evaluation		
Evaluat consiste task cri	te the o ency, o teria a	design elements (SDD and IDD) for correctness, completeness, accuracy, readability, and testability. The re		
a)	Corr	ectness		
	1)	Verify and validate that the software design satisfies the software requirements.		
	2)	Verify that the software design complies with stan- dards, references, regulations, policies, physical laws, and business rules.		
	3)	Validate the design sequences of states and state changes using logic and data flows coupled with domain expertise, prototyping results, engineering prin- ciples, or other basis.		
	4)	Validate that the flow of data and control satisfy func- tionality and performance requirements.		
	5)	Validate data usage and format.		
	6)	Assess the appropriateness of design methods and stan- dards used.		
b)	Con	sistency		
	1)	Verify that all terms and design concepts are documented consistently.		
	2)	Verify that there is internal consistency between the design elements and external consistency with architectural design.		

5.4.3 Activity: Design V&V (Process: Development) (continued)				
		V&V tasks	Required inputs	Required outputs
(2) Sot	ftware	e design evaluation <i>(continued)</i>	SRS	Task report(s)—
c)	Con 1)	verify that the following elements are in the SDD.	IRS	evaluation
	-)	within the assumptions and constraints of the system:	SDD	Anomaly
		i) Functionality (e.g., algorithms, state/mode definitions, input/output validation, exception	IDD	report(s)
		handling, reporting and logging)	Design standards	
		ii) Process definition and schedulingiii) Hardware, software, and user interface descriptions	(e.g., standards, practices, and conventions)	
		iv) Performance criteria (e.g., timing, sizing, speed, capacity, accuracy, precision, safety, and security)		
		v) Critical configuration data		
		v1) System, device, and software control (e.g., initialization, transaction and state monitoring, and self-testing)		
	2)	Verify that the SDD and IDD satisfy specified configu- ration management procedures.		
d)	Acc	puracy		
	1)	Validate that the logic, computational, and interface precision (e.g., truncation and rounding) satisfy the requirements in the system environment.		
	2)	Validate that the modeled physical phenomena conform to system accuracy requirements and physical laws.		
e)	Rea	dability		
	1)	Verify that the documentation is legible, understand- able, and unambiguous to the intended audience.		
	2)	Verify that the documentation defines all acronyms, mnemonics, abbreviations, terms, symbols, and design language, if any.		
f)	Tes	tability		
	1)	Verify that there are objective acceptance criteria for validating each software design element and the system design.		
	2)	Verify that each software design element is testable to objective acceptance criteria.		

5.4.3 Activity: Design V&V (Process: Development) (continued)				
	V&V tasks	Required inputs	Required outputs	
(3) Int	erface analysis	Concept	Task report(s)—	
Verify user, o	and validate that the software design interfaces with hardware, perator, software, and other systems for correctness,	(system requirements)	analysis	
consist are	tency, completeness, accuracy, and testability. The task criteria	SRS	Anomaly report(s)	
a)	Correctness	IRS		
	Validate the external and internal software interface design in the context of system requirements.	SDD		
b)	Consistency	IDD		
	Verify that the interface design is consistent between the SDD and IDD.			
c)	Completeness			
	Verify that each interface is described and includes data for- mat and performance criteria (e.g., timing, bandwidth, accu- racy, safety, and security).			
d)	Accuracy			
	Verify that each interface provides information with the required accuracy.			
e)	Testability			
	Verify that there are objective acceptance criteria for validat- ing the interface design.			
(4) Cri	iticality analysis	Criticality task report	Task report(s)—	
a)	Review and update the existing criticality analysis results from the prior criticality task report using the SDD and IDD.	SDD	Criticality analysis	
b)	Implementation methods and interfacing technologies may cause previously assigned software integrity levels to be raised or lowered for a given software element (i.e., require- ment, module, function, subsystem, other software partition). Verify that no inconsistent or undesired software integrity consequences are introduced by reviewing the revised soft- ware integrity levels.	IDD	Anomaly report(s)	

	5.4.3 Activity: Design V&V (Process: Development) (continued)				
		V&V tasks	Required inputs	Required outputs	
(5) Cor	npon	ent V&V test plan generation	SRS	Component	
a)	Sof	tware integrity levels 3 and 4	SDD	V&V—Test	
	1)	Plan Component V&V testing to validate that the soft-	500	pian	
		ware components (e.g., units, source code modules)	IRS	Anomaly	
	2)	Plan tracing of design requirements to test design	מתו	report(s)	
	2)	cases, procedures, and results.			
	3)	Plan documentation of test tasks and results.	Component test plan		
	4)	The Component V&V test plan shall address the			
		following:			
		i) Conformance to design requirements			
		ii) Assessment of timing, sizing, and accuracy			
		iii) Performance at boundaries and interfaces and under stress and error conditions			
		iv) Measures of requirements test coverage and soft-			
		ware reliability and maintainability			
	5)	Verify that the Component V&V test plan conforms to			
		project-defined test document purpose, format, and content (e.g., see IEEE Std 829-1998 [B4]).			
	6)	Validate that the Component V&V test plan satisfies the following criteria:			
		i) Traceable to the software requirements and design			
		ii) External consistency with the software require-			
		ments and design			
		iii) Internal consistency between unit requirements			
		iv) Test coverage of requirements in each unit			
		v) Feasibility of software integration and testing			
		 vi) reasibility of operation and maintenance (e.g., capability to be operated and maintained in accor- dance with user needs) 			
b)	Soft	tware integrity level 2			
	1)	Verify that the developer's component test conforms to project-defined test document purpose, format, and content (e.g., see IEEE Std 829-1998 [B4]).			
	2)	Validate that the developer's component test plan satis- fies the following criteria:			
		i) Traceable to the software requirements and design			
		ii) External consistency with the software require- ments and design			
		iii) Internal consistency between unit requirements			
		iv) Test coverage of units			
		v) Feasibility of software integration and testing			
		vi) Feasibility of operation and maintenance (e.g.,			
		capability to be operated and maintained in accor-			
	Q~^	dance with user needs)			
()	50fl	iware integrity level 1			
1	rne	at at no component test requirements.			

	5.4.3 Activity: Design V&V (Process: Development) (continued)				
	V&V tasks			Required inputs	Required outputs
(6) Integration V&V test plan generation				SRS	Integration V&V
a)	For	software integrity levels 3 and 4	IRS	test plan	
	1)	Plan rectl	i integration testing to validate that the software cor-	(DD	Anomaly
		as e	ach software component (e.g., units or modules) is	SDD	report(s)
		incre	ementally integrated with each other.	IDD	
	2)	Plan cedu	a tracing of requirements to test design, cases, pro- ires, and results.	Integration test plan	
	3)	Plan	documentation of test tasks and results.		
	4)	The follo	Integration V&V test plan shall address the owing:		
		i)	Conformance to increasingly larger set of func- tional requirements at each stage of integration		
		i)	Assessment of timing, sizing, and accuracy		
		i)	Performance at boundaries and under stress conditions		
		i)	Measures of requirements test coverage and soft- ware reliability		
	5)	Veri follo	ify that the Integration V&V Test Plan satisfies the owing criteria:		
	Cor mat	forma , and c	ance to project-defined test document purpose, for- content (e.g., see IEEE Std 829-1998 [B4]).		
	6)	Vali	date that the Integration V&V test plan satisfies the		
		follo	owing criteria:		
		i)	Traceable to the system requirements		
		11)	External consistency with the system requirements		
		iii)	Internal consistency		
		iv)	Test coverage of the software requirements		
		v)	Appropriateness of test standards and methods used		
		vi)	Conformance to expected results		
		vii)	Feasibility of software qualification testing		
		viii)	Feasibility of operation and maintenance (e.g., capability to be operated and maintained in accordance with user needs).		

	5.4.3 Activity: Design V&V (Process: Development) (continued)			
		V&V tasks	Required inputs	Required outputs
6) Integration V&V test plan generation (continued)				
b)	Sof	tware integrity levels 1 and 2		
	1)	Verify that the developer's integration test plan con- forms to project-defined test document purpose, format, and content (e.g., see IEEE Std 829-1998 [B4]).		
	2)	Validate that the developer's integration test plan satis- fies the following criteria:		
		i) Traceable to the system requirements		
		ii) External consistency with the system requirements		
		iii) Internal consistency		
		iv) Test coverage of the software requirements		
		v) Appropriateness of test standards and methods		
		vi) Conformance to expected results		
		vii) Feasibility of software qualification testing		
		viii) Feasibility of operation and maintenance (e.g., capability to be operated and maintained in accor- dance with user needs)		
(7) Co	mpon	ent V&V test design generation	SDD	Component
a)	Sof	tware integrity levels 3 and 4		V&V test
	1)	Design tests for component testing.	IDD	design(s)
	2)	Continue tracing required by the Component V&V test plan.	User documentation	Anomaly report(s)
	3)	Verify that the Component V&V test designs conform	Test plans	
		to project-defined test document purpose, format, and content (e.g., see IEEE Std 829-1998 [B4]).	Test designs	
	4)	Validate that the Component V&V test designs satisfy the criteria in V&V activity 5.4.3, Task 5.		
b)	Sof	tware integrity level 2		
	1)	Verify that the developer's test designs for component testing conform to project-defined test document purpose, format, and content (e.g., see IEEE Std 829-1998 [B4]).		
	2)	Validate that the developer's component test designs satisfy the criteria in V&V activity 5.4.3, Task 5.		
c)	Sof	tware integrity level 1		
	The	ere are no component test requirements.		

	5.4.3 Activity: Design V&V (Process: Development) (continued)				
		V&V tasks	Required inputs	Required outputs	
(8) Integration V&V test design generation			SDD	Integration V&V	
a) b)	Sof 1) 2) 3) Sof	 tware integrity levels 3 and 4 Design tests for integration testing. Continue tracing required by the Integration V&V test plan. Verify that the Integration V&V test designs conform to project-defined test document purpose, format, and content (e.g., see IEEE Std 829-1998 [B4]). Validate that the Integration V&V test designs satisfy the criteria in V&V activity 5.4.3, Task 6. tware integrity levels 1 and 2 	IDD User documentation Test plans Test designs	test design(s) Anomaly report(s)	
	1) 2)	Verify that the developer's test designs for integration testing conform to project-defined test document pur- pose, format, and content (e.g., see IEEE Std 829-1998 [B4]). Validate that the developer's integration test designs satisfy the criteria in V&V activity 5.4.3, Task 6.			
(9) Sys	stem \	V&V test design generation	SDD	System V&V	
a) b)	Sof 1) 2) 3) Sof 1)	 Tware integrity levels 3 and 4 Design tests for system testing. Continue tracing required by the System V&V test plan. Verify that the System V&V test designs conform to project-defined test document purpose, format, and content (e.g., see IEEE Std 829-1998 [B4]). Validate that the System V&V test designs satisfy the criteria in V&V activity 5.4.2, Task 5 Tware integrity levels 1 and 2 Verify that the developer's test designs for system testing conform to project-defined test document purpose, format, and content (e.g., see IEEE Std 829-1998 [B4]). 	IDD User documentation Test plans Test designs	test design(s) Anomaly report(s)	
	2)	Validate that the developer's system test designs satisfy the criteria in V&V activity 5.4.2, Task 5.			

	5.4.3 Activity: Design V&V (Process: Development) (continued)					
	V&V tasks	Required inputs	Required outputs			
(10) A(a)	 cceptance V&V test design generation Software integrity levels 3 and 4 Design tests for acceptance testing. Continue tracing required by the Acceptance V&V test plan. Verify that the Acceptance V&V test designs conform to project-defined test document purpose, format, and content (e.g., see IEEE Std 829-1998 [B4]). Validate that the Acceptance V&V test designs satisfy the criteria in V&V activity 5.4.2, Task 6. 	SDD IDD User documentation Test plans Test designs	Acceptance V&V test design(s) Anomaly report(s)			
c)	 Verify that the acquirer's test designs for acceptance testing conform to project-defined test document pur- pose, format, and content (e.g., see IEEE Std 829-1998 [B4]). Validate that the acquirer's acceptance test designs sat- isfy the criteria in V&V activity 5.4.2, Task 6. Software integrity level 1 There are no acceptance test requirements. 					
(11) Ha a) b)	azard Analysis Verify that logic design and associated data elements correctly implement the critical requirements and introduce no new hazards. Update the hazard analysis.	SDD IDD Hazard analysis report	Task report(s)— Hazard analysis Anomaly report(s)			
 (12) Security analysis a) Verify that the architecture and detailed design outputs adequately address the identified security requirements. This verification includes both the system itself and security risks introduced as a result of interfacing with external components. 		SDD IDD	Task report(s)— Security analysis Anomaly report(s)			
(13) Ri a) b)	isk analysis Review and update risk analysis using prior task reports. Provide recommendations to eliminate, reduce, or mitigate the risks.	SDD IDD Supplier development plans and schedules Hazard analysis report Security analysis V&V task results	Task report(s)— Risk analysis Anomaly report(s)			

5.4.4 Activity: Implementation V&V (Process: Development)				
		V&V tasks	Required inputs	Required outputs
(1) Tra	aceabi	ility analysis	SDD	Task report(s)
Trace the source code components to corresponding design specification(s), and design specification(s) to source code components.			IDD Source code	Traceability analysis
Analyz comple a)	ze ider etenes Cor	ntified relationships for correctness, consistency, and s. The task criteria are rectness		report(s)
	Val nen	idate the relationship between the source code compo- ts and design element(s).		
b)	Con	sistency		
	Ver nem of d	ify that the relationships between the source code compo- ts and design elements are specified to a consistent level etail.		
c)	Con	npleteness		
	1)	Verify that all source code components are traceable from the design elements.		
	2)	Verify that all design elements are traceable to the source code components.		
(2) Sou	irce c	ode and source code documentation evaluation	Source code	Task report(s)—
Evalua docum	te the entatio	source code components (source code and source code on) for correctness, consistency, completeness, accuracy,	SDD	Source code and source code documentation
readab	ility, a	and testability. The task criteria are	IDD	evaluation
a)	Cor	rectness	Coding standards	Anomaly
	1)	Verify and validate that the source code component sat- isfies the software design.	(e.g., standards, practices, project	report(s)
	2)	Verify that the source code components comply with standards, references, regulations, policies, physical laws, and business rules.	restrictions, and conventions)	
	3)	Validate the source code component sequences of states and state changes using logic and data flows coupled with domain expertise, prototyping results, engineering principles, or other basis.	User documentation	
	4)	Validate that the flow of data and control satisfy func- tionality and performance requirements.		
	5)	Validate data usage and format.		
	6)	Assess the appropriateness of coding methods and standards.		

5.4.4 Activity: Implementation V&V (Process: Development) (continued)				
		V&V tasks	Required inputs	Required outputs
(2) Sou <i>(contir</i>	urce cod <i>1ued)</i>	e and source code documentation evaluation		
b)	Consis	stency		
	1) V c	Verify that all terms and code concepts are documented consistently.		
	1) V s	Verify that there is internal consistency between the source code components.		
	1) V a	Validate external consistency with the software design and requirements.		
c)	Compl	leteness		
	1) V c s	Verify that the following elements are in the source code, within the assumptions and constraints of the system:		
	i) Functionality (e.g., algorithms, state/mode definitions, input/output validation, exception handling, reporting and logging)		
	i	i) Process definition and scheduling		
	i	ii) Hardware, software, and user interface descriptions		
	i	v) Performance criteria (e.g., timing, sizing, speed, capacity, accuracy, precision, safety, and security)		
	v	7) Critical configuration data		
	V	System, device, and software control (e.g., initialization, transaction and state monitoring, and self-testing)		
	7) V s	Verify that the source code documentation satisfies pecified configuration management procedures.		
d)	Accura	acy		
	1) V p e	Validate the logic, computational, and interface precision (e.g., truncation and rounding) in the system environment.		
	2) V t	Validate that the modeled physical phenomena conform o system accuracy requirements and physical laws.		
e)	Reada	bility		
	1) V a	Verify that the documentation is legible, understand- ble, and unambiguous to the intended audience.		
	2) V n	Verify that the documentation defines all acronyms, nnemonics, abbreviations, terms, and symbols.		
f)	Testab	pility		
	1) V v	Verify that there are objective acceptance criteria for validating each source code component.		
	2) V a	Verify that each source code component is testable gainst objective acceptance criteria.		

5.4.4 Activity: Implementation V&V (Process: Development) (continued)			
	V&V tasks	Required inputs	Required outputs
(3) Int	erface analysis	Concept	Task report(s)—
Verify hardwa	and validate that the software source code interfaces with are, user, operator, software, and other systems for correctness,	(system requirements)	analysis
consist are	tency, completeness, accuracy, and testability. The task criteria	SDD	Anomaly report(s)
a)	Correctness	IDD	
	Validate the external and internal software interface code in the context of system requirements.	Source code	
b)	Consistency	User documentation	
	Verify that the interface code is consistent between source code components and to external interfaces (i.e., hardware, user, operator, and other software).		
c)	Completeness		
	Verify that each interface is described and includes data for- mat and performance criteria (e.g., timing, bandwidth, accu- racy, safety, and security).		
d)	Accuracy		
	Verify that each interface provides information with the required accuracy.		
e)	Testability		
	Verify that there are objective acceptance criteria for validat- ing the interface code.		
(4) Cri	iticality analysis	Criticality task report	Task report(s)—
a)	Review and update the existing criticality analysis results	Source code	Criticality
b)	Irom the prior criticality task report using the source code.		unary 515
0)	cause previously assigned software integrity levels to be raised or lowered for a given software element (i.e., requirement, module, function, subsystem, other software partition). Verify that no inconsistent or undesired software integrity consequences are introduced by reviewing the revised software integrity levels.		Anomaly report(s)

	5.4.4 Activity: Implementation V&V (Process: Development) (continued)			
		V&V tasks	Required inputs	Required outputs
(5) Co	mpon	ent V&V test case generation	SRS Component	
a)	Sof 1)	tware integrity levels 3 and 4 Develop V&V test cases for component testing.	IRS	V&V test cases
	2)	Continue tracing required by the Component V&V test plan.	SDD	report(s)
	3)	Verify that the Component V&V test cases conform to project-defined test document purpose, format, and content (e.g., see IEEE Std 829-1998 [B41]).	IDD User documentation	
	4)	Validate that the Component V&V test cases satisfy the criteria in V&V activity 5.4.3, Task 5.	Test design	
b)	Sof	tware integrity level 2	Test cases	
	1)	Verify that the developer's component test cases con- form to project-defined test document purpose, format, and content (e.g., see IEEE Std 829-1998 [B4]).		
	2)	Validate that the developer's component test cases sat- isfy the criteria in V&V activity 5.4.3, Task 5.		
c)	Sof	tware integrity level 1		
	The	ere are no component test requirements.		
(6) Int	egrat	ion V&V test case generation	SRS	Integration V&V
a)	Sof	tware integrity levels 3 and 4	IDC	test cases
	1)	Develop V&V test cases for integration testing.	IKS	Anomaly
	2)	Continue tracing required by the Integration V&V test plan.	SDD	report(s)
	3)	Verify that the Integration V&V test cases conform to project-defined test document purpose, format, and	IDD	
	4)	content (e.g., see IEEE Std 829-1998 [B4]). Validate that the Integration V&V test cases satisfy the	Test design	
1	C (criteria in V&V activity 5.4.3, Task 6.	Test asses	
b)	Sot	Ware integrity levels 1 and 2	rest cases	
	1)	form to project-defined test document purpose, format, and content (e.g., see IEEE Std 829-1998 [B4]).		
	2)	Validate that the developer's integration test cases sat- isfy the criteria in V&V activity 5.4.3, Task 6.		

	5.4.4 Activity: Implementation V&V (Process: Development) (continued)			
		V&V tasks	Required inputs	Required outputs
(7) Sys	tem V	&V test case generation	SRS	System V&V
a)	Soft 1) 2)	tware integrity levels 3 and 4 Develop V&V test cases for system testing.	IRS	test cases Anomaly
	3)	plan. Verify that the System V&V test cases conform to	IDD	report(s)
		content (e.g., see IEEE Std 829-1998 [B4]).	User documentation	
	4)	Validate that the System V&V test cases satisfy the cri- teria in V&V activity 5.4.2, Task 5.	Test design	
b)	Soft	ware integrity levels 1 and 2	Test cases	
	1)	Verify that the developer's system test cases conform to project-defined test document purpose, format, and content (e.g., see IEEE Std 829-1998 [B4]).		
	2)	Validate that the developer's system test cases satisfy the criteria in V&V activity 5.4.2, Task 5.		
(8) Acc	eptai	nce V&V test case generation	SRS	Acceptance
a)	Soft 1)	tware integrity levels 3 and 4 Develop V&V test cases for acceptance testing.	IRS	V&V test cases
	2)	Continue tracing required by the Acceptance V&V test plan.	SDD	report(s)
	3)	Verify that the Acceptance V&V test cases conform to	IDD	
		content (e.g., see IEEE Std 829-1998 [B4]).	User documentation	
	4)	Validate that the Acceptance V&V test cases satisfy the criteria in V&V activity 5.4.2, Task 6.	Test design	
b)	Soft	tware integrity level 2	Test cases	
	1)	Verify that the acquirer's acceptance test cases conform to project-defined test document purpose, format, and content (e.g., see IEEE Std 829-1998 [B4]).		
	2)	Validate that the acquirer's acceptance test cases satisfy the criteria in V&V activity 5.4.2, Task 6.		
c)	Sof	tware integrity level 1		
	The	re are no acceptance test requirements.		

	5.4.4 Activity: Implementation V&V (Process: Development) (continued)			
		V&V tasks	Required inputs	Required outputs
(9) Co	mpon	ent V&V test procedure generation	SRS	Component
a)	Sof 1)	tware integrity levels 3 and 4 Develop V&V test procedures for component testing.	IRS	V&V test procedures
	2)	Continue tracing required by the Component V&V test plan.	SDD	Anomaly report(s)
	3)	Verify that the Component V&V test procedures con- form to project-defined test document purpose, format,	IDD	
		and content (e.g., see IEEE Std 829-1998 [B4]).	User documentation	
	4)	Validate that the Component V&V test procedures sat- isfy the criteria in V&V activity 5.4.3, Task 5.	Test cases	
b)	Sof	tware integrity level 2	Test procedures	
	1)	Verify that the developer's component test procedures conform to project-defined test document purpose, for- mat, and content (e.g., see IEEE Std 829-1998 [B4]).		
	2)	Validate that the developer's component test proce- dures satisfy the criteria in V&V activity 5.4.3, Task 5.		
c)	Sof	tware integrity level 1		
	The	ere are no component test requirements.		
(10) In	tegra	tion V&V test procedure generation	SRS	Integration V&V
a)	Sof	tware integrity levels 3 and 4	IDC	test procedures
	1)	Develop V&V test procedures for Integration testing.	IKS	Anomaly
	2)	Continue tracing required by the Integration V&V test plan.	SDD	report(s)
	3)	Verify that the Integration V&V test procedures con- form to project-defined test document purpose, format, and content (e.g., see IEEE Std 829-1998 [B4]).	IDD User documentation	
	4)	Validate that the Integration V&V test procedures sat- isfy the criteria in V&V activity 5.4.3, Task 6.	Test cases	
b)	Sof	tware integrity levels 1 and 2	Test procedures	
	1)	Verify that the developer's integration test procedures conform to project-defined test document purpose, for- mat, and content (e.g., see IEEE Std 829-1998 [B4]).		
	2)	Validate that the developer's integration test procedures satisfy the criteria in V&V activity 5.4.3, Task 6.		

	5.4.4 Activity: Implementation V&V (Process: Development) (continued)			
		V&V tasks	Required inputs	Required outputs
(11) Sy	ystem	V&V test procedure generation	SRS	System V&V
a)	Sof	tware integrity levels 3 and 4	IRS	test procedures
	1) 2)	Develop V&V test procedures for system testing. Continue tracing required by the System V&V test	SDD	Anomaly report(s)
	3)	plan. Verify that the System V&V test procedures conform to project-defined test document purpose format and	IDD	
		content (e.g., see IEEE Std 829-1998 [B4]).	User documentation	
	4)	Validate that the System V&V test procedures satisfy the criteria in V&V activity 5.4.2 Task 5.	Test cases	
b)	Sof	tware integrity levels 1 and 2	Test procedures	
	1)	Verify that the developer's system test procedures con- form to project-defined test document purpose, format, and content (e.g., see IEEE Std 829-1998 [B4]).		
	2)	Validate that the developer's system test procedures satisfy the criteria in V&V activity 5.4.2, Task 5.		
(12) C	ompo	nent V&V test execution	Source code	Task report(s)—
a)	Sof	tware integrity levels 3 and 4	Executable code	Test results
	1)	Perform V&V component testing.	Encountrie couc	Anomaly
	2)	Analyze test results to validate that software correctly implements the design.	SDD	report(s)
	3)	Validate that the test results trace to test criteria established by the test traceability in the test planning	IDD Component test plans	
		documents.	Component test plans	
	4)	Document the results as required by the Component V&V test plan.	Component test procedures	
	5)	Use the V&V component test results to validate that the software satisfies the V&V test acceptance criteria.	Component test	
	6)	Document discrepancies between actual and expected test results.	iosuits	
b)	Sof	tware integrity level 2		
	Use the	the developer's component test results to validate that software satisfies the test acceptance criteria.		
c)	Sof	tware integrity level 1		
	The	re are no component test requirements.		
(13) H	azard	analysis	Source code	Task report(s)-
a)	Ver	ify that the implementation and associated data elements	SDD	Hazard analysis
	cori no i	new hazards.		Anomaly
b)	Upo	late the hazard analysis.		report(s)
			Hazard analysis report	

	5.4.4 Activity: Implementation V&V (Process: Development) (continued)			
	V&V tasks	Required inputs	Required outputs	
(14) Se a)	ecurity analysis Verify that the implementation is completed in accordance with the system design in that it addresses the identified security risks and that the implementation does not introduce new security risks through coding flaws or compiler error.	Source Code SDD IDD	Task report(s)— Security analysis Anomaly report(s)	
(15) R a)	isk analysis Review and update risk analysis using prior task reports. Provide recommendations to eliminate, reduce, or mitigate the risks.	Source code Supplier development plans and schedules Hazard analysis report Security analysis V&V task results	Task report(s)— Risk analysis Anomaly report(s)	

5.4.5 Activity: Test V&V (Process: Development)			
V&V tasks	Required inputs	Required outputs	
 (1) Traceability analysis Analyze relationships in the V&V test plans, designs, cases, and procedures for correctness and completeness. The task criteria are a) Correctness Verify that there is a valid relationship between the V&V test plans, designs, cases, and procedures. b) Completeness Verify that all V&V test procedures are traceable to the V&V test plans. 	V&V test plans V&V test designs V&V test procedures	Task report(s)— Traceability analysis Anomaly report(s)	

5.4.5 Activity: Test V&V (Process: Development) (continued)			
	V&V tasks	Required inputs	Required outputs
(2) Acc	ceptance V&V test procedure generation	SDD	Acceptance
a)	Software integrity levels 3 and 4	מתו	V&V test
	1) Develop V&V test procedures for acceptance testing.		procedures
	2) Continue the tracing required by the Acceptance V&V test plan.	Source code	Anomaly report(s)
	 Verify that the Acceptance V&V test procedures con- form to project-defined test document purpose, format, and content (e.g., see IEEE Std 829-1998 [B4]). 	User documentation Acceptance test plan	
	4) Validate that the Acceptance V&V test procedures sat- isfy the criteria in V&V activity 5.4.2, Task 6.	Acceptance test procedures	
b)	Software integrity level 2		
	 Verify that the developer's acceptance test procedures conform to project-defined test document purpose, for- mat, and content (e.g., see IEEE Std 829-1998 [B4]). 		
	2) Validate that the developer's acceptance test procedures satisfy the criteria in V&V activity 5.4.2, Task 6.		
c)	Software integrity level 1		
	There are no acceptance test requirements.		
(3) Int	egration V&V test execution	Source code	Task report(s)—
a)	Software integrity levels 3 and 4	Evenutable ande	Test results
	1) Perform V&V integration testing.	Executable code	Anomaly
	 Analyze test results to verify that the software compo- nents are integrated correctly. 	Integration test plan	report(s)
	3) Validate that the test results trace to test criteria established by the test traceability in the test planning documents	Integration test procedures	
	4) Document the results as required by the Integration V&V test plan.	Integration test results	
	5) Use the V&V integration test results to validate that the software satisfies the V&V test acceptance criteria.		
	6) Document discrepancies between actual and expected test results.		
b)	Software integrity levels 1 and 2		
	Use the developer's integration test results to verify that the software satisfies the test acceptance criteria.		

	5.4.5 Activity: Test V&V (Process: Development) (continued)			
		V&V tasks	Required inputs	Required outputs
(4) Sys a) b)	stem V Soft 1) 2) 3) 4) 5) 6) Soft	 V&V test execution tware integrity levels 3 and 4 Perform V&V system testing. Analyze test results to validate that the software satisfies the system requirements. Validate that the test results trace to test criteria established by the test traceability in the test planning documents. Document the results as required by the System V&V test plan. Use the V&V system test results to validate that the software satisfies the V&V test acceptance criteria. Document discrepancies between actual and expected test results. tware integrity levels 1 and 2 	Source code Executable code System test plan System test procedures System test results	Task report(s)— Test results Anomaly report(s)
(5) Acc a) b) c)	war Soff 1) 2) 3) 4) 5) 6) Soff Use soft Soff The	e satisfies the test acceptance criteria. nce V&V test execution tware integrity levels 3 and 4 Perform acceptance V&V testing. Analyze test results to validate that the software satis- fies the system requirements. Validate that the test results trace to test criteria estab- lished by the test traceability in the test planning docu- ments. Document the results as required by the Acceptance V&V test plan. Use the acceptance V&V test results to validate that the software satisfies the V&V test acceptance criteria. Document discrepancies between actual and expected test results. tware integrity level 2 the acquirer's acceptance test results to verify that the ware satisfies the test acceptance criteria. tware integrity level 1 re are no acceptance test requirements.	Source code Executable code User documentation Acceptance test plan Acceptance test procedures Acceptance test results V&V task results	Task report(s)— Test results Anomaly report(s)
(6) Haa a) b)	zard a Ver haza Upo	analysis ify that the test instrumentation does not introduce new ards. late the hazard analysis.	Source code Executable code Test results Hazard analysis report	Task report(s)— Hazard analysis Anomaly report(s)

	5.4.5 Activity: Test V&V (Process: Development) (continued)			
	V&V tasks	Required inputs	Required outputs	
(7) Sec a)	curity analysis Verify that the implemented system does not increase security risk.	Source code Executable code	Task report(s)— Security analysis Anomaly report(s)	
(8) Ris a) b)	sk analysis Review and update risk analysis using prior task reports. Provide recommendations to eliminate, reduce, or mitigate the risks.	Supplier development plans and schedules Hazard analysis report Security analysis V&V task results	Task report(s)— Risk analysis Anomaly report(s)	

	5.4.6 Activity: Installation and checkout V&V (Process: Development)			
	V&V tasks	Required inputs	Required outputs	
(1) Ins a) b)	tallation configuration auditVerify that all software products required to correctly install and operate the software are present in the installation package.Validate that all site-dependent parameters or conditions to verify supplied values are correct.	Installation package (e.g., source code, executable code, user documentation, SDD, IDD, SRS, IRS, concept documentation, installation procedures, site- specific parameters, installation tests, and configuration management data)	Task report(s)— Installation configuration audit Anomaly report(s)	
(2) Ins a) b) c) d)	tallation checkoutConduct analyses or tests to verify that the installed software corresponds to the software subjected to V&V.Verify that the software code and databases initialize, exe- cute, and terminate as specified.In the transition from one version of software to the next, val- idate that the software can be removed from the system with- out affecting the functionality of the remaining system components.Verify the requirements for continuous operation and service during transition, including user notification.	User documentation Installation package	Task report(s)— Installation checkout Anomaly report(s)	
(3) Ha a) b)	zard analysis Verify that the installation procedures and installation environment does not introduce new hazards. Update the hazard analysis.	Installation package Hazard analysis report	Task report(s)— Hazard analysis Anomaly report(s)	

5.4.6 Activity: Installation and checkout V&V (Process: Development) (continued)										
	V&V tasks	Required inputs	Required outputs							
(4) Sec a)	curity analysis Verify that the installed software does not introduce new or increased vulnerabilities or security risks to the overall system.	Installation package User documentation	Task report(s)— Security analysis Anomaly report(s)							
(5) Ris a) b)	sk analysis Review and update risk analysis using prior task reports. Provide recommendations to eliminate, reduce, or mitigate the risks.	Installation package Supplier development plans and schedules Security analysis V&V task results	Task report(s)— Risk analysis Anomaly report(s)							
(6) V& a) b)	 V final report generation Summarize in the V&V final report the V&V activities, tasks, and results, including status and disposition of anomalies. b) Provide an assessment of the overall software quality and provide recommendations. 	V&V activity summary report(s)	Task report(s)— V&V final report							

5.5.1 Activity: Operation V&V (Process: Operation)									
	V&V tasks	Required inputs	Required outputs						
(1) Evalua Evalua charact require	aluation of new constraints the new constraints (e.g., operational requirements, platform teristics, operating environment) on the system or software ements to verify the applicability of the SVVP. (See NOTE.)	SVVP New constraints	Task report(s)— Evaluation of new constraints						
(2) Op Verify docum	that the operating procedures are consistent with the user entation and conform to the system requirements.	Operating procedures User documentation Concept documentation	Task report(s)— Operating procedures evaluation Anomaly report(s)						
(3) Ha a) b)	zard analysisVerify that the operating procedures and operational environment does not introduce new hazards.b) Update the hazard analysis.	Operating procedures Hazard analysis report	Task report(s)— Hazard analysis Anomaly report(s)						
(4) Sec a) b)	curity analysis Verify that no new security risks are introduced due to changes in the operational environment. Over time, changes in external interfaces, threats or technol- ogy in general require that an updated security analysis be performed to determine an updated residual risk.	New constraints Environmental changes Operating procedures	Task report(s)— Security analysis						

5.5.1 Activity: Operation V&V (Process: Operation) (continued)									
	V&V tasks	Required inputs	Required outputs						
(5) Ris	sk analysis	Installation package	Task report(s)—						
a) b)	Review and update risk analysis using prior task reports. Provide recommendations to eliminate reduce or mitigate the	Proposed changes	KISK Allalysis						
3)	risks.	Hazard analysis report	Anomaly report(s)						
		Security analysis							
		Supplier development plans and schedules							
		Operation problem reports							
		V&V task results							

5.6.1 Activity: Maintenance V&V (Process: Maintenance)									
	V&V tasks	Required inputs	Required outputs						
(1) SV	VP revision	SVVP	Updated SVVP						
a) b)	Revise the SVVP to conform to approved changes. When the development documentation required by this stan-	Approved changes							
	dard is not available, generate a new SVVP and consider the methods in Annex D for deriving the required development	Installation package							
	documentation.	Supplier development plans and schedules							
(2) An	omaly evaluation	Anomaly report(s)	Task report(s)— Anomaly						
Evalua	the effect of software operation anomalies.		evaluation						
(3) Cr	iticality analysis	Proposed changes	Task report(s)—						
a)	Determine the software integrity levels for proposed modifications.	Installation package	analysis						
b)	Validate the integrity levels provided by the maintainer. For V&V planning purposes, the highest software integrity level assigned to the software shall be the software system integrity level.	Maintainer integrity levels	Anomaly report(s)						
(4) Mi	gration assessment	Installation package	Task report(s)—						
a)	Assess whether the software requirements and implementation address the following:	Approved changes	Migration assessment						
	1) Specific migration requirements		Anomaly						
	2) Migration tools		report(s)						
	3) Conversion of software products and data								
	4) Software archiving								
	5) Support for the prior environment								
	6) User notification								

5.6.1 Activity: Maintenance V&V (Process: Maintenance) (continued)									
V&V tasks	Required inputs	Required outputs							
 (5) Retirement assessment a) Assess whether the installation package addresses the following: 1) Software support 2) Impact on existing systems and databases 3) Software archiving 4) Transition to a new software product 5) User notification 	Installation package Approved changes	Task report(s)— Retirement assessment Anomaly report(s)							
 (6) Hazard analysis a) Verify that software modifications correctly implement the critical requirements and introduce no new hazards. b) Update the hazard analysis. (7) Security analysis 	Proposed changes Installation Package Hazard analysis report Proposed changes	Task report(s)— Hazard analysis Anomaly report(s) Task report(s)—							
Verify that proposed changes/updates to the software do not introduce new or increased security risks to the overall system.	Installation package	Security analysis							
 (8) Risk analysis a) Review and update risk analysis using prior task reports. b) Provide recommendations to eliminate, reduce, or mitigate the risks. 	Installation package Proposed changes Hazard analysis report Security analysis Supplier development plans and schedules Operation problem reports V&V task results	Task report(s)— Risk analysis Anomaly report(s)							
 (9) Task iteration a) Perform V&V tasks, as needed, to ensure that 1) Planned changes are implemented correctly 2) Documentation is complete and current 3) Changes do not cause unacceptable or unintended system behaviors. 	Approved changes Installation package	Task report(s)— Anomaly report(s)							

^a Other inputs may be used. For any V&V activity and task, all of the required inputs and outputs from preceding activities and tasks may be used, but for conciseness, only the primary inputs are listed.

vel
/ le
grity
inte
oftware
ŝ
each
t
assigned
tasks
V&V
2Minimum
Table

				1											
rocess: Aainte- nance	ce 2.6)	ctivity: Mainte- nance V&V ee 5.6.1)	sla	7							X				
	nan see 5		Leve	e							×				
	3	A S		4							×				
	_			-											
ess:	5.5)	ity: ution V .5.1)	els	7											
roc	see	ctiv pera V&	Lev	e											
	\sim	v P S)		4											
		, n /		-											
		vity: latio kout &V 5.4.6	/els	7											
		Acti stall stall chec V d see 2	Le	3											
		II		4											
		6		-											
		ivity est &V 5.4.5	vels	7	×			Х		X					
		Acti T V, (see	Le	e	×			X		×					
1				4	\times			X		×					
		4) en-		-	<u> </u>										
		tivity leme tion & V 5.4.	svels	7	×	×						x		×	
s:	(Act Impl ta V (see	Ľ	m m	×	×						×			
oces	e 5.4			4	$\hat{}$	~						~			
Pr	(se	:3) : 13	~		×		×						x		
-	-	tivit esig &V & 5.4	evel	~	×		×						x		
		D D Sec (sec		4	×		×						Component V&V test design Component V&V X		
				-											
		ty: 78.V 4.2)	s	7	×				×						
		ctivi equi nts V se 5.4	eve	e	×										
		ctivity: A oncept Ro V&V ee 5.4.1) (se	Levels	4	×				×						
				-											
				7											
				e											
		A (s		4											
				-											
ess:	5.3)	vity: ning rV (.3.1)	vels	7											
Proc	(see	Acti Plan V &	Lev	e											
				4											
5				-											
cess	5.2	ivity lisiti por & V & Z	vels	7											
Pro	eet a	Acti cqu vcqu Vc	Fe	e											
	4	4		4											
3433	2262	S	-	levels		case	design		plan			case	design		
Life cycle proces		V&V activitie		Software integrity	Acceptance support	Acceptance V&V test generation	Acceptance V&V test generation	Acceptance V&V test execution	Acceptance V&V test generation	Acceptance V&V test procedure generation	Anomaly evaluation	Component V&V test generation	Component V&V test generation	Component V&V test execution	
			<u>s</u>	2 1						X			×		
---	------------------------------	---	----------	--	----------------------------------	---------------------------------------	--------------------------------	----------------------------------	---------------------	------------------	--	--------------	--	-------------------	------------------------------
	oces aint anc se 5.	aint anc 2&V 2&V 6 5.6	evel	~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~						×		×	×		
	T M n S	Sec MAC		4						×		×	×		
				-						, ,		,,	×		
	ss: ion 5)	ty: ion 5.1)	s	6									×		
	oces erat ee 5.	tivii erat V&V e 5.5	evel	6								×	×		
	Pr Op	Op Op (see		4								×	×		
				-									×		
		ty: 	s	6									×		
`		ctivi alla ecko v & v e 5.4	eve	e								×	×	x	×
		Inst ch (se		4								×	×	x	×
				-									×		
		t t 4.5)	s	7									×		
		ctivi Tes V & S	Leve	m								×	×		
		A (st		4								×	×		
				-						×			×		
		ity: nen (4.4)	els	7		×				×			×		
	nt	tatic V& v&	Lev	e		×				×		×	×		
	ess: pmei 5.4)	In (s)		4		×				×		×	×		
	roc veloj see :			-						×			×		
	H Dev (ity: Ign (V 3)	els	7	×					×			×		
		Activ Desi V & See 5	Lev	e	×					×		×	×		
		×		4	×					×		×	×		
				1						×			×		
		vity: uire- V&- 5.4.2	vels	7						X			Х		
		Acti Requ ents see 2	Lei	3				X		×		X	Х		
				4				×		×		×	x		
				-						×			x		
		ivity Icep & V 5.4.]	vels	7			×			×			×		
		Acti Cor Va See	Le	e			×			×		×	×		
				4			×			×	×	×	×		
	;; .	.: <u>1</u>		-					-				×		
	ocess pply e 5.3	ivity nnin & V 5.3.	svels	7									×		
	Pro Su (se	Act Pla V (see	Ľ	~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~					~				×		
				4									×		
	s: ion 2)	in the first state of the second state of the	~										×		
	oces uisit se 5.	tivit uisit ppo 7&V/ &V	evel	~									×		
	Pr Acq (se	Acq Su Su (see		4									×		
	Life cycle processes	V&V activities		soltware integrity levels	nponent V&V test plan eration	nponent V&V test sedure generation	ncept documentation luation	ifiguration management ssment	itract verification	icality analysis	dware/software/user irrements allocation lysis	ard analysis	ntify improvement ortunities in the conduct of V	allation checkout	allation configuration audit
				1	Con gené	Con proc	Con eval	Con asse	Con	Crit	Har requ anal	Haz	Ider opp V&	Inst	Inst

Table 2—Minimum V&V tasks assigned to each software integrity level (continued)

Table 2—Minimum V&V tasks assigned to each software integrity level *(continued)*

Life cycle processes	Process Acquisiti (see 5.2	;; u	Prc (se	ocess: upply e 5.3)										De D	Proce velop (see 5	ess: 5.4)	f									H 0.0	Proce	ess: dtion 5.5)		Pro Ma na (see	cess: inte- unce e 5.6)	
V&V activities	Activity Acquisiti suppor V&V (see 5.2.]	1) t	Act Pla V (see	tivity mning &V 5.3.1	w 🗢	శర్జ	ctivit oncel V&V e 5.4.	F) Jak	° I I	Activ Requents see 5.	ity: ire- V&V 4.2)		Acti De V.	ivity: sign &V 5.4.3		Im I (Se	ctivi plen tatio V&V se 5.4	ty: n f.4)		Act T V. (see	ivity: est &V 5.4.5		Ac Inst ch (see	tivity allatio eckou 2.5.4.0	e tri :	₹0° S	Activ pera V& tee 5.	ity: V 5.1)		Acti Ma V.	ivity: inte- mce & V 5.6.1	
	Levels		ř	evels			,evel			Leve	sls		Le	vels			Leve	ls		Le	vels			evels			Leve	sls		Le	vels	
Soltware integrity levels	4 3 2	-	4	5	-	4	3	-	4	e	~	4	e e	7	-	4	m	1	4		7	-	4	3	-	4	e	7	4	m m	3	
Integration V&V test case generation																×	×	×	×													
Integration V&V test design generation												\sim	×	×	×																	
Integration V&V test execution																			\sim	×	×	×										
Integration V&V test plan generation												~	x	×	×																	
Integration V&V test procedure generation																×	×	×	×													
Interface analysis									×	×	×		×	×		×	×	×														
Interface with organizational and supporting processes	x		×	×		×	×		X	×		\sim	X			×	×		~	X			×	×		×	×		~	×		
Management and technical review support	x		×	×		×	×		X	×		\sim	×			×	×		~	X			×	×		×	×		~	×		
Management review of the V&V effort	x x x	x	×	x	×	×	x	x	X	X	X	×	×	X	×	×	×	×	×	X	×	×	×	x	X	Х	x	x	x	x	X	X
Migration assessment																													\sim	X		
New constraints evaluation																										×	×	×				
Operating procedures evaluation																										×	×					

Copyright © 2005 IEEE. All rights reserved.

(continued)
level
software integrity
o each
assigned t
tasks
V&V
2—Minimum
Table 2

Life cycle processes	Process Acquisitio (see 5.2)	;; u (Prod Sup (see	cess: 5.3)									Pr (s	ocess Jopn See 5.4	s: t)								-00	Proces perat see 5.	ss: 5)		Proce Main nano see 5	sss: te- te .(6)
V&V activities	Activity Acquisiti support V&V (see 5.2.1	1) t u	Acti Plan V &	wity: ming &V 5.3.1)		Activ Conc V& (see 5	vity: cept .4.1)	= -	Activ Requirents (see 5.	ity: lire- V&V .4.2)	-	Activ Desi V& See 5	vity: ign ¿V		Acti Imple tat V d (see 2	vity: emen ion &V 5.4.4)		Aci J V (see	ivity: Cest &V 5.4.5)		Acti Install chec V & (see 5	vity: ation/ kout ¿V :4.6)	~ 0 s	Activi perat V&V tee 5.5	ty: ion (1)		Activ Main nan V &	ity: te- te- 6.1)
	Levels		Lev	vels		Lev	els		Lev	els		Lev	els		Lev	vels		Ľ	stels		Lev	'els		Leve	s		Leve	sl
Soltware integrity levels	4 3 2	-	4 3	7	4	e	7	1 4	e	7	1 4	e	7	4	e	7	-	4	7	-	4 3	2	4	m	1	4	e	2
Planning the interface between the V&V effort and supplier	x x x	×	x	×	×																							
Proposed/baseline change assessment					×	x	×	×	×	×	×	X	x	~	X	×		×	x		x	x	x	x	×	Х	x	x
Retirement assessment																										Х	×	
Risk analysis					×	x		x	x		x	X		×	X			X		. 1	XX		Х	х		Х	Х	
Scoping the V&V effort	x x x	x																										
Security analysis					~	X		×	×		×	×		×	X			X			XX		×	×		Х	×	
Software design evaluation											x	X	X	x														
Software requirements evaluation								×	×	X	×																	
SVVP generation	x x x	X	XX	x	x	X	×	×																		Х	×	X
SVVP revision																										Х	×	X
Source code and source code documentation														~	x	×												
System requirements review	x x x	x																										
System V&V test case generation														×	×	×	×											

Table 2—Minimum V&V tasks assigned to each software integrity level *(continued)*

Life cycle processes	Proce Acquisi (see 5.	sss: ition .2)		Pr St (se	oces uppl	33) <u>v</u>											I Dev	roce /elop see 5	ess: men (.4)	±										d O S	roce pera	sss: tion 5.5)		¶∑ - ©	roce laint nanc ee 5.	e - 9	
V&V activities	Activi Acquisi suppo V&Y (see 5.2	ity: ition ort 2.1)		Ac Pla V (see	etivit anni 7&V 8 5.3	iy: .1)		Act Co V (see	tivity ncep & V 5.4.	÷t î	E .	Acti Req nents (see :	ivity uire s V& 5.4.2	: 120		Activ Des V& See 5	vity: ign ¿V		Im A	ctivil plem tation V&V xe 5.4	ty: 		Act V (see	cest S.4.5	6		Activ stall: check V & see 5	ity: ation £V .4.6)	2	S O ^A	ctiv pera V& ee 5.	ity: tion V 5.1)		Se T MA	ctivi laint nanc V&V	• • • · · ·	
	Leve	sl			evel	s		Ľ	evels			Le'	vels			Lev	els			Level	s		Ĕ	evels			Lev	els			Leve	sis			eve	<u>s</u>	
Software integrity levels	4 3	6	-	4	~		4	~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~	8	-	4	e	7	-	4	з	7	-	4	~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~	2	4	m	7	-	4	e	7	-	4	e	6	-	4	e	2	
System V&V test design generation															x	x	×	×																			
System V&V test execution																						Ś	x	X	X												
System V&V test plan generation											X	x	X	x																							
System V&V test procedure generation																			x	X	X	×															
Task iteration																																		x	x	x	
Traceability analysis							\sim	×	x		X	X	×		x	x	×		×	X	×	~	×	X													
V&V final report generation																										X	X	×	×								

IEEE Std 1012-2004

V&V life cycle activities	Activity: Management of V&V (see 5.1.1)	Activity: Acquisition support V&V (see 5.2.1)	Activity: Planning V&V (see 5.3.1)	Activity: Concept V&V (see 5.4.1)	Activity: Requirements V&V (see 5.4.2)	Activity: Design V&V (see 5.4.3)	Activity: Implementation V&V (see 5.4.4)	Activity: Test V&V (see 5.4.5)	Activity: Installation/checkout V&V (see 5.4.6)	Activity: Operation V&V (see 5.5.1)	Activity: Maintenance V&V (see 5.6.1)
Algorithm analysis					x	x	x				X
Audit performance					x	x	x	х	x		x
Audit support	X				x	x	x	х	x		X
Control flow analysis					x	x	x				x
Cost analysis	X	Х	X	x	x	x	X	х	x		x
Database analysis					X	X	X	х			X
Data flow analysis					X	x	х				X
Disaster recovery plan assessment	X			x	x	x	x			x	X
Distributed architecture assessment				X	X	X					X
Feasibility study evaluation	X	Х	Х	х	X	X					X
Independent risk assessment	X	Х	Х	x	x	x	x	х	x	x	x
Inspection											
Concept				х							X
Requirements					X						X
Design						x					X
Source code							X				X
Test plan					x	x	x		x		X
Test design						x	x		x		X
Test case						X	X	Х	X		X
Operational evaluation										X	
Performance monitoring				x	x	x	x	х	x	x	X
Post installation validation									X	X	X
Project management oversight support	X	Х	Х	x	X	x	x	Х	x	x	x
Proposal evaluation support		Х									
Qualification testing								х	x		X
Regression analysis and testing					x	x	x	X	x		x

Table 3—Optional V&V tasks and suggested applications in the life cycle

Table 3—Optional V&V tasks and suggested applications in the life cycle $($	(continued)
---	-------------

V&V life cycle activities	Activity: Management of V&V (see 5.1.1)	Activity: Acquisition support V&V (see 5.2.1)	Activity: Planning V&V (see 5.3.1)	Activity: Concept V&V (see 5.4.1)	Activity: Requirements V&V (see 5.4.2)	Activity: Design V&V (see 5.4.3)	Activity: Implementation V&V (see 5.4.4)	Activity: Test V&V (see 5.4.5)	Activity: Installation/checkout V&V (see 5.4.6)	Activity: Operation V&V (see 5.5.1)	Activity: Maintenance V&V (see 5.6.1)
Reusability analysis	x	X	х	x	x	x	x				X
Reuse analysis	x	х	Х	x	x	x					Х
Simulation analysis				x	x	x	x	x	X	x	X
Sizing and timing analysis					x	x	x	x			X
System software assessment						X	X	X	X	X	X
Test certification								x	X	x	X
Test evaluation					x	x	x	x	X	x	X
Test witnessing								х	X	х	X
Training document evaluation					x	x	x	x	X	x	X
Usability analysis				x	x	x	x	x	X	x	X
User documentation evaluation	X			X	X	x	X	x	X	x	X
User training	x							x	X	x	X
V&V tool plan generation	X	X	х								X
Walk-throughs											
Design						x					X
Requirements					X						X
Source code							X				X
Test								x	X		X

Annex G contains a description of the optional V&V tasks.



Figure 1—An example of V&V processes, activities, and tasks



Figure 2—An example of V&V test product and test execution task scheduling

Annex A

(informative)

Mapping of IEEE Std 1012 V&V activities and tasks

A.1 Mapping of ISO/IEC 12207 V&V requirements to IEEE Std 1012 V&V activities and tasks

Table A.1 shows a mapping of all ISO/IEC 12207:1995 [B13] V&V requirements (i.e., processes, activities and tasks) to the V&V activities and tasks of this standard.

The first column of Table A.1 lists the ISO/IEC 12207:1995 [B13] clause numbers and titles of V&V processes and activities. The second column of Table A.1 lists the IEEE Std 1012-2004 clauses and tables that address the topics listed in the first column.

ISO/IEC 12207 V&V requirements	IEEE Std 1012 V&V activities and tasks (see corresponding clause/table)
5.1.4.1 Supplier Monitoring V&V	 5.2.1 Activity: Acquisition support V&V Task 1 Scoping the V&V effort Task 2 Planning the interface between the V&V effort and supplier Task 3 System requirements review
5.2.4.5(h) and 5.2.5.5 Interfacing with V&V ^a	 5.2.1 Activity: Acquisition support V&V Task 2 Planning the interface between the V&V effort and supplier 5.3.1 Activity: Planning V&V Task 1 Planning the interface between the V&V effort and supplier Annex C Definition of IV&V
5.2.6.3 Verification and Validation ^a	All clauses, tables, software V&V figures, and annexes
5.3.2 System Requirements Analysis	 5.2.1 Activity: Acquisition support V&V Task 3 System requirements review 5.4.1 Activity: Concept V&V Task 1 Concept documentation evaluation Task 4 Traceability analysis
5.5.5 and 5.5.6 Migration and Soft- ware Retirement	 5.1.1 Activity: Management of V&V Task 2 Proposed/baseline change assessment 5.6.1 Activity: Maintenance V&V

Table A.1—Mapping ISO/IEC 12207 V&V requirements to IEEE Std 1012 V&V activities and tasks

ISO/IEC 12207 V&V requirements	IEEE Std 1012 V&V activities and tasks (see corresponding clause/table)
6.4.1 Verification Process Implemen-	Clause 4 Software integrity levels
tation	Clause 6 Software V&V reporting, administrative, and documentation requirements
	6.2 V&V Administrative requirements
	Clause 7 SVVP outline
	7.7 SVVP section 7: V&V administrative requirements
6.4.1.1 Criticality of Software to be	Clause 4 Software integrity levels
vermeu	Table B.1 Assignment of software integrity levels
	Table B.2 Definition of consequences
	Annex D V&V of reuse software
6.4.1.2 Process for Verification ^a	Clause 6 Software V&V reporting, administrative, and documentation requirements
	Clause 7 SVVP outline
6.4.1.3 and 6.4.1.4 Extent and Rigor	Clause 4 Software integrity levels
of vernication	Table 2 Minimum V&V tasks assigned to each software integrity level
	Annex C Definition of independent V&V (IV&V)
6.4.1.5 Verification Plan ^a	Clause 6 Software V&V reporting, administrative, and documentation requirements
	Clause 7 SVVP outline
6.4.1.6 Problem and Non-	6.2 V&V Administrative requirements
contornance Reports	7.7 SVVP section 7: V&V Administrative requirements
6.4.2 Verification	Clause 5 Software V&V processes
6.4.2.1 Contract Verification	5.3.1 Activity: Planning V&V Task 2 Contract Verification
6.4.2.2 Process Verification	5.2 Process: Acquisition
	5.3 Process: Supply
	5.4 Process: Development

Table A.1—Mapping ISO/IEC 12207 V&V requirements to IEEE Std 1012 V&V activities and tasks *(continued)*

ISO/IEC 12207 V&V requirements	IEEE Std 1012 V&V activities and tasks (see corresponding clause/table)
6.4.2.3 Requirements Verification	5.2.1 Activity: Acquisition support V&V Task 3 System requirements review
	5.4.1 Activity: Concept V&V Task 1 Concept documentation evaluation
	5.4.2 Activity: Requirement V&V Task 1 Traceability analysis Task 2 Software requirements evaluation Task 3 Interface analysis Task 4 Criticality analysis Task 5 System V&V test plan generation Task 6 Acceptance V&V test plan generation Task 8 Hazard analysis
	Task 9 Security analysis
6.4.2.4 Design Verification	5.4.3 Activity: Design V&V Task 1 Traceability analysis Task 2 Software design evaluation Task 3 Interface analysis Task 4 Criticality analysis Task 5 Component V&V test plan generation Task 6 Integration V&V test plan generation Task 7 Component V&V test design generation Task 8 Integration V&V test design generation Task 9 System V&V test design generation Task 10 Acceptance V&V test design generation Task 11 Hazard analysis Task 12 Security analysis
6.4.2.5 Code Verification	5.4.4 Activity: Implementation V&V Task 1 Traceability analysis Task 2 Source code and source code documentation evaluation Task 3 Interface analysis Task 4 Criticality analysis Task 5 Component V&V test case generation Task 6 Integration V&V test case generation Task 7 System V&V test case generation Task 8 Acceptance V&V test case generation Task 9 Component V&V test procedure generation Task 10 Integration V&V test procedure generation Task 11 System V&V test procedure generation Task 12 Component V&V test execution Task 13 Hazard analysis Task 14 Security analysis
6.4.2.6 Integration Verification	5.4.5 Activity: Test V&V Task 3 Integration V&V test execution

Table A.1—Mapping ISO/IEC 12207 V&V requirements to IEEE Std 1012 V&V activities and tasks *(continued)*

ISO/IEC 12207 V&V requirements	IEEE Std 1012 V&V activities and tasks (see corresponding clause/table)
6.4.2.7 Documentation Verification	5.2.1 Activity: Acquisition support V&V Task 3 Systems requirements review
	5.3.1 Activity: Planning V&V Task 2 Contract verification
	5.4.1 Activity: Concept V&V Task 1 Concept documentation evaluation
	5.4.2 Activity: Requirements V&V Task 2 Software requirements evaluation Task 3 Interface analysis
	5.4.3 Activity: Design V&V Task 2 Software design evaluation Task 3 Interface analysis
	5.4.4 Activity: Implementation V&V Task 2 Source code and source code documentation evaluation Task 3 Interface analysis
	5.4.6 Activity: Installation and Checkout Task 1 Installation configuration audit
	5.5.1 Activity: Operation V&V Task 2 Operating procedures evaluation
6.5.1 Validation Process	Clause 4 Software integrity levels
Implementation	Clause 6 Software V&V reporting, administrative, and documentation requirements
	6.2 V&V Administrative requirements
	Clause 7 SVVP outline
	7.7 SVVP section 7: V&V administrative requirements
	Annex C Definition of independent V&V (IV&V)
	Annex D V&V of reuse software
	Annex E V&V measures
6.5.1.1 Criticality of Software to be	Clause 4 Software integrity levels
Vandaled	Table B.1 Assignment of software integrity levels
	Table B.2 Definition of consequences
	Annex D V&V of reuse software
6.5.1.2 Process for Validation	Clause 6 Software V&V reporting, administrative, and documentation requirements
	Clause 7 SVVP Outline

Table A.1—Mapping ISO/IEC 12207 V&V requirements to IEEE Std 1012 V&V activities and tasks *(continued)*

ISO/IEC 12207 V&V requirements	IEEE Std 1012 V&V activities and tasks (see corresponding clause/table)
6.5.1.3 Extent and Rigor of Validation ^a	Table 2 Minimum V&V tasks assigned to each software integrity level Annex C Definition of independent V&V (IV&V)
6.5.1.4 Validation Plan ^a	Clause 6 Software V&V reporting, administrative, and documentation requirements
	Clause 7 SVVP outline
6.5.1.5 Problem and Non- conformance Reports ^a	6.2 V&V Administrative requirements
6.5.2 Validation	Clause 5 Software V&V processes
6.5.2.1 Validate Test Preparation ^a	5.4.2 Activity: Requirements V&V Task 5 System V&V Test plan generation Task 6 Acceptance V&V test plan generation
	5.4.3 Activity: Design V&V Task 5 Component V&V test plan generation Task 6 Integration V&V test plan generation Task 7 Component V&V test design generation Task 8 Integration V&V test design generation Task 9 System V&V test design generation Task10 Acceptance V&V test design generation
	 5.4.4 Activity: Implementation V&V Task 5 Component V&V test case generation Task 6 Integration V&V test case generation Task 7 System V&V test case generation Task 8 Acceptance V&V test case generation Task 9 Component V&V test procedure generation Task 10 Integration V&V test procedure generation 5.4.5 Activity: Test V&V Task 2 Acceptance V&V test procedure generation
6.5.2.2 Validate Test Traceability ^a	 5.4.4 Activity: Implementation V&V Task 12 Component V&V test execution 5.4.5 Activity: Test V&V Task 3 Integration V&V test execution Task 4 System V&V test execution Task 5 Acceptance V&V test execution
6.5.2.3 Validate Test Conduct ^a	 5.4.4 Activity: Implementation V&V Task 12 Component V&V test execution 5.4.5 Activity: Test V&V
	Task 3 Integration V&V test executionTask 4 System V&V test executionTask 5 Acceptance V&V test execution

Table A.1—Mapping ISO/IEC 12207 V&V requirements to IEEE Std 1012 V&V activities and tasks *(continued)*

ISO/IEC 12207 V&V requirements	IEEE Std 1012 V&V activities and tasks (see corresponding clause/table)
6.5.2.4 Validate Software for Intended Use ^a	5.4.1 Activity: Concept V&V Task 1 Concept documentation evaluation
	5.4.2 Activity: Requirements V&V Task 2 Software requirements evaluation Task 3 interface analysis
	5.4.3 Activity: Design V& V Task 2 Software design evaluation Task 3 Interface analysis
	5.4.4 Activity: Implementation V&V Task 2 Source code and source code documentation evaluation Task 3 Interface analysis
	5.4.5 Activity: Test V&V Task 4 System V&V test execution Task 5 Acceptance V&V test execution
6.5.2.5 Installation Test of Software ^a	5.4.6 Activity: Installation and checkout V&V Task 1 Installation configuration audit Task 2 Installation checkout Task 3 Hazard analysis Task 4 Security analysis Task 5 Risk analysis
Annex A Tailoring Process	N/A
Annex B Guidance on Tailoring	N/A
Annex C Guidance on Processes and Organizations	N/A
Annex D Bibliography	N/A
Annex E Basic Concepts of ISO/IEC 12207	N/A
Annex F Purpose and Outcomes	Clause 4 Software integrity level
	Clause 5 Software V&V processes
	Clause 6 Software V&V reporting, administrative, and documentation requirements
	Clause 7 SVVP outline
Annex G	N/A
Annex H	N/A

Table A.1—Mapping ISO/IEC 12207 V&V requirements to IEEE Std 1012 V&V activities and tasks *(continued)*

^aNo ISO/IEC 12207:1995 [B13] clause title was listed. For purposes of this mapping, this standard assigned a clause title to reflect the clause contents.

A.2 Mapping of IEEE Std 1012 V&V activities to ISO/IEC 12207 software life cycle processes and activities

This standard defines 11 V&V activities, as shown in the first column of Table A.2, that are part of the V&V process. These 11 V&V activities correspond to the ISO/IEC 12207:1995 [B13] software life cycle processes and activities shown in columns 2 and 3 of Table A.2.

IEEE Std 1012 V&V activities (see corresponding subclause)	ISO/IEC 12207 software life cycle		
	Process ^a	Activity	
5.2.1 Activity: Acquisition support V&V	Acquisition	 —Initiation —RFP (tender) preparation —Contract preparation and update —Supplier monitoring —Acceptance and completion 	
5.3.1 Activity: Planning V&V	Supply	 —Initiation —Preparation of response —Contract —Planning —Execution and control —Review and evaluation —Delivery and completion 	
5.4.1 Activity: Concept V&V	Development	 Process implementation Requirements elicitation System requirements analysis System architectural design 	
5.4.2 Activity: Requirements V&V	Development	—Software requirements analysis	
5.4.3 Activity: Design V&V	Development	-Software architectural design -Software detailed design	
5.4.4 Activity: Implementation V&V	Development	—Software coding and testing	
5.4.5 Activity: Test V&V	Development	 —Software integration —Software qualification testing —System integration —System qualification testing 	
5.4.6 Activity: Installation and checkout V&V	Development	-Software installation -Software acceptance support	
5.5.1 Activity: Operation V&V	Operation	 Process implementation Operational testing System operation User support 	
5.6.1 Activity: Maintenance V&V	Maintenance	 Process implementation Problem and modification analysis Modification implementation Maintenance review/acceptance Migration Software retirement 	
5.1.1 Activity: Management of V&V	All processes	All activities	

Table A.2—Mapping of IEEE Std 1012 V&V activities to ISO/IEC 12207

^aAnnex F contains description, purposes, and outcomes of the ISO/IEC process model.

A.3 Mapping of IEEE Std 1074 V&V requirements to IEEE Std 1012 V&V activities and tasks

Table A.3 shows a mapping of all IEEE Std 1074-1997 [B10] V&V requirements (i.e., processes, activities and tasks) to the V&V activities and tasks of this standard.

IEEE Std 1074 V&V requirements	IEEE Std 1012 V&V activities and tasks (see corresponding clause)
A.1 Project management activity groups A.1.1 Project initiation activities A.1.1.1 Create SLCP A.1.1.2 Perform estimations A.1.1.3 Allocate project resources A.1.1.4 Define metrics	 5.2.1 Activity: Acquisition support V&V Task 1 Scoping the V&V effort Task 2 Planning the Interface between the V&V effort and supplier 5.3.1Activity: Planning V&V Task 1 Planning the interface between the V&V effort and supplier 5.1.1 Activity: Management of V&V Task 1 SVVP Generation 5.6.1 Activity: Maintenance V&V Task 1 SVVP Revision 6.1 V&V reporting requirements 7.6 SVVP section 6: V&V reporting requirements 6.2 Administrative V&V requirements 7.7 SVVP section 7: V&V administrative requirements 6.3.1 V&V Test documentation 7.8 SVVP section 8: V&V test documentation requirements 6.3.2 SVVP documentation Clause 7 SVVP outline
	Annex E V&V measures
A.1.2 Project planning activities A.1.2.1 Plan evaluations A.1.2.2 Plan configuration management A.1.2.3 Plan system transition (if applicable)	Clause 5 Software V&V processes All tasks Clause 6 Software V&V reporting, administrative, and
A.1.2.4 Plan installation A.1.2.5 Plan documentation A.1.2.6 Plan training A.1.2.7 Plan project management A.1.2.8 Plan integration	documentation requirements Clause 7 SVVP outline

Table A.3—Mapping of IEEE Std 1074 V&V requirements to IEEE Std 1012 V&V activities and tasks

Table A.3—Mapping of IEEE Std 1074 V&V requirements to IEEE Std 1012 V&V activities and tasks *(continued)*

IEEE Std 1074 V&V requirements	IEEE Std 1012 V&V activities and tasks (see corresponding clause)
 A.1.3 Project monitoring and control activities A.1.3.1 manage risks A.1.3.2 Manage the project A.1.3.3 Identify SLCP improvement needs A.1.3.4 Retain records A.1.3.5 Collect and analyze metric data 	5.1.1 Activity: Management of V&V Task 1 SVVP generation Task 2 Proposed/baseline change assessment Task 3 Management review of the V&V effort Task 4 Management and technical review support Task 5 Interface with organizational and supporting processes
 A.2 Pre-development activity groups A.2.1 Concept exploration activities A.2.1.1 Identify ideas or needs A.2.1.2 Formulate potential approaches A.2.1.3 Conduct feasibility studies A.2.1.4 Refine and finalize the idea or need A.2.2 System allocation activities A.2.2.1 Analyze functions A.2.2.2 Develop system architecture A.2.2.3 Decompose system requirements A.2.3 Software importation activities A.2.3.1 Identify imported software requirements A.2.3.2 Evaluate software import sources (if applicable) A.2.3 Define software import method (if 	 5.4.1 Activity: Concept V&V Task 1 Concept documentation evaluation Task 2 Criticality analysis Task 4 Traceability analysis Task 5 Hazard analysis Task 6 Security analysis Task 7 Risk analysis 5.4.1 Activity: Concept V&V Task 1 Concept documentation evaluation Task 3 Hardware/software/user requirements allocation analysis Clause 5 Software V&V Processes All tasks Annex D V&V of reuse software
applicable) A.2.3.4 Import software (if applicable)	
 A.3 Development activity groups A.3.1 Requirements activities A.3.1.1 Define and develop software requirements A.3.1.2 Define interface requirements A.3.1.3 Prioritize and integrate software requirements 	5.4.2 Activity: Requirements V&V Task 1 Traceability analysis Task 2 Software requirements evaluation Task 3 Interface analysis Task 4 Criticality analysis Task 5 System V&V test plan generation Task 6 Acceptance V&V test plan generation Task 7 Configuration management assessment Task 8 Hazard analysis Task 9 Security analysis Task 10 Risk analysis

Table A.3—Mapping of IEEE Std 1074 V&V requirements	to
IEEE Std 1012 V&V activities and tasks (continued)	

IEEE Std 1074 V&V requirements	IEEE Std 1012 V&V activities and tasks (see corresponding clause)
 A.3 Development activity groups (continued) A.3.2 Design activities A.3.2.1 Perform architectural design A.3.2.2 Design database (if applicable) A.3.2.3 Design interfaces A.3.2.4 Perform detailed design 	5.4.3 Activity: Design V&V Task 1 Traceability analysis Task 2 Software design evaluation Task 3 Interface analysis Task 4 Criticality analysis Task 5 Component V&V test plan generation Task 6 Integration V&V test plan generation Task 7 Component V&V test design generation Task 8 Integration V&V test design generation Task 9 System V&V test design generation Task 10 Acceptance V&V test design generation Task 11 Hazard analysis Task 12 Security analysis Task 13 Risk analysis
A.3.3 Implementation activities A.3.3.1 Create executable code A.3.3.2 Create operating documentation A.3.3.3 Perform integration	 5.4.4 Activity: Implementation V&V Task 1 Traceability analysis Task 2 Source code and source code documentation evaluation Task 3 Interface analysis Task 4 Criticality analysis Task 5 Component V&V test case generation Task 5 Component V&V test case generation Task 6 Integration V&V test case generation Task 7 System V&V test case generation Task 8 Acceptance V&V test case generation Task 9 Component V&V test procedure generation Task 10 Integration V&V test procedure generation Task 11 System V&V test procedure generation Task 12 Component V&V test execution Task 13 Hazard analysis Task 15 Risk analysis 5.4.5 Activity: Test V&V Task 1 Traceability analysis Task 2 Acceptance V&V test execution Task 3 Integration V&V test execution Task 4 System V&V test procedure generation Task 5 Acceptance V&V test execution Task 5 Acceptance V&V test procedure generation Task 6 Hazard analysis

Table A.3—Mapping of IEEE Std 1074 V&V requirements to IEEE Std 1012 V&V activities and tasks *(continued)*

IEEE Std 1074 V&V requirements	IEEE Std 1012 V&V activities and tasks (see corresponding clause)
 A.4 Post-development activity groups A.4.1 Installation activities A.4.1.1 Distribute software A.4.1.2 Install software A.4.1.3 Accept software in operational environment 	5.4.6 Activity: Installation and checkout V&V Task 1 Installation configuration audit Task 2 Installation checkout Task 3 Hazard analysis Task 4 Security analysis Task 5 Risk analysis Task 6 V&V final report generation
 A.4.2 Operation and support activities A.4.2.1 Operate the system A.4.2.2 Provide technical assistance and consulting A.4.2.3 Maintain support request log 	5.5.1 Activity: Operation V&V Task 1 Evaluation of new constraints Task 2 Operating procedures evaluation Task 3 Hazard analysis Task 4 Security analysis Task 5 Risk analysis
A.4.3 Maintenance activities A.4.3.1 Identify software improvement needs A.4.3.2 Implement problem reporting method A.4.3.3 Reapply SLC	5.6.1 Activity: Maintenance V&V Task 1 SVVP revision Task 2 Anomaly evaluation Task 3 Criticality analysis Task 4 Migration assessment Task 5 Retirement assessment Task 6 Hazard analysis Task 7 Security analysis Task 8 Risk analysis Task 9 Task iteration
A.4.4 Retirement activities A.4.4.1 Notify user A.4.4.2 Conduct parallel operations (if applicable) A.4.4.3 Retire system	5.6.1Activity: Maintenance V&V Task 1 SVVP revision Task 2 Anomaly evaluation Task 3 Criticality analysis Task 4 Migration assessment Task 5 Retirement assessment Task 6 Hazard analysis Task 7 Security analysis Task 8 Risk analysis Task 9 Task iteration
 A.5 Integral activity groups A.5.1 Evaluation activities A.5.1.1 Conduct reviews A.5.1.2 Create traceability matrix A.5.1.3 Conduct audits A.5.1.4 Develop test procedures A.5.1.5 Create test data A.5.1.6 Execute tests A.5.1.7 Report evaluation results 	Clause 5 Software V&V processes All tasks Clause 6 Software V&V reporting, administrative, and documentation requirements Clause 7 SVVP outline
 A.5 Integral activity groups A.5.1 Evaluation activities A.5.1.1 Conduct reviews A.5.1.2 Create traceability matrix A.5.1.3 Conduct audits A.5.1.4 Develop test procedures A.5.1.5 Create test data A.5.1.6 Execute tests A.5.1.7 Report evaluation results 	Clause 5 Software V&V processes All tasks Clause 6 Software V&V reporting, administrative, and documentation requirements Clause 7 SVVP outline

A.4 Mapping between CMMI and IEEE Std 1012 tasks

The following tables provide a mapping between the Software Engineering Process Groups CMMI process areas and the IEEE Std 1012 software V&V tasks.

Table A.4—IEEE Std 1012 CMMI process	mapping matrix for requirements
--------------------------------------	---------------------------------

IEEE Std 1012 V&V activities and tasks (see corresponding clause)
5.1.1 Activity: Management of the V&V effort Task 3 Management review of the V&V effort
5.1.1 Activity: Management of the V&V effort Task 5 Interface with Organizational and Supporting Processes
N/A
5.1.1 Activity: Management of the V&V effort Task 3 Management review of the V&V effort
5.1.1 Activity: Management of the V&V effort Task 6 Identify improvement opportunities in the conduct of V&V
 5.1.1 Activity: Management of the V&V effort Task 1 SVVP Generation Task 2 Proposed/baseline change assessment 5.2.1 Activity: Acquisition support V&V Task 1 Scoping the V&V Effort Task 2 Planning the interface between V&V effort and supplier Task 3 System requirements review 5.3.1 Activity: Planning V&V Task 1 Planning the interface between V&V effort and supplier 5.4.1 Activity: Concept V&V Task 3 Hardware/software/user requirements allocation analysis 5.4.2 Activity: Requirements V&V Task 5 System V&V test plan generation Task 6 Acceptance V&V test plan generation 5.4.3 Activity: Design V&V Task 5 Component V&V test plan generation Task 6 Integration V&V test plan generation Task 6 Integration V&V test plan generation Task 7 Component V&V test design generation Task 8 Integration V&V test design generation

CMMI process groups and areas	IEEE Std 1012 V&V activities and tasks (see corresponding clause)
Project management Project planning (continued)	5.4.4 Activity: Implementation V&V Task 5 Component V&V test case generation Task 6 Integration V&V test case generation Task 7 System V&V test case generation Task 8 Acceptance V&V test case generation Task 9 Component V&V test procedure generation Task 10 Integration V&V test procedure generation Task 11 System V&V test procedure generation
Project monitoring and control	 5.5.1 Activity: Management of the V&V effort Task 1 SVVP generation Task 2 Proposed/baseline change assessment Task 3 Management review of the V&V effort Task 6 Identify improvement opportunities in the conduct of V&V
Supplier agreement management	 5.2.1 Activity: Acquisition support V&V Task 2 Planning the interface between V&V effort and supplier 5.3.1 Activity: Planning V&V Task 1 Planning the interface between V&V effort and supplier
Integrated project management for IPPD	Annex C Definition of independent V&V Annex F Relationship of V&V to other project responsibilities
Risk management	 5.4.1 Activity: Concept V&V Task 3 Hardware/software/user requirements allocation analysis Task 7 Risk analysis 5.4.2 Activity: Requirements V&V Task 10 Risk analysis 5.4.3 Activity: Design V&V Task 13 Risk analysis 5.4.4 Activity: Implementation V&V Task 15 Risk analysis 5.4.5 Activity: Test V&V Task 8 Risk analysis 5.6.1 Activity: Maintenance V&V Task 8 Risk analysis
Integrated teaming	 5.1.1 Activity: Management of the V&V effort Task 4 Management and technical review support Task 5 interface with organizational and supporting processes Annex C Definition of independent V&V Annex F Relationship of V&V to other project responsibilities
Integrated supplier management	 5.2.1 Activity: Acquisition support V&V Task 2 Planning the interface between V&V effort and supplier 5.3.1 Activity: Planning V&V Task 1 Planning the interface between V&V effort and supplier

CMMI process groups and areas	IEEE Std 1012 V&V activities and tasks (see corresponding clause)
Quantitative project management	5.1.1 Activity: Management of the V&V effort Task 6 Identify improvement opportunities in the conduct of V&V
	Annex E V&V measures
Engineering	
Requirements development	5.1.1 Activity: Management of the V&V effort Task 2 Proposed/baseline change assessment
	5.4.2 Activity: Requirements V&V Task 2 Software Requirements Evaluation
Requirements management	5.1.1 Activity: Management of the V&V effort Task 4 Management and technical review support Task 5 Interface with organizational and supporting processes
	5.4.1 Activity: Concept V&V Task 3 Hardware/software/user requirements allocation analysis Task 4 Traceability analysis
	5.4.2 Activity: Requirements V&V Task 1 Traceability Analysis
Technical solution	5.4.1 Activity: Concept V&V Task 1 Concept documentation evaluation Task 3 Hardware/software/user requirements allocation analysis Task 5 Hazard analysis Task 6 Security analysis
	5.4.2 Activity: Requirements V&V Task 2 Software requirements evaluation Task 8 Hazard analysis Task 9 Security analysis
	5.4.3 Activity: Design V&V Task 2 Software design evaluation Task 3 Interface analysis Task 11 Hazard analysis Task 12 Security analysis
	5.4.4 Activity: Implementation V&V Task 2 Source code and source code documentation evaluation Task 3 Interface analysis Task 13 Hazard analysis Task 14 Security analysis

CMMI process groups and areas	IEEE Std 1012 V&V activities and tasks (see corresponding clause)
Product integration	5.4.2 Activity: Requirements V&V Task 1 Traceability analysis Task 3 Interface analysis Task 5 System V&V test plan generation Task 6 Accentance V&V test plan generation
	 5.4.3 Activity: Design V&V Task 1 Traceability analysis Task 3 Interface analysis Task 5 Component V&V test plan generation Task 6 Integration V&V test plan generation Task 7 Component V&V test design generation Task 8 Integration V&V test design generation Task 9 System V&V test design generation Task 10 Acceptance V&V test design generation
	5.4.4 Activity: Implementation V&V Task 1 Traceability analysis Task 3 Interface analysis Task 5 Component V&V test case generation Task 6 Integration V&V test case generation Task 7 System V&V test case generation Task 8 Acceptance V&V test case generation Task 9 Component V&V test procedure generation Task 10 Integration V&V test procedure generation Task 11 System V&V test procedure generation Task 12 Component V&V test execution
	5.4.5 Activity: Test V&V Task 1 Traceability analysis Task 2 Acceptance V&V test procedure generation Task 3 Integration V&V test execution Task 4 System V&V test execution Task 5 Acceptance V&V test execution
	5.4.6 Activity: Installation and checkout V&V Task 1 Installation configuration audit Task 2 Installation checkout
Verification	All clauses
Validation	All clauses

CMMI process groups and areas	IEEE Std 1012 V&V activities and tasks (see corresponding clause)
Support	
Configuration management	5.1.1 Activity: Management of the V&V effort Task 2 Proposed/baseline change assessment Task 6 Identify improvement opportunities in the conduct of V&V
	5.4.1 Activity: Concept V&V Task 4 Traceability Analysis
	5.4.2 Activity: Requirements V&V Task 1 Traceability analysis Task 7 Configuration management assessment
	5.4.3 Activity: Design V&V Task 1 Traceability analysis
	5.4.4 Activity: Implementation V&V Task 1 Traceability analysis
	5.4.5 Activity: Test V&V Task 1 Traceability analysis
	5.4.6 Activity: Installation & Checkout V&V Task 1 Installation configuration audit
Process & product quality assurance	5.1.1 Activity: Management of the V&V effort Task 6 Identify improvement opportunities in the conduct of V&V
	Annex E V&V measures
	Annex F Relationship of V&V to other project responsibilities
Organizational environment for integration	Annex C Definition of independent V&V
ior modiation	Annex F Relationship of V&V to other project responsibilities

CMMI process groups and areas	IEEE Std 1012 V&V activities and tasks (see corresponding clause)
Decision analysis & resolution	5.1.1 Activity: Management of the V&V effort Task 2 Proposed/baseline change assessment
	5.4.1 Activity: Concept V&V Task 7 Risk analysis
	5.4.2 Activity: Requirements V&V Task 10 Risk analysis
	5.4.3 Activity: Design V&V Task 13 Risk analysis
	5.4.4 Activity: Implementation V&V Task 15 Risk analysis
	5.4.5 Activity: Test V&V Task 8 Risk analysis
	5.4.6 Activity: Installation and checkout V&V Task 5 Risk analysis
	5.5.1 Activity: Operation V&V Task 5 Risk analysis
	5.6.1 Activity: Maintenance V&V Task 8 Risk analysis
Causal analysis & resolution	5.1.1 Activity: Management of the V&V effort Task 6 Identify improvement opportunities in the conduct of V&V
	Annex E V&V measures
	Annex F Relationship of V&V to other project responsibilities

Annex B

(informative)

A risk-based software integrity level scheme

B.1 A risk-based software integrity level scheme

Table B.1 defines four software integrity levels used for reference purposes by this standard. Table B.2 describes the consequences of software errors for each of the four software integrity levels. There are overlaps between the software integrity levels to allow for individual interpretations of acceptable risk depending on the application.

Software integrity level	Description
4	An error to a function or system feature that causes: —catastrophic consequences to the system with reasonable, probable, or occasional likelihood of occurrence of an operating state that contributes to the error; or —critical consequences with reasonable or probable likelihood of occurrence of an operating
	state that contributes to the error.
3	An error to a function or system feature that causes: — catastrophic consequences with occasional or infrequent likelihood of occurrence of an oper- ating state that contributes to the error; or
	-marginal consequences with reasonable or probable likelihood of occurrence of an operating state that contributes to the error.
2	An error to a function or system feature that causes: —critical consequences with infrequent likelihood of occurrence of an operating state that con- tributes to the error; or
	-marginal consequences with probable or occasional likelihood of occurrence of an operating state that contributes to the error;
	 or —negligible consequences with reasonable or probable likelihood of occurrence of an operating state that contributes to the error.
1	An error to a function or system feature that causes: —critical consequences with infrequent likelihood of occurrence of an operating state that con- tributes to the error; or
	or —negligible consequences with probable, occasional, or infrequent likelihood of occurrence of an operating state that contributes to the error.

Table B.1—Assignment of software integrity levels

Consequence	Definitions
Catastrophic	Loss of human life, complete mission failure, loss of system security and safety, or extensive financial or social loss.
Critical	Major and permanent injury, partial loss of mission, major system damage, or major financial or social loss.
Marginal	Severe injury or illness, degradation of secondary mission, or some financial or social loss.
Negligible	Minor injury or illness, minor impact on system performance, or operator inconvenience.

Table B.2—Definition of consequences

Table B.3 illustrates the risk-based scheme shown in Table B.1 and Table B.2. Each cell in the table assigns a software integrity level based upon the combination of an error consequence and the likelihood of occurrence of an operating state that contributes to the error. Some table cells reflect more than one software integrity level, indicating that the final assignment of the software integrity level can be selected to address the system application and risk mitigation recommendations. For some industry applications, the definition of likelihood of occurrence categories may be expressed as probability figures derived by analysis or from system requirements.

Error	Likelihood of occurrence of an operating state that contributes to the error (decreasing order of likelihood)			
Consequence	Reasonable	Probable	Occasional	Infrequent
Catastrophic	4	4	4 or 3	3
Critical	4	4 or 3	3	2 or 1
Marginal	3	3 or 2	2 or 1	1
Negligible	2	2 or 1	1	1

Table B.3—Graphic illustration of the assignment of software integrity levels

Annex C

(informative)

Definition of independent V&V (IV&V)

IV&V is defined by three parameters: technical independence, managerial independence, and financial independence.

C.1 Technical independence

Technical independence requires the V&V effort to utilize personnel who are not involved in the development of the software. The IV&V effort should formulate its own understanding of the problem and how the proposed system is solving the problem. Technical independence ("fresh viewpoint") is an important method to detect subtle errors overlooked by those too close to the solution.

For software tools, technical independence means that the IV&V effort uses or develops its own set of test and analysis tools separate from the developer's tools. Sharing of tools is allowable for computer support environments (e.g., compilers, assemblers, utilities) or for system simulations where an independent version would be too costly. For shared tools, IV&V conducts qualification tests on tools to ensure that the common tools do not contain errors that may mask errors in the software being analyzed and tested. Off-the-shelf tools that have extensive history of use do not require qualification testing. The most important aspect for the use of these tools is to verify the input data used.

C.2 Managerial independence

This requires that the responsibility for the IV&V effort be vested in an organization separate from the development and program management organizations. Managerial independence also means that the IV&V effort independently selects the segments of the software and system to analyze and test, chooses the IV&V techniques, defines the schedule of IV&V activities, and selects the specific technical issues and problems to act upon. The IV&V effort provides its findings in a timely fashion simultaneously to both the development and program management organizations. The IV&V effort must be allowed to submit to program management the IV&V results, anomalies, and findings without any restrictions (e.g., without requiring prior approval from the development group) or adverse pressures, direct or indirect, from the development group.

C.3 Financial independence

This requires that control of the IV&V budget be vested in an organization independent of the development organization. This independence prevents situations where the IV&V effort cannot complete its analysis or test or deliver timely results because funds have been diverted or adverse financial pressures or influences have been exerted.

C.4 Forms of independence

The extent to which each of the three independence parameters (technical, managerial, financial) is vested in a V&V organization determines the degree of independence achieved.

Many forms of independence can be adopted for a V&V organization. The five most prevalent are: (1) classical, (2) modified, (3) integrated, (4) internal, and (5) embedded. Table C.1 illustrates the degree of independence achieved by these five forms.

IV&V Form	Technical	Management	Financial
Classical	Ι	Ι	Ι
Modified	Ι	i	Ι
Integrated	i	Ι	Ι
Internal	i	i	i
Embedded	e	e	e
NOTE—I = Rigorous independence; i = Conditional independence; e = Minimal independence			

Table C.1—Forms of IV&V

C.4.1 Classical IV&V

Classical IV&V embodies all three independence parameters. The IV&V responsibility is vested in an organization that is separate from the development organization. IV&V uses a close working relationship with the development organization to ensure that IV&V findings and recommendations are integrated rapidly back into the development process. Typically, classical IV&V is performed by one organization (e.g., supplier) and the development is performed by a separate organization (i.e., another vendor). Classical IV&V is generally required for software integrity level 4 (i.e., loss of life, loss of mission, significant social, or financial loss) through regulations and standards imposed on the system development.

C.4.2 Modified IV&V

Modified IV&V is used in many large programs where the system prime integrator is selected to manage the entire system development including the IV&V. The prime integrator selects organizations to assist in the development of the system and to perform the IV&V. In the modified IV&V form, the acquirer reduces its own acquisition time by passing this responsibility to the prime integrator. Since the prime integrator performs all or some of the development, the managerial independence is compromised by having the IV&V effort report to the prime integrator. Technical independence is preserved since the IV&V effort formulates an unbiased opinion of the system solution and uses an independent staff to perform the IV&V. Financial independence is preserved since a separate budget is set aside for the IV&V effort. Modified IV&V effort would be appropriate for systems with software integrity level 3 (i.e., an important mission and purpose).

C.4.3 Integrated IV&V

This form is focused on providing rapid feedback of V&V results into the development process and is performed by an organization that is financially and managerially independent of the development organization to minimize compromises with respect to independence. The rapid feedback of V&V results into the development process is facilitated by the integrated IV&V organization: working side-by-side with the development organization; reviewing interim work products; and providing V&V feedback during inspections, walk-throughs, and reviews conducted by the development staff (potential impact on technical independence). Impacts to technical independence are counterbalanced by benefits associated with a focus on interdependence between the integrated IV&V organization and the development organization.

Interdependence means that the successes of the organizations are closely coupled, ensuring that they work together in a cooperative fashion.

C.4.4 Internal IV&V

Internal IV&V exists when the developer conducts the IV&V with personnel from within its own organization, although preferably not the same personnel involved directly in the development effort. Technical, managerial, and financial independence are compromised. Technical independence is compromised because the IV&V analysis and test is vulnerable to overlooking errors by using the same assumptions or development environment that masked the error from the developers. Managerial independence is compromised because the internal IV&V effort uses the same common tools and corporate analysis procedures as the development group. Peer pressure from the development group may adversely influence how aggressively the software is analyzed and tested by the IV&V effort. Financial independence is compromised because the development group controls the IV&V budget. IV&V funds, resources, and schedules may be reduced as development pressures and needs redirect the IV&V funds into solving development problems. The benefit of an internal IV&V effort is access to staff who know the system and its software. This form of IV&V is used when the degree of independence is not explicitly stated and the benefits of preexisting staff knowledge outweigh the benefits of objectivity.

C.4.5 Embedded V&V

This form is similar to internal IV&V in that it uses personnel from the development organization who should not be involved directly in the development effort. Embedded V&V is focused on ensuring conformance to the development procedures and processes. The embedded V&V organization works sideby-side with the development organization and attends the same inspections, walk-throughs, and reviews as the development staff (i.e., compromise of technical independence). Embedded V&V is not tasked specifically to independently assess the original solution or conduct independent tests (i.e., compromise of managerial independence). Financial independence is compromised because the V&V staff resource assignments are controlled by the development group. Embedded V&V allows rapid feedback of V&V results into the development process but compromises the technical, managerial, and financial independence of the V&V organization.

Annex D

(informative)

V&V of reuse software

D.1 Purpose

The purpose of this annex is to provide options and suggestions to help the V&V effort of reuse software and to overcome the particular challenges associated with reuse software. Reuse software can take many forms and could include software from software libraries, custom software developed for other applications, COTS software, software requirements, software designs, or other artifacts from existing software. This annex addresses both (1) reuse software developed and used as part of a reuse process, and (2) reuse software developed and used outside of a reuse process. Figure D.1 illustrates V&V activities and tasks for reuse software whether it was developed under a reuse process or outside of a reuse process.



Figure D.1—V&V of reuse software

D.2 V&V of software developed in a reuse process

A structured software reuse process develops assets (e.g., design, code, and documentation) intended for use in multiple contexts. The software reuse processes of IEEE Std 1517-1999 [B11] provide a framework for extending the software life cycle processes of IEEE/EIA Std 12207.0-1996 [B12] to include a systematic, domain engineering process for software reuse. The domain scope and the domain analysis of an asset

provide requirements, intended use, interface parameters, and other information necessary for V&V of the asset, or an understanding of previously performed V&V of the asset.

D.2.1 V&V of assets in development

The V&V effort should analyze the artifacts (e.g., plans, models, architecture) of the domain engineering as part of the required V&V tasks. Significant analysis of the domain engineering products should occur during system requirements review, software requirements evaluation, interface analysis, software design evaluation, source code and source code documentation evaluation, and all test planning. The V&V effort must include the assignment of a software integrity level to the asset, in the context of the domain for its intended use, to determine the minimum V&V tasks to be performed (see Table 2). When planning the V&V effort, the optional task reusability analysis (see Annex G) should be included.

D.2.2 V&V of reused assets

A domain engineering process ensures that the information used in developing software systems is identified, captured, and organized so that it can be reused to create new systems within a domain. The V&V effort must include the assignment of a software integrity level to the asset, in the context of its actual use, to determine the minimum V&V tasks to be performed (see Table 2). When planning the V&V effort, the optional task reuse analysis (see Annex G) should be included.

D.3 V&V of software developed and reused outside of a reuse process

Some software systems are developed, operated, and maintained using software items that were not designed for use in multiple contexts or were not developed as part of a structured software reuse process (e.g., domain engineering products are not available). In these cases the V&V effort should perform the optional task reuse analysis (see Annex G) to produce inputs for determining the suitability of the reuse candidate software. The V&V effort must assign a software integrity level to the reuse candidate software to determine the minimum V&V tasks to be performed.

Reused software requires special consideration during the V&V effort when any one of the following is applicable:

- The inputs for a required V&V task are not available for the reused software.
- The reused software was developed as part of a system that is different in function or application from the system where it will be reused.
- The reused software was developed to meet different user needs from the current system.
- The original user needs are unknown.

In some cases, inputs for the V&V tasks may not be available, reducing visibility into the software products and processes. Options and techniques are available to compensate for the lack of inputs. Each technique has varying strengths and weaknesses—consideration should be given to performing multiple techniques to counter the weaknesses of one technique with strengths of another technique when high confidence is demanded. These options are addressed in decreasing order of desirability.

First, substitute tasks. Substitution for Table 1 V&V tasks is permitted if equivalent substitute V&V tasks can be shown to satisfy the same criteria as in Table 1. Two substitution task techniques are suggested in Table D.1.

Table D.1—Substitution tasks to establish V&V task inputs

Substitution tasks Description: Substitute alternative analysis and test me tasks to generate objective conclusions about the corre reused software.	ethods in lieu of the IEEE Std 1012 requirement V&V ctness, completeness, accuracy, and usability of the
Technique 1: Black box testing	Pros
<i>Black box testing and validation</i> : Execute the reused software against a spectrum of test case inputs and validate the correctness of the output.	 Test results reflect actual target software Limits catastrophic errors from propagating into interfacing systems
<i>User's manual analysis</i> : Derive system and software requirements from the user's manual and validate that the black box testing results satisfy the requirements.	 Ability to check the major system and user requirements derived from user's manual Independent analysis
<i>Limit checks in interfacing software</i> : Add limit checks within all interface software on all data and logical information received from the reused software to ensure that no erroneous information is accepted.	Cons — Inability to detect all test errors if presence of error not observable in black box outputs (e.g., latent errors) — Limit checks difficult to cover all execution scenarios — Limited by the thoroughness of the user's manual
Technique 2: Review developer's QA	Pros
<i>Developer's QA results</i> : Review developer's QA results and confirm the evidence of data similar to those that would be generated from V&V tasks.	 Ability to derive insight into the details of the software design and internal performance characteristics
<i>Developer's test results</i> : Review the developer's test results and confirm the evidence of data similar to those that would be generated from V&V tasks.	 Identification of possible program error charac- teristics warranting further analysis and testing by other methods
<i>Review of developer's notebook</i> : Review the developer's notebook to derive additional insights and problems with the software during early stages of development.	 Observations of program performance using test results reflecting actual software execution characteristics
<i>User's manual analysis</i> : Derive system and software requirements from the user's manual and validate that the developer's QA and test results satisfy the requirements.	Cons — Limited by the scope and extent of the QA analysis and the specific focus of the testing performed — Limited by the thoroughness of the user's
	manualNot a totally independent analysis

Second, use alternative sources of information to perform the V&V tasks in Table 1 and Table 2 of this standard. Three alternative source techniques are suggested in Table D.2.

Table D.2—Alternate sources to establish V&V task inputs

Alternative sources Description: Use alternative sources of program data to completeness, accuracy, and usability of the reused soft	o derive conclusions about the correctness, tware.
Technique 3: Operational history	Pros
<i>Historical Data Analysis</i> : Examine and analyze the oper- ational history of the reused software with particular attention to how the software performed in a system with similar characteristics to the new system being proposed. <i>User Interviews</i> : Conduct interviews with operational users. Focus data gathering on how the system per- formed in scenarios and conditions similar to those expected in the new system being proposed.	 Real data of the reused software in an operational environment User observations about the performance of the software and its related system Software burn-in established and track record of discrepancies recorded Independent analysis
expected in the new system being proposed.	Cons
	 Different characteristics, technologies, and user interfaces with new proposed system could cause error not observed in historical system
	 Not all interactions recordable or observable in historical systems so data completeness and accuracy are limited
	 User observations can be subjective, biased, and error-prone, so correctness, completeness, and accuracy may be limited
Technique 4: Audit results	Pros
<i>Developer's interview</i> : Conduct interviews with development team to extract pertinent information about the design and performance characteristics of the reused software.	 Depending on the thoroughness of the develop- ment team's records, good insight into the design and code approaches can be obtained from the interviews
<i>Design walk-through review analysis</i> : Analyze the design and code walkthrough data to determine how the reused software would interact in the new proposed system.	 Historical artifacts of design and code walk- throughs may be of sufficient quality to act as a substitute of the actual source code and design details
<i>Standard compliance analysis</i> : Review the results of any standards compliance audits to determine that the proper software standards were followed in the construction of the reused software.	Cons — Limited by the thoroughness of the development team's documentation and recollection during interviews
	 Not a totally independent analysis

Г

Alternative sources Description: Use alternative sources of program data t completeness, accuracy, and usability of the reused sof	o derive conclusions about the correctness, tware.
Technique 5: Artifacts	Pros
Product documentation analysis: Review any product documentation to derive artifacts similar to require- ments, design, and code [if possible—for example, if a pseudo design language (PDL) is used] <i>Prior V&V results analysis</i> : Analyze any prior V&V results and develop inferences and extrapolation of the data to the new proposed system.	Use actual artifacts representing some form of the reused software
	 Prior V&V results for an initial basis for formu- lating additional analysis and testing to conduct
	to fill in the analysis and testing voids caused by lack of program documentation
	— Independent analysis
	Cons
	— Overstating a conclusion without having a solid
	basis for knowing the system conditions could
	in the new proposed system and its different system conditions.
	 Limited by the thoroughness of the product documentation

Table D.2—Alternate sources to establish V&V task inputs (continued)

Third, use reverse engineering to generate inputs to perform the V&V tasks in Table 1 and Table 2 of this standard. One reverse engineering technique is suggested in Table D.3.

Table D.3—Reverse engineering to establish V&V task inputs

Reverse engineering Description: Reverse engineer requirements, design, and code data to generate objective conclusions about the correctness, completeness, accuracy, and usability of the reused software.			
Technique 6: Reverse compilation <i>Reverse engineer source code</i> : Reverse compile "pseudo source" code from the program object file. Analyze the reverse compiled pseudo code using normal V&V proce- dures including all the V&V test strategies and methods. <i>Reverse engineer requirements</i> : Derive the system and software requirements from the user's manual. Analyze the requirements using the IEEE Std 1012 V&V tasks and test the reused software against these reverse engi- neered requirements.	Pros — Uses the actual code—no hidden or implied data. — Perform all of the IEEE Std 1012 V&V tasks — Test data reflects actual performance of the reused software under the system conditions of the new proposed system — Independent analysis Cons — — Time consuming to reverse engineer data — Pseudo code hard to read		

Fourth, use independent prototyping and comparison of performance results with those of the reuse asset to perform the V&V tasks in Table 1 and Table 2 of this standard. Two independent prototyping and comparison techniques are suggested in Table D.4.

Table D.4—Independent prototyping and comparison to establish V&V task inputs

Independent prototyping and comparison Description: Develop a model (prototype) of the propose Execute test scenarios on the prototype or prior system software. Analyze the results to generate objective cond and usability of the reused software.	sed software or use portions of the prior system. and compare the test results against the reused clusions about the correctness, completeness, accuracy,
Technique 7: Prototyping	Pros
<i>Comparison of prototype code:</i> Develop a replication model (prototype) of the function or requirements in a user-friendly language. Execute test cases representing the range of system scenarios on both the model and reuse software. Compare the results and analyze the dif- ferences to determine whether the reused software is per- forming as intended.	 Useful for small functions and sets of requirements Easy to diagnose problems in the reused software Ability to run a wide range of system scenarios and compare against a benchmark program Independent analysis
	Cons — Cost and time of building the model — Errors in the model can mask similar errors in the reused software (likelihood of two similar errors generated by two independent sources should be small or unlikely)
Technique 8: Prior system results	Pros
<i>Comparison with prior system/function</i> : Execute test cases representing the range of system scenarios on the prior system/function and the reused software. Compare the results and analyze the differences to determine whether the reused software is performing as intended.	 Inexpensive to execute test cases on prior system and compare. Proven track record of performance of the prior system/function establishes a performance baseline Differences in execution results leads to other analysis and testing to be conducted Independent analysis
	Cons

Lastly, use a combination of the following circumstantial evidence that provides visibility and insight into the reused software to perform the V&V tasks in Table 1 and Table 2 of this standard:

- a) Operational history
- b) Test history
- c) Audit results
- d) User interviews
- e) Engineering judgment
- f) Product documentation
- g) Prior hazard analysis results
- h) Prior V&V results
- i) Software developer's notebook
- j) Design process documentation
- k) Original developers' interviews
- 1) Static code analysis results
- m) Standards compliance assessments

If V&V of reused software cannot be accomplished at the appropriate level, the items may be used so long as the risk associated with this use is recognized and accounted for in the risk mitigation strategy. The V&V effort should ensure that the risks are thoroughly understood, properly documented, and properly tracked under the risk analysis tasks.

Annex E

(informative)

V&V measures

E.1 Introduction

The management of V&V activity uses measures to provide feedback for the continuous improvement of the V&V process and to evaluate the software development processes and products. Trends can be identified and addressed by computing evaluation measures over a period of time. Threshold values of measures should be established and trends should be evaluated to serve as indicators as to whether a process, product, or V&V task has been satisfactorily accomplished. No standard set of measures is applicable for all projects, so the use of measures may vary according to the application domain and software development environment.

No consensus exists on measures for evaluating the quality and coverage of the V&V tasks. IEEE Std 1061[™]-1998 [B9] provides a standard definition of available software quality measures. Other measure-related standards and guides are IEEE Std 982.1-1988 [B5] and FP-05 Software Measurement [B1].

This standard considers three categories of measures associated with the V&V effort: (1) measures for evaluating anomaly density, (2) measures for assessing V&V effectiveness, and (3) measures for evaluating V&V efficiency.

E.2 Measures for evaluating anomaly density

Anomaly density measures can provide insightful information on the software product quality, the quality of the software development processes, and the quality of the V&V effort to discover anomalies in the system/ software and to facilitate correction of the anomalies. Anomaly density measures are influenced by numerous variables (e.g., software complexity, type of domain, and time-phase application of the V&V processes); consequently, the measures must be analyzed to gain insight into the interdependencies between the development efforts and the V&V efforts.

If the V&V anomaly density measure value is low, this suggests that the program development quality is high, that the V&V processes need to be improved, or a combination of both. If the measure value is high, then this suggests that the program development quality is low, that the V&V processes are effective, or a combination of both. Regardless of the measure value, the next step is to evaluate related software program development measures to further clarify and discern the measure trends to determine the need for process improvements.

Anomaly measures and trends can be used to improve the quality of the current project and can be used to improve the planning and execution of V&V processes for future projects with similar characteristics. The measures defined by Equation (E.1), Equation (E.2), Equation (E.3), and Equation (E.4) are applicable for four software development phases:

$$Requirements anomaly density = \frac{\# Requirements anomalies found by V\&V effort}{\# Requirements reviewed by V\&V effort}$$
(E.1)

$$Design anomaly density = \frac{\# Design statement anomalies found by V\&V effort}{\# Design statements reviewed by V\&V effort}$$
(E.2)

$$Code anomaly density = \frac{\# Code anomalies found by V\&V effort}{\# Code volume reviewed by V\&V effort}$$
(E.3)

$$Test anomaly density = \frac{\# Test anomalies found by V\&V effort}{\# Tests reviewed by V\&V effort}$$
(E.4)

E.3 Measures for evaluating V&V effectiveness

Measures associated with V&V effort effectiveness provide quantitative indications that characterize the added benefits of V&V to discover anomalies in software products and processes. These measures delineate the percentage of the total anomalies found by the V&V effort. The measures are influenced by numerous variables (e.g., software complexity), and the measures must be analyzed to gain insight into the interdependencies between the development efforts and the V&V efforts.

The V&V effectiveness measure values are highly influenced by the degree of parallelism between the software development effort and the V&V effort. Assuming that the efforts are parallel, then a low V&V effectiveness measure value suggests that the software development effort is effective, or that the V&V effort may require improvement, or a combination of both. If the V&V effectiveness measure value is high, then this suggests that the software development processes may require improvement, or that only incremental changes to the V&V processes may be required. Regardless of the measure value, the next step is to evaluate related software program development measures to further clarify and discern the measure trends to determine the need for process improvements. The measures defined by Equation (E.5), Equation (E.6), Equation (E.7), and Equation (E.8) are applicable for four software development phases:

$$Requirements \ V \& V \ effectiveness \ = \ \frac{\# \ Requirement \ anomalies \ found \ by \ V \& V \ effort}{\# \ Requirements \ anomalies \ found \ by \ all \ sources}$$
(E.5)

$$Design \ V \& V \ effectiveness \ = \ \frac{\# \ Design \ statement \ anomalies \ found \ by \ V \& V \ effort}{\# \ Design \ statement \ anomalies \ found \ by \ all \ sources}$$
(E.6)

$$Code \ V \& V \ effectiveness \ = \ \frac{\# \ Code \ anomalies \ found \ by \ V \& V \ effort}{\# \ Code \ anomalies \ found \ by \ all \ sources}$$
(E.7)

$$Test \ execution \ V \& V \ effectiveness \ = \ \frac{\# \ Test \ anomalies \ found \ by \ V \& V \ effort}{\# \ Test \ anomalies \ found \ by \ all \ sources}$$
(E.8)

E.4 Measures for evaluating V&V efficiency

Measures associated with V&V effort efficiency provide data that characterize the capability of the V&V effort to discover anomalies in software products and processes in the development activity in which they are injected. Maximum benefits are realized when software anomalies are discovered as early as possible in the development life cycle, thereby minimizing rework and development costs. Analysis of these measures, the anomalies, and the causal factors that prevented discovery of the anomaly in the phase in which it was injected can reveal needed improvements in methods, processes, tools, and skills to improve the overall V&V effort.

A low V&V efficiency measure value suggests that the software V&V effort is not discovering anomalies in the earliest possible activity, or that the software development products are immature, or a combination of both. If the V&V efficiency measure value is high, then this suggests that the V&V effort is discovering anomalies in the earliest possible activity, or that the software development products are mature, or a

combination of both. Regardless of the measure value, the next step is to evaluate related software program development measures to further clarify and discern the measure trends to determine the need for process improvements. The measures defined by Equation (E.9), Equation (E.10), Equation (E.11), and Equation (E.12) are applicable for four software development phases:

$$\# Requirements anomalies found by V\&V$$
(E.9)

$$RequirementsV\&V efficiency = \frac{in requirements activity}{\# Requirements anomalies found by V\&V in all activities} \times 100\%$$
(E.9)

$$Design V\&V efficiency = \frac{\# Design statement anomalies found by V\&V in design activity}{\# Design statement anomalies found by V\&V in all activities} \times 100\%$$
(E.10)

$$V\&V efficiency = \frac{\# Code anomalies found by V\&V in implementation activity}{\# Code anomalies found by V\&V in all activities} \times 100\%$$
(E.11)

$$V\&V efficiency = \frac{\# Test \ statement \ anomalies \ found \ by \ V\&V \ in \ test \ activity}{\# Test \ anomalies \ found \ by \ V\&V \ in \ all \ activities} \times 100\%$$
(E.12)

Annex F

(informative)

Example of V&V organizational relationship to other project responsibilities

F.1 V&V organizational relationships

Figure F.1 provides an example of organizational relationships among the V&V team, the acquirer and the supplier, and identifies the information and data flows throughout the V&V effort. Many other organizational relationships will work well as long as project responsibilities, data flows, and reporting flows are defined and documented.



Figure F.1—Relationship of V&V to other project responsibilities

NOTE—The lines in Figure F.1 represent the flow of control and data as follows:

A: Submittal of program documentation (e.g., concept, requirements, design, users manuals), source code, program status, program budgets, and developmental plans and schedules.

B: Approval, denial, and recommendations on development issues and deliverables listed in A.

C: Submittal of SVVP, V&V task results, anomaly reports, activity reports, and other special reports.

D: Approval, denial, and recommendations on V&V issues and deliverables listed in C.

E: Submittal of V&V task results, anomaly reports, activity reports, and special reports as directed by the acquirer program management.

F: Submittal of program documentation (e.g., concept, requirements, design, users manuals, special reports, source code, and program schedules).

*: The quality assurance staff may report directly to the Quality Assurance Director rather than through the development organization.

Annex G

(informative)

Optional V&V tasks

Algorithm analysis. Verify the correct implementation of algorithms, equations, mathematical formulations, or expressions. Rederive any significant algorithms and equations from basic principles and theories. Compare against established references or proven past historical data. Validate the algorithms, equations, mathematical formulations, or expressions with respect to the system and software requirements. Ensure that the algorithms and equations are appropriate for the problem solution. Validate the correctness of any constraints or limitations, such as rounding, truncation, expression simplifications, best-fit estimations, and nonlinear solutions imposed by the algorithms and equations.

Audit performance. Provide an independent assessment of whether a software process and its products conform to applicable regulations, standards, plans, procedures, specifications, and guidelines. Audits may be applied to any software process or product at any development stage. Audits may be initiated by the supplier, the acquirer, the developer, or other involved party such as a regulatory agency. The initiator of the audit selects the audit team and determines the degree of independence required. The initiator of the audit and the audit team leader establish the purpose, scope, plan, and reporting requirements for the audit.

The auditors collect sufficient evidence to decide whether the software processes and products meet the evaluation criteria. They identify major deviations, assess risk to quality, schedule, and cost, and report their findings. Examples of processes that could be audited include configuration management practices, use of software tools, degree of integration of the various software engineering disciplines particularly in developing an architecture, security issues, training, and project management.

Audit support. Provide technical expertise to the auditors on request. They may represent the acquirer at audit proceedings and may assist in the V&V of remedial activities identified by the audit.

Control flow analysis. Assess the correctness of the software by diagramming the logical control. Examine the flow of the logic to identify missing, incomplete, or inaccurate requirements. Validate whether the flow of control among the functions represents a correct solution to the problem.

Cost analysis. Evaluate the cost status of the development processes. Compare budgeted costs against actual costs. Correlate cost expenditures with technical status and schedule progress. Identify program risks if actual costs indicate behind schedule and over cost estimates.

Database analysis. Evaluation of database design as part of a design review process could include

- a) Physical limitations analysis. Identify the physical limitations of the database, such as maximum number of records, maximum record length, largest numeric value, smallest numeric value, and maximum array length in a data structure and compare them to designed values.
- b) Index vs. storage analysis. Analyze the use of multiple indexes compared to the volume of stored data to determine if the proposed approach meets the requirements for data retrieval performance and size constraints.
- c) Data structures analysis. Some database management systems have specific data structures within a record, such as arrays, tables, and date formats. Review the use of these structures for potential impact on requirements for data storage and retrieval.
- d) Backup and disaster recovery analysis. Review the methods employed for backup against the requirements for data recovery and system disaster recovery and identify deficiencies.

Data flow analysis. Evaluation of data flow diagrams as part of a design review process could include

- a) Symbology consistency check. The various methods used to depict data flow diagrams employ very specific symbology to represent the actions performed. Verify that each symbol is used consistently.
- b) Flow balancing. Compare the output data from each process to the data inputs and the data derived within the process to ensure the data is available when required. This process does not specifically examine timing or sequence considerations.
- c) Confirmation of derived data. Examine the data derived within a process for correctness and format. Data designed to be entered into a process by operator action should be confirmed to ensure availability.
- d) Keys to index comparison. Compare the data keys used to retrieve data from data stores within a process to the database index design to confirm that no invalid keys have been used and the uniqueness properties are consistent.

Disaster recovery plan assessment. Verify that the disaster recovery plan is adequate to restore critical operation of the system in the case of an extended system outage. The disaster recovery plan should include the following:

- a) Identification of the disaster recovery team and a contact list
- b) Recovery operation procedures
- c) Procedure for establishing an alternative site including voice and data communications, mail, and support equipment
- d) Plans for replacement of computer equipment
- e) Establishment of a system backup schedule
- f) Procedures for storage and retrieval of software, data, documentation, and vital records off-site
- g) Logistics of moving staff, data, documentation, etc.

Distributed architecture assessment. Assess the distribution of data and processes in the proposed architecture for feasibility, timing conflicts, availability of telecommunications, cost, backup and restore features, downtime, system degradation, and provisions for installation of software updates.

Feasibility study evaluation. Verify that the feasibility study is correct, accurate, and complete. Validate that all logical and physical assumptions (e.g., physical models, business rules, logical processes), constraints, and user requirements are satisfied.

Independent risk assessment. Conduct an independent risk assessment on any aspect of the software project and report on the findings. Such risk assessments will be primarily from a system perspective. Examples of risk assessment include: appropriateness of the selected development methodology or tools for the project; and quality risks associated with proposed development schedule alternatives.

Inspection. Inspect the software products to detect defects in the product at each selected development stage to assure the quality of the emerging software. The inspection process may consist of multiple steps for the segregation of the inspection functions of the following:

- a) Inspection planning
- b) Product overview
- c) Inspection preparation
- d) Examination meeting
- e) Defect rework
- f) Resolution follow-up

An inspection is performed by a small team of peer developers and includes but is not led by the author. The inspection team usually consists of three to six persons, and in some cases includes personnel from the test

group, quality assurance, or V&V. The participants assume specific roles to find, classify, report, and analyze defects in the product. Each type of inspection is specifically defined by its intended purpose, required entry criteria, defect classification, checklists, exit criteria, designated participants, and its preparation and examination procedures. Inspections do not debate engineering judgments, suggest corrections, or educate project members; they detect anomalies and problems and verify their resolution by the author.

Inspection (concept). Validate that the system architecture and requirements satisfy customer needs. Verify that the system requirements are complete and correct, and that omissions, defects, and ambiguities in the requirements are detected.

Inspections (design). Verify that the design can be implemented, is traceable to the requirements, and that all interface and procedural logic is complete and correct, and that omissions, defects, and ambiguities in the design are detected.

Inspections (requirements). Validate that the requirements meet customer needs and can be implemented. Verify that they are complete, traceable, testable, and consistent so that omissions, defects, and ambiguities in the requirements are detected.

Inspection (source code). Verify that the source code implementation is traceable to the design, and that all interfaces and procedural logic are complete and correct, and that omissions, defects, and ambiguities in the source code are detected.

Inspection—Test case (component, integration, system, acceptance). Verify that the (component, integration, system, acceptance) test plan has been followed accurately, that the set of component test cases is complete, and that all component test cases are correct.

Inspection—Test design (component, integration, system, acceptance). Verify that the (component, integration, system, acceptance) test design is consistent with the test plan, and that the test design is correct, complete, and readable.

Inspection—Test plan (component, integration, system, acceptance). Verify that the scope, strategy, resources, and schedule of the (component, integration, system, acceptance) testing process have been completely and accurately specified, that all items to be tested and all required tasks to be performed have been defined, and to ensure that all personnel and resources necessary to perform the testing have been identified.

Operational evaluation. Assess the deployment readiness and operational readiness of the software. Operational evaluation may include examining the results of operational tests, audit reviews, and anomaly reports. This evaluation verifies that the software is

- a) At a suitable point of correctness for mass production of that software
- b) Valid and correct for site specific configurations

Performance monitoring. Collect information on the performance of software under operational conditions. Determine whether system and software performance requirements are satisfied. Performance monitoring is a continual process and may include evaluation of the following items:

- a) Database transaction rates to determine the need to reorganize or re-index the database
- b) CPU performance monitoring for load balancing
- c) Direct access storage utilization
- d) Network traffic to ensure adequate bandwidth
- e) Critical outputs of a system (e.g., scheduled frequency, expected range of values, scheduled system reports, reports of events)

Post installation validation. Execute a reference benchmark or periodic test for critical software when reliability is crucial or there is a possibility of software corruption. By automatically or manually comparing results with the established benchmark results, the system can be validated prior to each execution of the software. When pre-use benchmark testing is impractical, such as for real time, process control, and emergency-use software, a periodic test, conducted at a predetermined interval, can be used to ensure continued reliability.

Project management oversight support. Assess project development status for technical and management issues, risks, and problems. Coordinate oversight assessment with the acquirer and development organization. Evaluate project plans, schedules, development processes, and status. Collect, analyze, and report on key project measures.

Proposal evaluation support. Participate in the development organization source selection process. Develop proposal evaluation factors and assessment criteria. Independently evaluate development organization proposals to assess conformance to the statement of work and performance requirements.

Qualification testing. Verify that all software requirements are tested according to qualification testing requirements demonstrating the feasibility of the software for operation and maintenance. Conduct as necessary any tests to verify and validate the correctness, accuracy, and completeness of the qualification testing results. Document the qualification test results together with the expected qualification test results. Planning for qualification testing may begin during the Requirements V&V activity.

Regression analysis and testing. Determine the extent of V&V analyses and tests that must be repeated when changes are made to any previously examined software products. Assess the nature of the change to determine potential ripple or side effects and impacts on other aspects of the system. Rerun test cases based on changes, error corrections, and impact assessment, to detect errors spawned by software modifications.

Reusability analysis. Verify that the artifacts (products) of the domain engineering process conform to project-defined purpose, format, and content (e.g., IEEE Std 1517-1999 [B11]). Verify that the domain models and domain architecture are correct, consistent, complete, accurate, and conform to the domain engineering plan. Analyze the asset (software item intended for reuse) to verify that the asset is consistent with the domain model and domain architecture.

Reuse analysis. Analyze the developer's documentation to verify that the original domain of the candidate reuse software will satisfy the domain of the new system (e.g. software integrity level, user needs, operating environment, safety, security, and interfaces). If the developer has performed no domain analysis, perform domain analysis (see IEEE Std 1517-1999 [B11]) to compare the original domain and the new domain of the candidate reuse software. Verify that developer reuse planning dispositions and document all domain differences.

Simulation analysis. Use a simulation to exercise the software or portions of the software to measure the performance of the software against predefined conditions and events. The simulation can take the form of a manual walk-through of the software against specific program values and inputs. The simulation can also be another software program that provides the inputs and simulation of the environment to the software under examination. Simulation analysis is used to examine critical performance and response time requirements or the software's response to abnormal events and conditions.

Sizing and timing analysis. Collect and analyze data about the software functions and resource utilization to determine if system and software requirements for speed and capacity are satisfied. The types of software functions and resource utilization issues include, but are not limited to

- a) CPU load
- b) Random access memory and secondary storage (e.g. disk, tape) utilization

- c) Network speed and capacity
- d) Input and output speed

Sizing and timing analysis is started at software design and iterated through acceptance testing.

System software assessment. Assess system software (e.g., operating system, computer aided software engineering tools, database management system, repository, telecommunications software, graphical user interface) for feasibility, impact on performance and functional requirements, maturity, supportability, adherence to standards, developer's knowledge of and experience with the system software and hardware, and software interface requirements.

Test certification. Certify the test results by verifying that the tests were conducted using baseline requirements, a configuration control process, and repeatable tests, and by witnessing the tests. Certification may be accomplished at a software configuration item level or at a system level.

Test evaluation. Evaluate the tests for requirements coverage and test completeness. Assess coverage by assessing the extent of the software exercised. Assess test completeness by determining if the set of inputs used during test are a fair representative sample from the set of all possible inputs to the software. Assess whether test inputs include boundary condition inputs, rarely encountered inputs, and invalid inputs. For some software it may be necessary to have a set of sequential or simultaneous inputs on one or several processors to test the software adequately.

Test witnessing. Monitor the fidelity of test execution to the specified test procedures and witness the recording of test results. When a test failure occurs, the testing process can be continued by: (1) implementing a "work around" to the failure; (2) inserting a temporary code patch; or (3) halting the testing process and implementing a software repair. In all cases, assess the test continuation process for test process breakage (e.g., some software is not tested or a patch is left in place permanently), adverse impact on other tests, and loss of configuration control. Regression analysis and testing should be done for all the software affected by the test failure.

Training documentation evaluation. Evaluate the training materials and procedures for completeness, correctness, readability, and effectiveness.

Usability analysis. Verify that stakeholder needs and interests are considered during development, operation, and maintenance process activities. The analysis will ensure that: human-centered design activities are performed; human factors and ergonomics considerations are incorporated into the design, potential adverse effects on human health and safety are addressed in the design; and user needs are satisfied in a manner that supports user effectiveness and efficiency.

User documentation evaluation. Evaluate the user documentation for its completeness, correctness, and consistency with respect to requirements for user interface and for any functionality that can be invoked by the user. The review of the user documentation for its readability and effectiveness should include representative end users who are unfamiliar with the software. Employ the user documentation in planning an acceptance test that is representative of the operational environment.

User training. Assure that the user training includes rules that are specific to the administrative, operational and application aspects, and industry standards for that system. This training should be based on the technical user documentation and procedures provided by the manufacturer of the system. The organization responsible for the use of the system should be responsible for providing appropriate user training.

V&V tool plan generation. Prepare a plan that describes the tools needed to support the V&V effort. The plan includes a description of each tool's performance, required inputs and associated tools, outputs generated, need date, and cost of tool purchase or development. The tool plan should also describe test

facilities and integration and system test laboratories supporting the V&V effort. The scope and rigor of the V&V effort as defined by the selected software integrity level should be considered in defining the performance required of each tool.

Walk-through. Participate in the evaluation processes in which development personnel lead others through a structured examination of a product. Ensure that the participants are qualified to examine the products and are not subject to undue influence. See specific descriptions of the requirement walk-through, design walk-through, source code walk-through, and test walk-through.

Walk-through (design). Participate in a walk-through of the design and updates of the design to ensure completeness, correctness, technical integrity, and quality.

Walk-through (requirements). Participate in a walk-through of the requirements specification to ensure that the software requirements are correct, unambiguous, complete, verifiable, consistent, modifiable, traceable, testable, and usable throughout the life cycle.

Walk-through (source code). Participate in a walk-through of the source code to ensure that the code is complete, correct, maintainable, free from logic errors, conforms to coding standards and conventions, and will operate efficiently.

Walk-through (test). Participate in a walk-through of the test documentation to ensure that the planned testing is correct, complete, and that the test results will be correctly analyzed.

Annex H

(informative)

Bibliography

[B1] FP-05 Software Measurement, IEEE Computer Society Software and Systems Engineering Standards Committee Policy.⁴

[B2] IEEE 100, The Authoritative Dictionary of IEEE Standards Terms, Seventh Edition.^{5,6}

[B3] IEEE Std 610.12-1990 (Reaff 2002), IEEE Standard Glossary of Software Engineering Terminology.

[B4] IEEE Std 829-1998, IEEE Standard for Software Test Documentation.

[B5] IEEE Std 982.1-1988, IEEE Standard Dictionary of Measures to Produce Reliable Software.

[B6] IEEE Std 1012A[™]-1998, Supplement to IEEE Standard for Software Verification and Validation: Content Map to IEEE/EIA 12207.1-1997.

[B7] IEEE Std 1028-1997, IEEE Standard for Software Reviews.

[B8] IEEE Std 1044-1993, IEEE Standard for Software Anomalies.

[B9] IEEE Std 1061-1998, IEEE Standard for a Software Quality Metrics Methodology.

[B10] IEEE Std 1074-1997, IEEE Standard for Developing Software Life Cycle Processes.

[B11] IEEE Std 1517-1999, IEEE Standard for Information Technology—Software Life Cycle Processes— Reuse Processes.

[B12] IEEE/EIA Std 12207.0-1996, IEEE/EIA Standard—Industry Implementation of International Standard ISO/IEC 12207:1995 (ISO/IEC 12207) Standard for Information Technology—Software Life Cycle Processes.

[B13] ISO/IEC 12207:1995, Information Technology—Software Life Cycle Processes; as amended by Amendment 1:2002.⁷

⁴This publication can be found at http://standards.computer.org/s2esc/s2esc_pols/FP-05_Software_Measurement.htm.

⁵IEEE publications are available from the Institute of Electrical and Electronics Engineers, Inc., 445 Hoes Lane, Piscataway, NJ 08854, USA (http://standards.ieee.org/).

⁶The IEEE standards or products referred to in this clause are trademarks of the Institute of Electrical and Electronics Engineers, Inc. ⁷ISO/IEC publications are available from the ISO Central Secretariat, Case Postale 56, 1 rue de Varembé, CH-1211, Genève 20, Switzerland/Suisse (http://www.iso.ch/). ISO/IEC publications are also available in the United States from Global Engineering Documents, 15 Inverness Way East, Englewood, CO 80112, USA (http://global.ihs.com/). Electronic copies are available in the United States from the American National Standards Institute, 25 West 43rd Street, 4th Floor, New York, NY 10036, USA (http://www.ansi.org/).